


CERTIFICATION AND CLASSIFICATION		Force	
Type of flooring	EN ISO 26986	Expanded (cushioned) polyvinyl chloride floor covering	
CE certification	EN 14041:2004/AC:2006	2701-0071-DoP-2021-11	
Classification	ISO 10874 (EN 685)		Residential: 23 Commercial: 33
TECHNICAL CHARACTERISTICS		STANDARD	
Extreme protection PUR reinforcement		yes	
Total thickness	ISO 24346 (EN 428)		2,50 mm
Wear layer thickness	ISO 24340 (EN 429)		0,60 mm
Total weight	ISO 23997 (EN 430)		2,5 kg/m ²
Form of delivery - Rolls	ISO 24341 (EN 426)		30 lm (15-30lm) x 2,5/3m 25 lm (15-25lm) x 3,5m 22 lm (15-22lm) x 4m
Wear layer binder content	ISO 11638	Type I	
TECHNICAL PERFORMANCES		STANDARD	
Dimensional stability	ISO 23999 (EN 434)		Requirement by standard: < 0,4 % Tarkett result: ≤ 10,011 %
Reaction to fire	EN 13501-1		Bfl - s1
Residual indentation	ISO 24343-1 (EN 433)		≤ 0,20 mm
Impact sound reduction	ISO 717/2		10 dB
Underfloor heating			Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance	EN ISO 846/2019	Does not contribute to infection spreading	
Castor chair test	ISO 4918 (EN 425)		Excellent
Light fastness	ISO 105 B02 - Method 3	≥ 6	
Thermal resistance	EN 12524	0,03-0,04 m²K/W	
Static electrical propensity	EN 1815	≤ 2 kV (antistatic)	



Manufactured by:
Tarkett d.o.o. Bačka
Palanka
Industrijska zona 14
21400 Bačka Palanka
SERBIA