

SOFAR 3.3K~12KTLX-G3

3.3 / 4.4 / 5.5 / 6.6 / 8.8 / 11 / 10 / 12 kW

THREE-PHASE DUAL MPPT



Product advantages

- Maximum efficiency 98.6%
- Low start-up voltage, wide MPPT voltage
- Maximum DC input voltage 1100 V
- Smart string level monitoring
- Remote firmware upgrade
- Natural cooling, no fans, low noise
- Type II SPD for both DC and AC side




Datasheet	SOFAR 3.3KTLX-G3	SOFAR 4.4KTLX-G3	SOFAR 5.5KTLX-G3	SOFAR 6.6KTLX-G3	SOFAR 8.8KTLX-G3	SOFAR 11KTLX-G3	SOFAR 10KTLX-G3-A	SOFAR 12KTLX-G3
Input (DC)								
Max. input voltage	1100V							
Rated input voltage	650V							
Start-up voltage	160V							
MPPT operating voltage range	140V-1000V							
Number of MPPTs	2							
Number of DC inputs	1/1				1/2			
Max. input MPPT current	15A/15A				15A/30A			
Max. input short circuit current	22.5A/22.5A				22.5A/45A			
Output (AC)								
Rated output power	3000W	4000W	5000W	6000W	8000W	10000W	10000W	12000W
Max. apparent power	3300VA	4400VA	5500VA	6600VA	8800VA	11000VA	10000VA	13200VA
Max. output current	5A	6.7A	8.3A	10A	13.3A	16.7A	15.2A	20A
Rated output voltage	3/N/PE, 230/400Vac							
Output voltage range	310Vac-480Vac							
Rated output frequency	50/60Hz							
Output frequency range	45Hz-55Hz/55Hz-65Hz							
Active power adjustable range	0-100%							
THDi	<3%							
Power factor	1 (adjustable+/-0.8)							
Efficiency								
Max. efficiency	98.40%	98.40%	98.40%	98.40%	98.50%	98.50%	98.50%	98.50%
European efficiency	97.50%	97.50%	97.50%	97.50%	98.00%	98.00%	98.00%	98.00%
Protection								
DC reverse polarity protection	Yes							
Anti-islanding protection	Yes							
Leakage current protection	Yes							
Ground fault monitoring	Yes							
PV-array string fault monitoring	Yes							
DC switch	Yes							
SPD	PV: type II, AC: type II							
General Data								
Ambient temperature range	-30℃--+60℃							
Self-consumption at night	<1W							
Topology	Transformerless							
Degree of protection	IP65							
Allowable relative humidity range	0-100%							
Max. operating altitude	4000m							
Cooling	Natural							
Dimension (W×H×D)	430×385×182mm							
Weight	17kg					18kg		
Display	LCD & Bluetooth +APP							
Communication	RS485/WiFi							
Standard	IEC/EN 61000-6-1/3, IEC/EN 61000-3-2/3, IEC/EN 61000-3-11/12, IEC 62116, IEC 61727, IEC 61683, IEC 60068-1/2/14/30, IEC/EN 62109-1/2, G98/C99, CEI0-21, VDE-AR-N 4105, VDE V 0126-1-1, EN 50549-1, UNE 217002-2020							


*All specifications are subject to change without notice.

Certificate of Conformity

Certificate Number: CN-PV-210111

On the basis of the tests undertaken, the samples of the below product have been found to comply with the requirements of the referenced specifications /standards at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture. The manufacturer shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant Name & Address:	Shenzhen SOFARSOLAR Co., Ltd. 401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen, China
Product Description:	Anti-backflow system
Ratings & Principle Characteristics:	See Annex to Certificate of Conformity
Models/Type References:	SOFAR 3.3KTLX-G3, SOFAR 4.4KTLX-G3, SOFAR 5KTLX-G3-A SOFAR 5.5KTLX-G3, SOFAR 6.6KTLX-G3, SOFAR 8.8KTLX-G3, SOFAR 8.8KTLX-G3-A, SOFAR 11KTLX-G3, SOFAR 10KTLX-G3-A SOFAR 11KTLX-G3-A, SOFAR 12KTLX-G3
Brand Name:	
Specification/Standard:	UNE 217001 IN: October 2020 Tests for systems that avoid the discharge of energy to the distribution network
Certificate Issuing Office Name & Address:	Intertek Testing Services Ltd. Shanghai West Area, 2nd Floor, No. 707, Zhangyang Road China (Shanghai) Pilot Free Trade Zone, Shanghai, P. R. China
Test Report Number:	210416108GZU-015
Additional information in Appendix.	



Signature

Certification Manager: Grady Ye

Date: 17 May 2021

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210111

MODEL	SOFAR 3.3KTLX-G3	SOFAR 4.4KTLX-G3	SOFAR 5KTLX-G3-A	SOFAR 5.5KTLX-G3
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15/15A			
PV Isc	22.5/22.5A			
Rated power(W)	3000	4000	5000	5000
Max.apparent power (VA)	3300	4400	5000	5500
Max output current	3×5.0 A	3×6.7 A	3×7.6 A	3×8.3 A
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency	50 Hz			
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	-30°C - +60°C			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210111

MODEL	SOFAR 6.6KTLX-G3	SOFAR 8.8KTLX-G3	SOFAR 8.8KTLX-G3-A	SOFAR 10KTLX-G3-A
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15/15A		15/30A	
PV Isc	22.5/22.5A		22.5A/45A	
Rated power(W)	6000	8000	8000	10000
Max.apparent power (VA)	6600	8800	8800	10000
Max output current	3×10.0 A	3×13.3 A	3×13.3 A	3×15.2 A
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency	50 Hz			
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	-30℃ - +60℃			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210111

MODEL	SOFAR 11KTLX-G3	SOFAR 11KTLX-G3-A	SOFAR 12KTLX-G3
Max PV voltage	1100Vdc		
MPPT Voltage range	140-1000Vdc		
Max. input current	15A/15A	15A/30A	
PV Isc	22.5/22.5A	22.5A/45A	
Rated power(W)	10000	10000	12000
Max.apparent power (VA)	11000	11000	13200
Max output current	3×16.7 A	3×16.7 A	3×20.0 A
Output voltage	3W/N/PE 230Vac/400Vac		
Nominal Frequency	50 Hz		
Power Factor	1 default (adjustable+/-0.8)		
Ambient Temperature	-30°C - +60°C		
Protection Degree	IP65		
Protection Class	Class I		
Software Version	V000001		

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.