

## Bio Mount HM

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Code: 05-BMHM508  
Product name: Bio Mount HM

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: In vitro medical-diagnostic disposable. Reagent for microscopy.

## 1.3. Details of the supplier of the safety data sheet

Name: BIO-OPTICA MILANO SPA  
Full address: via San Faustino, 58  
District and Country: 20134 Milano (MI)  
Italia  
Tel. 0039 02 2127131  
Fax 0039 02 2153000

e-mail address of the competent person responsible for the Safety Data Sheet: info@bio-stain.it

Product distribution by: Bio-Optica Milano S.p.a.

## 1.4. Emergency telephone number

For urgent inquiries refer to: Please contact the nearest Tossicology and Antivenin Center

## SECTION 2. Hazards identification

## 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Acute toxicity, category 4	H312	Harmful in contact with skin.
Acute toxicity, category 4	H332	Harmful if inhaled.
Skin irritation, category 2	H315	Causes skin irritation.

## 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H226	Flammable liquid and vapour.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.

Precautionary statements:

## Bio Mount HM

## SECTION 2. Hazards identification ... / &gt;&gt;

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P370+P378** In case of fire: use . . . to extinguish.  
**P261** Avoid breathing dust / fume / gas / mist / vapours / spray.

**Contains:** XYLENE (MIXTURE OF ISOMERS)

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients

## 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>XYLENE (MIXTURE OF ISOMERS)</b>		
CAS	1330-20-7      55 ≤ x < 60	<b>Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C</b>
EC	215-535-7	
INDEX	601-022-00-9	
<b>ETHYL ACETATE</b>		
CAS	141-78-6      5 ≤ x < 10	<b>Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066</b>
EC	205-500-4	
INDEX	607-022-00-5	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

## 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.  
**SKIN:** Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.  
**INHALATION:** Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.  
**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

## 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

## 5.1. Extinguishing media

## SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

## UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

## 5.2. Special hazards arising from the substance or mixture

## HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

## Bio Mount HM

## SECTION 5. Firefighting measures ... / &gt;&gt;

## 5.3. Advice for firefighters

## GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

## SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

## 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

## 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

## 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

## 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

## 7.3. Specific end use(s)

Information not available

## Bio Mount HM

## SECTION 8. Exposure controls/personal protection

## 8.1. Control parameters

## Regulatory References:

DEU	Deutschland	TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Graensevaerdier per stoffer og materialer
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2017
FIN	Suomi	HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveystieteiden tutkimuskeskus julkaisu 2012:5
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
HUN	Magyarország	50/2011. (XII. 22.) NGM rendelet a munkahelyek kémiai biztonságáról
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Council of Netherlands (SER) Values, AF 2011:18
NOR	Norge	Veiledning om Administrative normer for forurensning i arbeidsatmosfære
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZIN Y, PRAC Y I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República I 26; 2012-02-06
ROU	România	Monitorul Oficial al României 44; 2012-01-19
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18
TUR	Türkiye	KİMYASAL MADDELERLE ÇALIŞMALARDA SAĞLIK VE GÜVENLİK ÖNLEMLERİ HAKKINDA YÖNETMELİK - Resmi Gazete Tarihi: 12.08.2013 Resmi Gazete Sayısı: 28733
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2018

## XYLENE (MIXTURE OF ISOMERS)

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
HTP	FIN	220	50	440	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
TLV	GRC	435	100	650	150	
AK	HUN	221		442		SKIN
VLEP	ITA	221	50	442	100	SKIN
OEL	NLD	210		442		SKIN
TLV	NOR	108	25			SKIN
NDS	POL	100				
VLE	PRT	221	50	442	100	SKIN
TLV	ROU	221	50	442	100	SKIN
MAK	SWE	221	50	442	100	SKIN
ESD	TUR	221	50	442	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

## Bio Mount HM

## SECTION 8. Exposure controls/personal protection ... / &gt;&gt;

## ETHYL ACETATE

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	1500	400	3000	800
MAK	DEU	1500	400	3000	800
TLV	DNK	540	150		
VLA	ESP	1460	400		
HTP	FIN	1100	300	1800	500
VLEP	FRA	1400	400		
WEL	GBR		200		400
TLV	GRC	1400	400		
AK	HUN	1400		1400	
OEL	NLD	550		1100	
TLV	NOR	550	150		
NDS	POL	734		1468	
TLV	ROU	400	111	500	139
MAK	SWE	500	150	1100	300
OEL	EU	734	200	1468	400
TLV-ACGIH		1441	400		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

TLV of solvent mixture: 467 mg/m3

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

## HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

## SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

## EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

## RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

## ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	

## Bio Mount HM

## SECTION 9. Physical and chemical properties ... / &gt;&gt;

Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	$23 \leq T \leq 60$ °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	Not available
Solubility	soluble in organic solvents
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

## 9.2. Other information

VOC (Directive 2010/75/EC) :	64,00 %
VOC (volatile carbon) :	55,57 %

## SECTION 10. Stability and reactivity

## 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

## ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

## 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

## XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

## ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

## 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

## ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

## 10.5. Incompatible materials

## ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid. Incompatible materials: plastic materials.

## 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## Bio Mount HM

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.  
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

XYLENE (MIXTURE OF ISOMERS)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

18,33 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

1833,33 mg/kg

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral)

3523 mg/kg Rat

LD50 (Dermal)

4350 mg/kg Rabbit

LC50 (Inhalation)

26 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

## Bio Mount HM

## SECTION 11. Toxicological information ... / &gt;&gt;

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

## 12.1. Toxicity

Information not available

## 12.2. Persistence and degradability

## XYLENE (MIXTURE OF ISOMERS)

Solubility in water

100 - 1000 mg/l

Degradability: information not available

## ETHYL ACETATE

Solubility in water

> 10000 mg/l

Rapidly degradable

## 12.3. Bioaccumulative potential

## XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water

3,12

BCF

25,9

## ETHYL ACETATE

Partition coefficient: n-octanol/water

0,68

BCF

30

## 12.4. Mobility in soil

## XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water

2,73

## 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## 12.6. Other adverse effects

Information not available



## Bio Mount HM

## SECTION 13. Disposal considerations

## 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

## 14.1. UN number

ADR / RID, IMDG, IATA: 1263

## 14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

## 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



## 14.4. Packing group

ADR / RID, IMDG, IATA: III

## 14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

## 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30  
Special Provision: -

Limited Quantities: 5 L

Tunnel restriction code: (D/E)

IMDG: EMS: F-E, S-E

Limited Quantities: 5 L

IATA: Cargo:

Maximum quantity: 220 L

Packaging instructions: 366

Pass.:

Maximum quantity: 60 L

Packaging instructions: 355

Special Instructions:

A3, A72, A192

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

## SECTION 15. Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

P5c

## Bio Mount HM

## SECTION 15. Regulatory information ... / &gt;&gt;

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product  
Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

## 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H312</b>	Harmful in contact with skin.
<b>H312+H332</b>	Harmful in contact with skin or if inhaled.
<b>H332</b>	Harmful if inhaled.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration

## Bio Mount HM

## SECTION 16. Other information ... / &gt;&gt;

- REACH: EC Regulation 1907/2006 - RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

## Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 12 / 13 / 16.

Changed TLVs in section 8.1 for following countries:

FIN,