

LLC «JV YUKOIL»

48A Ivana Pulyuya str., Bila Tserkva, Kyiv region, Ukraine, 09100

Hot-line: +38 (0) 800 60 5555

Tel: +38 (061) 222 80 25 (laboratory)

State register No. 31852954



Testing laboratory of JV "YUKOIL" LLC is certified for carrying out tests of quality parameters of petroleum products, technical fluids and lubricants. Certificate of technical competence recognition № AB 83-21 dated 16.11.2021 is issued by the State-owned enterprise "ZAPORIZHYASTANDARTMETROLOGIA", valid till 16.11.2024

Quality Certificate No 06114.01.01.1 Compressor oil YUKO VDL 100 (ISO 100)

Manufacturer JV YUKOIL LLC

Packed by JV YUKOIL LLC

Viscosity grade: **ISO 100**

Quality Index: **ISO 6743-3 (DAH), DIN 51506 (VDL)**

Production date: February 2023

Package: canister 1L PE

Batch No: 06114.10.02.23.01.



№	Test	Norm	Result	Test method
1	Density at 20°C, kg/m ³ , not more than	900	883,0	ASTM D1298
	Kinematic viscosity at 40°C, mm ² /s	76,0 - 130,0	102,71	ASTM D445
3	Viscosity index, not less than	85	88	ASTM D2270
4	Open cup flash point, °C, not less than	205	222	ASTM D92
5	Pour point, °C, not high than	minus 30	minus 30	ASTM D97
6	Mass fraction of mechanical impurities, %, not more than	absence	absence	GOST 6370
7	Water content, %, not more than	absence	absence	GOST 2477 or ASTM D95
15	Sulfur content, %, not more than	0,80	0,627	GOST 1431 or ASTM D6481 or ASTM D6443 or ASTM D4927
16	Acid number, mg KOH/g	0,2	0,07	GOST 5985 or ASTM D974
17	Ash content, %, not more than	0,08	0,06	GOST 1461 or ASTM D482
18	Foaming:			DSTU 8420 or ASTM D892
	- at 24°C, not more than	100	5	DSTU 8420 or ASTM D892
	- at 94°C, not more than	100	20	DSTU 8420 or ASTM D892
	- at 24°C, after 94°C, not more than	100	10	DSTU 8420 or ASTM D892
22	Corrosion on plates of the copper	withstands	pass	GOST 2917 or ASTM D130

Result: the product quality meets the standard of TY Y 19.2-31852954-115:2021

seal

Head of Quality Assurance Department

WEB: www.yuko.eu

Hot-line: +38 (0) 800 60 5555

E-mail: support@yukoil.com

Tel.: +38 (061) 222 80 32

Member of:



