



1 2 Magnetic stirrer with heating LLG-uniSTIRRER 3, complete set

Universal magnetic stirrer with all essential functions and equipment features. A LED display to control all parameters, an integrated temperature control as well as an enclosed design (IP 42) are integrated features. The included PT1000 sensor ensures an exact temperature control. A stand rod with a sensor holder is supplied with this instrument. The integrated **HOT-sign** warns the user of a hot plate even if the device is switched off.

- LED display to set the exact rotation speed and the temperature
- Digital controlled rotation speed and temperature
- 'HOT' warning sign, even if the device is switched off
- **Delivered as complete set:** magnetic stirrer, sensor PT1000, stand rod and sensor holder
- Integrated temperature control

Delivery includes: Magnetic stirrer with PT1000 probe, rod and holder

Specifications

Stirring quantity (H ₂ O):	3000 ml
Speed range:	100 to 1500 rpm
Setting accuracy:	±10 rpm
Magnetic bar:	max. 50 mm
Display:	LED
Heating plate:	135 mm diam./Stainless steel
Permissible ambient temperature:	5 to 40 °C
Temperature range:	RT to 280 °C
Setting accuracy:	±1 °C
Control accuracy:	±2 °C
Heat output:	500 W
Safety temperature:	320 °C
Dimensions (W x D x H):	155 x 215 x 100 mm
Weight:	1.5 kg
Power supply:	200 - 240 V, 50/60 Hz
Protection class:	IP 42
Warranty:	3 years



Type	PK	Cat. No.
LLG-uniSTIRRER 3 with EU-plug	1	6.263 410
LLG-uniSTIRRER 3 with UK-plug	1	6.263 411
Stand and sensor holder for LLG-uniSTIRRER 3	1	6.263 416



3 LLG-Magnetic stirring bars, cylindrical, PTFE, *eco pack*

Circular, smooth and PTFE-coated. Packaging size: 10 pieces

Diam. mm	Length mm	PK	Cat. No.
6	10	10	9.198 910
3	12	10	9.198 766
6	15	10	9.198 919
6	20	10	9.198 920
6	25	10	9.198 925
8	25	10	9.198 767
6	30	10	9.198 930
6	35	10	9.198 935
8	40	10	9.198 940
8	45	10	9.198 945
8	50	10	9.198 950
9	60	10	9.198 960
9	70	10	9.198 970
9	80	10	9.198 980