

Vipoil Kinematic Ultra 5W-30 C3 LL

Engine Oil

DESCRIERE

Vipoil Kinematic Ultra 5W-30 C3 LL este un ulei de motor multigrad, formulat din uleiuri de baza full-sintetice si un pachet de aditivi performant care ofera o protectie superioara impotriva uzurii, protejeaza impotriva coroziunii, asigura performante optime in conditii diferite de exploatare, curata si disperseaza eficient depunerile si asigura nivelul de performanta ACEA C3.

APLICATII

Este recomandata utilizarea la vehiculele echipate cu motoare pe benzina sau diesel cu injectie directa sau indirecta, vehiculele moderne echipate cu sisteme de tratare a emisiilor, cum ar fi DPF și CAT.

SPECIFICATII

ACEA C3
API SN
VW 504.00/507.00
MB 229.51
PORSCHE C30
BMW LL-04

BENEFICII

- Stabilitate foarte buna impotriva oxidarii
- Stabilitate foarte buna impotriva depunerilor
- Durata de exploatare extinsa (LongLife)
- Pornire usoara la temperature scazute

PROPRIETATI TIPICE

Caracteristici	Metoda de test	Valori
Densitate la 15°C, g/cm ³ , max.	ASTM D4052	0.865
Viscozitate cinematica la +40°C, mm ² /s ⁻¹ .	ASTM D445	68.0
Viscozitate cinematica la +100°C, mm ² /s ⁻¹ .	ASTM D445	11.8
Indice de viscozitate, min.	ASTM D2270	171
Punct de inflamabilitate °C, min.	ASTM D92	220
Punct de curgere °C, min.	ASTM D97	-42
Cifra de bazicitate TBN, mg KOH/g.	ASTM D2896	8.3

* These values are informative. Variations of these characteristics may occur.

This lubricant does not present a particular danger if it is used according to our recommendations and according to the purpose for which it was produced. The security sheet according to the European legislation in force can be obtained on request.