



'MADAM CORINNE ' ULTRA PAD - CERTIFICATE OF ANALYSIS

NAME OF MANUFACTURER	ARKAN GRUP SAGLIK URUNLERI A.S.
COUNTRY OF MANUFACTURE	: TURKEY
NAME OF PRODUCT	: "MADAM CORINNE " ULTRA LONG 7x48
PIECES OF PACK	: 7
SIZE	: LONG
DATE OF PRODUCTION	: 20.05.2020
EXPIRATION DATE	: 20.05.2025
LOT NO	: U-7
THE AMOUNT OF SAMPLE FOR TESTING	: 10 PACKAGE
DATE OF QUALITY TEST	: 20.05.2020
LABORATORY NAME	: BABY DIAPER and SANITARY PAD - QUALITY CONTROL LABORATORY

CERTIFICATE OF ANALYSES

As a result of the below analysis, it has been seen that "MADAM CORINNE " LONG Ultra Pads doesn't contain any harmful substance to human health and this product is produced following row materials.

1- Airraid (Contain SAP)	3- Hot Melt	5- Perforated Polyethylene	7-Ink	9-Hydrophilic Transfer Layer
2- Closing Tape	4- Polyethylene	6-Silicon Paper	8-Single Wrap	

RESULT OF ANALYSES

	TARGET	AVERAGE	TEST RESULT MAX.	TEST RESULT MIN.
PAD GRAMAJ	6,06 (±1 gr)	6,06 gr	7,05 gr	5,89 gr
ULTRA PAD DIAMETER	165 (± 5 mm)	165 mm	166 mm	163 mm
ULTRA PAD LENGHT	285 (± 5 mm)	285 mm	288 mm	280 mm

RESULT OF ANALYSES

TEST PARAMETERS	ACCEPTANCE LIMITS	RESULT
Classification	All materials used in the sanitary pad manufacture shall have no harmful effect during normal use.	Approved
	shall be made of an absorbent material which gives a feeling of comfort during use.	Approved
Filling	shall be free of protrusions, oil spots, dirty, or any other foreign matter, and shall have no harmful effect.	Approved
	shall be arranged in a way to allow the distribution of menstrual flow in the absorbent material, and prevent it from leaking to any side.	Approved
Porous fabric	This fabric, if present shall be placed between the filling and outer layer.	Approved
Base layer	Shall be a thin layer of plastic or any other leak-proof material that is placed at the back side of the pad.	Approved
Adhesive tapes	One or several lines of adhesive substances shall be made on the backt of the pad to secure it in place on the underwear when used. The adhesive shall be covered with a protective cover.	Approved
	The adhesive shall leave no traces on clothes when the pad is removed.	Approved
ABSORBENCY (LIQUID)	Overall absorbency shall not be less than 30 ml /pad	36 ml
ABSORPTION TIME	≤15 seconds	8 seconds
PH	Ph shall vary between 5,5 and 9,5 according to International Standart ISO 6588-1	6,5
Absorbency Capacity (ml)	No Leakage	36 ml
ANAEROBIC/AEOROBIC BACTERIA COUNT(cfu/mg)	≤10 cfu/mg	Absent
STAOHYLOCOCCUS AUREUS(cfu/mg)	Not Found	Absent
CANDIDA ALBICANS(cfu/mg)	Not Found	Absent
PSEUDOMONAS AUREGINOSA(cfu/mg)	Not Found	Absent
E-COLI(cfu/mg)	Not Found	Absent

ARKAN GRUP SAGLIK URUNLERI A.S.
QUALITY CONTROL DEPARTMENT

ARKAN GRUP SAGLIK URUNLERI A.S. /Velimeşe Mah. Hacı Şeremet Cad. No: 14 , ERGENE / TEKİRDAĞ

Tel : (+90) 212 438 7601 Fax : (+90) 212 438 7604 Web: <http://www.pine.com.tr>