


## E-07ST Oxygen sensor



<b>Reference</b>	E-07ST
<b>Series</b>	O2
<b>Description</b>	Oxygen sensor for medical application that show high signal stability at low cross interferences to anesthesia gases combined with superior linearity over the entire range
<b>Other compatible references</b>	City Technology MOX-3, Maxtec MAX-3 (R109P11), Nuova E-77/0S
<b>Measurement range</b>	0 to 100 Vol.%
<b>Temperature range (operating)</b>	10 to 40°C
<b>Interferences</b>	according to DIN EN ISO 21647 and ISO 7767
<b>Temperature range (storage)</b>	recommended: 5 to 30°C, maximum: -20 to 50°C
<b>Humidity (storage)</b>	up to 100 % RH
<b>CE class</b>	Ila
<b>CE</b>	1011

<b>Shelf life</b>	recommended less than 6 months
<b>Packaging</b>	1 unit per box
<b>Brand &amp; Model(s)</b>	Mindray VT50 Ventilator, Paragon Platinum SC430, Penlon Prima SP, Prima SP2
<b>Packaging weight</b>	0.05 kg
<b>Manufacturer</b>	Carril Instruments, Congost, 28, ES08024 Barcelona, Spain

The manufacturers listed are the holders of their respective names and/or trademarks and are not to be taken as an endorsement or affiliation with Carril Instruments.

January 2012

This data sheet is subject to change without prior notice.