

SAFETY DATA SHEET CAUSTIC SODA

2020/878 in ANNEX II: GUIDE TO THE COMPILATION OF SAFETY DATA SHEETS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CAUSTIC SODA

Chemical name SODIUM HYDROXIDE

Product number DD.44.15

REACH registration number 01-2119457892-27-0130

CAS number 1310-73-2 **EC number** 215-185-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

In rayon ,In pulp, textile, rubber, Aluminium and food industry, petroleum industry,In

manufacturing of soaps and detergents, and in water treatment. There is no specific

information on the use not recommended.

Uses advised againstNo specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Koruma Klor Alkali Sanayi ve Ticaret A.Ş

Derince Factory

Deniz Mah. Petrol Ofisi Cad. No: 43 41100 Derince-Kocaeli/TURKEY

Phone: +90 262 239 22 70 / 4 hat Fax: +90 262 239 22 78

Kırıkhan Factory

Menderes Mah. 898 Sk. No:6/A Kırıkhan-Hatay/TURKEY

Phone: +90 326 345 28 11 Fax:+90 326 345 27 97

Denizli Factory

Demokrasi Mah. Atatürk Cad. No: 237 Kocabaş kasabası Honaz-Denizli/TURKEY

Phone: +90 258 814 52 66 Fax: +90 258 814 52 66

Contact person koruma@koruma.com.tr

1.4. Emergency telephone number

Emergency telephone Koruma Phone: +90 262 239 22 70

National emergency telephone UZEM (Ulusal Zehir Danışma Merkezi- National Poison Solidarity Center): 114

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

CAUSTIC SODA

Health hazards Skin Corr. 1A - H314 Eye Dam. 1 - H318

Environmental hazards Not Classified

2.2. Label elements

EC number 215-185-5

Hazard pictograms



Signal word Danger

Hazard statements H314 Causes severe skin burns and eye damage.

Precautionary statements P260 Do not breathe vapour/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/ doctor.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

Contains sodium hydroxide

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Sodium hydroxide 47-48

CAS number: 1310-73-2 EC number: 215-185-5

Classification

Skin Corr. 1A - H314 Eye Dam. 1 - H318

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Chemical burns must be treated by a physician.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

CAUSTIC SODA

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

Skin contact It is important to remove the substance from the skin immediately. Take off immediately all

contaminated clothing. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention. Chemical burns must be treated by a physician.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. If it is

suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth

resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Severe irritation of nose and

throat. Symptoms following overexposure may include the following: Corrosive to the

respiratory tract.

Ingestion May cause chemical burns in mouth, oesophagus and stomach. Symptoms following

overexposure may include the following: Severe stomach pain. Nausea, vomiting.

Skin contact Causes severe burns. Symptoms following overexposure may include the following: Pain or

irritation. Redness. Blistering may occur.

Eye contact Causes serious eye damage. Symptoms following overexposure may include the following:

Pain. Profuse watering of the eyes. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up.

Severe corrosive hazard. Water used for fire extinguishing, which has been in contact with the

product, may be corrosive.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Very

toxic or corrosive gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Regular protection may not be safe. Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Koruyucu gözlük, neopren eldiven, lastik bot , özel solunum aygıtı kullanın. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes. Avoid contact with contaminated tools and objects.

6.2. Environmental precautions

Environmental precautions

The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms. Avoid discharge to the aquatic environment. Toprak ve yüzey sularının kirlenmesini önlemek için izole edilmelidir.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. This product is corrosive. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Yıkama sularını arıtma tesisine gönderin. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. This product is corrosive. Immediate first aid is imperative. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers. Çok kuvvetli alkali olduğundan yükleme, boşaltma ve kullanımda çok dikkatli olun ve özel talimatlara göre hareket edin. Dolu kaplar yerinden oynatılmadan önce ağzının kapalı olup olmadığını kontrol edin. Ambalajı çok dikkatli açın. Kullanım sırasında mutlaka gözlük, eldiven gibi koruyucu tedbirleri alın.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Boiling point: 136- 137°C

Crystallization point (% 50): 9 C

Storage temperatures:

Stores must be heated by steam under 18 C.

Temperature range must be between 29 – 38 C. It creates corrosion and iron rust occurs above this temperature.

The substance is hygroscopic and carbonate is formed together with moisture and carbon dioxide in contact with air.

Surroundings must be well ventilated when it is stored in closed area. Store away from incompatible materials (see Section 10). Store locked up. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent. Karbon çeliğinden yapılmış varil, kara ve deniz tankerleri ile taşınır. Metallerden, alevlenir sıvılardan ve organik halojenlerden uzak tutulmalıdır.

Storage class Corrosive storage.

Shelf life 2 years

Tank (Ürün) Sıcaklığı :

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Sodium hydroxide

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment











Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure. Ürünün mesleki maruziyet sınır değerlerinin üzerine çıkılma riskini önlemek için çalışma ortamının çok iyi havalandırıldığından ve temizlendiğinden emin olunmalıdır. Gerekli alanlarda hava filtreleme sistemi NIOSH ve CEN sistemlerine uygun kurulmalıdır. Kullanım alanı ürünün çevreye bulaşmasını engelleyecek şekilde tasarlanmalıdır.

Personal protection

The product is corrosive. Direct contact with the skin or eyes should be avoided as this may cause severe burns

Avoid inhalation of vapors.

Use only in well ventilated areas.

Remove contaminated clothing immediately.

Hands should be washed at the end of work and at work. Do not eat or drink any food when using this substance.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. TS/EN 374'e uygun, sızdırmaz, lastik, alkali dirençli, PVC ya da neopren eldiven giyilerek elle teması engellenmelidir. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible. Vücudu tümüyle örten uygun koruyucu kıyafet, tulum, lastik bot giyilmelidir.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Havadaki konsantrasyonu TLV limitlerinin üzerindeyse maske kullanımı gerekir.100 ppm'e kadar olan konsantrasyonlarda yüksek verimli özel tip maske gereklidir. Bu seviyenin üzerinde ise solunum cihazı kullanılmalıdır. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

CAUSTIC SODA

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Çevrenin korunmasına yönelik mevcut mevzuat çerçevesindeki yükümlülükler bütünüyle yerine getirilmelidir.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Colourless **Appearance** Odour Odourless. 14 at 20°C pН

+9 C Melting point

Initial boiling point and range 137°C

Flash point Not applicable.

Flammability (solid, gas) Not applicable.

Vapour pressure <2,4

1,500-1,512 kg/m³ **Bulk density** Solubility(ies) Miscible with water.

Explosive properties Not applicable.

9.2. Other information

Molecular weight 40,01 gr/grmol

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

No potentially hazardous reactions known.

reactions

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

Does not decompose when used and stored as recommended. Thermal decomposition or products combustion products may include the following substances: Corrosive gases or vapours.

SECTION 11: Toxicological information

CAUSTIC SODA

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Skin Corr. 1A - H314 Causes severe burns.

Serious eye damage/irritation

Serious eye damage/irritation Eye Dam. 1 - H318 Corrosive to skin. Corrosivity to eyes is assumed.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisationBased on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicityNone of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure
Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Corrosive to the respiratory tract. Symptoms following overexposure may include the

following: Severe irritation of nose and throat.

Ingestion May cause chemical burns in mouth, oesophagus and stomach. Symptoms following

overexposure may include the following: Severe stomach pain. Nausea, vomiting.

Skin contact Causes severe burns. Symptoms following overexposure may include the following: Pain or

irritation. Redness. Blistering may occur.

Eye contact Causes serious eye damage. Symptoms following overexposure may include the following:

Pain. Profuse watering of the eyes. Redness.

CAUSTIC SODA

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

AçıklamalarExplanations

SECTION 12: Ecological information

EcotoxicityNot regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 125 mg/l, Freshwater fish

Acute toxicity - aquatic

invertebrates

ECo, 48 hours: 100 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners

may retain some product residues and hence be potentially hazardous.

Disposal methods Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a

licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is

not feasible.

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal

documentation using the data shown in this section.

14.1. UN number

UN No. (ADR/RID) 1824 UN No. (IMDG) 1824 UN No. (ICAO) 1824 UN No. (ADN) 1824

14.2. UN proper shipping name

Proper shipping name

SODIUM HYDROXIDE SOLUTION

(ADR/RID)

Proper shipping name (IMDG) SODIUM HYDROXIDE SOLUTION
Proper shipping name (ICAO) SODIUM HYDROXIDE SOLUTION
Proper shipping name (ADN) SODIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es)

ADR/RID class 8

ADR/RID classification code C5

ADR/RID label 8

IMDG class 8

ICAO class/division 8

ADN class 8

Transport labels



14.4. Packing group

ADR/RID packing group II
IMDG packing group II
ICAO packing group II
ADN packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-A, S-B

ADR transport category 2

Emergency Action Code 2R

Hazard Identification Number (ADR/RID) 80

CAUSTIC SODA

Tunnel restriction code

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

(E)

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate.

LC₅o: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

EC₅: 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations

and acronyms

Eye Dam. = Serious eye damage Skin Corr. = Skin corrosion

Classification procedures

according to Regulation (EC)

1272/2008

Eye Dam. 1 - H318: Skin Corr. 1A - H314: : Calculation method.

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

Revision date 03/01/2022

Revision 10.1

Supersedes date 30/06/2016
SDS number DD.44.15

Hazard statements in full H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.