

Specificații tehnice (F4.1)

[Acest tabel va fi completat de către ofertant în coloanele 3, 4, 5, 7, iar de către autoritatea contractantă – în coloanele 1, 2, 6, 8]


	Numărul procedurii de achiziție <u>Conform SIA „RSAP” din Conform SIA „RSAP”</u>
	Denumirea procedurii de achiziție: Cererea ofertelor de prețuri

COD CPV	Denumirea bunurilor/serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
	Bunuri						
	Lotul 3						
32341000-5	Microfon	CVG12S-B/C	PRC	SHURE	• Frequency range: 70Hz-16kHz • Frequency response: contoured • Sensitivity: -33.00 dBV/Pa – 22.00 mV/Pa • Self noise: 27dBSPL • Maximum SPL: 120 dB • Cartridge type: electret condenser • Polar pattern: cardioid • Connectivity: 3-pin XLR • Needs phantom power: 11-52 V DC II. (Analog cu Shure CVG12S-B/C Gooseneck Microphone, 30.5cm, Condensator, Cardioid, 3pin XLR male, inkl. Preamp, Mute, LED bottom) Garanție 2 ani	• Frequency range: 70Hz-16kHz • Frequency response: contoured • Sensitivity: -33.00 dBV/Pa – 22.00 mV/Pa • Self noise: 27dBSPL • Maximum SPL: 120 dB • Cartridge type: electret condenser • Polar pattern: cardioid • Connectivity: 3-pin XLR • Needs phantom power: 11-52 V DC Garanție 2 ani	

32341000-5	Microfon USB	SM58 + X2U	Mexico	SHURE	Shure SM58-X2U Cardioid Dynamic Vocal Microphone with X2U XLR-to-USB Signal Adapter SM58® Cardioid Dynamic Microphone Specifications Type: Dynamic Frequency Response: 50 to 15,000 Hz Polar Pattern: Cardioid Sensitivity (at 1,000 Hz Open circuit voltage): -54.5 dBV/Pa (1.85 mV) 1 Pa = 94 dB SPL Impedance: Rated impedance is 150 Ω (300 Ω actual) for connection to microphone inputs rated low impedance Polarity: Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3 Case: Dark gray, enamel-painted, die cast metal; matte-finished, silver colored, spherical steel mesh grille Connector: Three-pin professional audio connector (male XLR type) Weight Net: 298 g Dimensions: 162 mm L x 51 mm W Shure X2u XLR-to-USB Signal Adapter With Headphone Output Specifications Frequency Response 20 to 20,000 Hz +/- 1 dB Power Requirements USB-powered, 500 mA, maximum Digital Noise Floor (20 Hz to 20 kHz, A-weighted) : -78 dB FS Sampling Rate up to 48 kHz Bit Depth 16 bit Peak Signal Indicator (Tri-color) OFF: -30 dB FS Green: -30 to -12 dB FS Yellow: -12 to 0 dB FS Red: >0 (digital converter clipped) Adjustable Gain Range 40 dB Headphone Output 3.5 mm (1/8 inch)	Shure SM58-X2U Cardioid Dynamic Vocal Microphone with X2U XLR-to-USB Signal Adapter SM58® Cardioid Dynamic Microphone Specifications Type: Dynamic Frequency Response: 50 to 15,000 Hz Polar Pattern: Cardioid Sensitivity (at 1,000 Hz Open circuit voltage): -54.5 dBV/Pa (1.85mV) 1 Pa = 94 dB SPL Impedance: Rated impedance is 150 Ω (300 Ω actual) for connection to microphone inputs rated low impedance Polarity: Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3 Case: Dark gray, enamel-painted, die cast metal; matte-finished, silver colored, spherical steel mesh grille Connector: Three-pin professional audio connector (male XLR type) Weight Net: 298 g Dimensions: 162 mm L x 51 mm W Shure X2u XLR-to-USB Signal Adapter With Headphone Output Specifications Frequency Response 20 to 20,000 Hz +/- 1 dB Power Requirements USB-powered, 500 mA, maximum Digital Noise Floor (20 Hz to 20 kHz, A-weighted) : -78 dB FS Sampling Rate up to 48 kHz Bit Depth 16 bit Peak Signal Indicator (Tri-color) OFF: -30 dB FS Green: -30 to -12 dB FS Yellow: -12 to 0 dB FS Red: >0 (digital converter clipped) Adjustable Gain Range 40 dB Headphone Output 3.5 mm (1/8 inch)
------------	--------------	------------	--------	-------	---	---

					Garanție 2 ani	Garanție 2 ani	
32341000-5	Microfon USB	PM700SP	PRC	Boya	• G-Track Pro - Professional USB Microphone with Audio Interface • Large, 19mm diaphragm studio condenser microphone • USB audio interface with 16-bit, 48kHz resolution • Plugs directly into any computer with a USB input, no drivers required • Compatible with most computer-based digital audio workstation software • Supercardioid pickup pattern • Smooth, flat frequency response of 20Hz–16kHz • 1/8" stereo input for mono instruments (guitar, bass, etc.) and stereo line level devices (MP3 players, keyboards, etc.) • 1/8" stereo headphone jack for no latency monitoring • Input and Direct Monitor selector switches • Volume, Instrument and Mic level controls • Dual color Power/Clip LED • Solid, die-cast construction with heavy gauge mesh grill • Includes desktop mic stand, mic clip and complete cable set (guitar cable, headphone extension, stereo line with RCA adapters and USB cable) • Optional SP04 shockmount available • Large, 19mm diaphragm studio condenser microphone • USB audio interface with 16-bit, 48kHz resolution • Plugs directly into any computer with a USB input, no drivers required • Compatible with most computer-based digital audio workstation software • Supercardioid pickup pattern • Smooth, flat frequency response of 20Hz–16kHz • 1/8" stereo input for mono instruments (guitar, bass, etc.) and stereo line level devices (MP3 players, keyboards, etc.) • 1/8" stereo headphone jack for no latency monitoring • Input and Direct Monitor selector switches • Volume, Instrument and Mic level controls • Dual color Power/Clip LED • Solid, die-cast construction with heavy gauge mesh grill • Includes desktop mic stand, mic clip and complete cable set (guitar cable, headphone extension, stereo line with RCA adapters and USB cable) • Optional SP04 shockmount available	• Professional USB Microphone with Audio Interface for IOS devices, Android devices, Windows and Mac computers • Triple diafragm • Cardioid, stereo, Omnidirectional, Bi-Directional pickup pattern • USB audio interface with 24-bit, 48kHz resolution • Plugs directly into any computer with a USB input, no drivers required • Compatible with most computer-based digital audioworkstation software • Smooth, flat frequency response of 20Hz–16kHz • Supercardioid pickup pattern • 1/8" stereo headphone jack for no latency monitoring • Includes desktop mic stand, complete cable set (USB-A, Tupe-C, Lighting cable)	

32342420-2	Audio mixer USB 2.0	Scarlett 2i2 3rd Gen	PRC	FOCUSRITE	ZERO LATENCY RECORDING 24-bit/192kHz SUPPORTED SAMPLE RATES 44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz Power: USB-bus-power MICROPHONE INPUTS Frequency Response: 20Hz - 20kHz $\pm$ 0.1dB Dynamic Range: 111dB (A-weighted) THD+N: <0.0012% Noise EIN: -128dB (A-weighted) Maximum Input Level: 9dBu (at minimum gain) Gain Range: 56dB Impedance: 3kΩ INSTRUMENT INPUTS Frequency Response 20Hz - 20kHz $\pm$ 0.1dB Dynamic Range 110dB (A-weighted) THD+N <0.03% Maximum Input Level 12.5dBu (at minimum gain) Gain Range 56dB Impedance 1.5MΩ LINE INPUTS Frequency Response: 20Hz - 20kHz $\pm$ 0.1dB Dynamic Range: 110.5dB (A-weighted) THD+N: <0.002% Maximum Input Level: 22dBu (at minimum gain) Gain Range: 56dB Impedance: 60kΩ LINE/MONITOR OUTPUTS Dynamic Range (Line Outputs): 108dB THD+N: <0.002% Maximum Output Level (0 dBFS): 15.5dBu Impedance: 430Ω HEADPHONE OUTPUTS Dynamic Range: 104dB (A-weighted) THD+N: <0.002% Maximum Output Level: 7dBu Impedance: <1Ω (Similar Focusrite Scarlett 2i2 3rd Gen) Garantie 2 ani	ZERO LATENCY RECORDING 24-bit/192kHz SUPPORTED SAMPLE RATES 44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz Power: USB-bus-power MICROPHONE INPUTS Frequency Response: 20Hz - 20kHz $\pm$ 0.1dB Dynamic Range: 111dB (A-weighted) THD+N: <0.0012% Noise EIN: -128dB (A-weighted) Maximum Input Level: 9dBu (at minimum gain) Gain Range: 56dB Impedance: 3kΩ INSTRUMENT INPUTS Frequency Response 20Hz - 20kHz $\pm$ 0.1dB Dynamic Range 110dB (A-weighted) THD+N <0.03% Maximum Input Level 12.5dBu (at minimum gain) Gain Range 56dB Impedance 1.5MΩ LINE INPUTS Frequency Response: 20Hz - 20kHz $\pm$ 0.1dB Dynamic Range: 110.5dB (A-weighted) THD+N: <0.002% Maximum Input Level: 22dBu (at minimum gain) Gain Range: 56dB Impedance: 60kΩ LINE/MONITOR OUTPUTS Dynamic Range (Line Outputs): 108dB THD+N: <0.002% Maximum Output Level (0 dBFS): 15.5dBu Impedance: 430Ω HEADPHONE OUTPUTS Dynamic Range: 104dB (A-weighted) THD+N: <0.002% Maximum Output Level: 7dBu Impedance: <1Ω Garantie 2 ani
------------	---------------------	----------------------	-----	-----------	--	--

Semnat: 

[semnătura persoanei autorizate pentru semnarea ofertei]

Nume: Tanurcov Serghei

În calitate de: administrator Audio Line SRL

[funcția oficială a persoanei ce semnează formularul ofertei]

Ofertantul: Audio Line SRL

Adresa: str.Sarmizegetusa 26, or.Chisinau

Data: "12" august 2021