



S.C TehnoWorld SRL

Loc. Baia, nr. 1616, DN2E km 2
Jud. Suceava, RO-727020
0230 546 696 tel
0230 206 090 fax
0743 069 587 mob
office@tehnworld.ro
www.tehnworld.ro
RC: J33/145/2003
CUI: RO15231305
RO87BACX0000003023781012
UNICREDIT BANK

CERTIFICAT DE CALITATE	
Nr.	Data
Beneficiar	
Adresa	
Aviz nr.	
Produs	
Executat dupa	SR EN 12201-2 -
Lot	
Cant. Livrata	M
Marcaj	

REZULTATE INCERCARI LOT PRODUS FINIT

Nr. Crt.	Tip de incercare	Metoda	UM	Valori prevazute SR EN 12201-2	Valori determinate
1	Aspect	Vizual		Suprafete interioare si exterioare: curate, netede, fara crestaturi, adancituri sau alte defecte	Conform
2	Culoare	Vizual		Negru	Conform
3	Caracteristici dimensionale	Diametru extern mediu/toleranta	mm		Conform
		Grosime perete/toleranta	mm		Conform
		Ovalizare	mm		Conform
4	Indice de fluiditate la cald (MFR)	SR ISO 1133	g/10min	0.2 - 1.4 si $\pm 20\%$ fata de MFR granula	Conform
5	Timp inducere oxidare la 200°C	ISO 11357-6	minute	≥ 20	Conform
6	Caracteristici tractiune	ISO 6259	%	≥ 350	Conform
7	Rezistența hidrostatică	SR ISO 1167	ore	≥ 165	Conform

Produsul este conform cu prevederile normei europene de referinta SR EN 12201-2



SC TEHNO WORLD SRL

Carmen Maria Benea
Sef Laborator