

## T-CLASSIC

MERCURY-FREE THERMOMETER



---

### SAFE AND ECOLOGICAL

Mercury-free, contains harmless calibrated liquid alloy.

### EASY TO CLEAN

Glass body, easy to clean between measurements with any alcohol-based solution.

---

### INCLUDED ACCESSORIES

#### PLASTIC CASE

for safe storage.

---

**PRODUCT CODE** TR 100200

## T-FLAP

MERCURY-FREE THERMOMETER



---

### SAFE AND ECOLOGICAL

Mercury-free, contains harmless calibrated liquid alloy.

### EASY TO CLEAN

Glass body, easy to clean between measurements with any alcohol-based solution.

### EASY TEMPERATURE LOWERING

Thanks to the flap added to the case.

---

### INCLUDED ACCESSORIES

#### PLASTIC CASE + FLAP

for safe storage and easy temperature lowering.

---

**PRODUCT CODE** TR 100300



	<b>T-PLUS</b>	<b>T-EASY</b>	<b>DIGIT-10P</b>	<b>DIGIT-40</b>	<b>DIGIT-40F</b>	<b>T-CLASSIC</b>	<b>T-FLAP</b>
	<i>Infrared thermometer</i>	<i>Infrared thermometer</i>	<i>Digital Thermometer</i>	<i>Digital Thermometer</i>	<i>Digital Thermometer</i>	<i>Mercury free thermometer</i>	<i>Mercury free thermometer</i>
<b>SIZE</b>	14,9 x 3,4 x 5,2 cm	14,9 x 3,4 x 5,2 cm	13,5 x 2,8 x 1 cm	12,6 x 2 x 1,1 cm	12,6 x 2 x 1,1 cm	12,5 x 1,2 x 0,9 cm	12,5 x 1,2 x 0,9 cm
<b>WEIGHT</b>	95 g	95 g	16 g	9,4 g	9,4 g	7,2 g	7,2 g
<b>LCD</b>	with 3 colours backlight	with 3 colours backlight	2,35 x 1,55 cm with 3 colours back light	1,6 x 0,75 cm	1,6 x 0,75 cm	—	—
<b>MEASUREMENT METHOD</b>	Infrared (no-touch)	Infrared (no-touch)	Thermistor	Thermistor	Thermistor	Thermal expansion of a calibrated liquid alloy	Thermal expansion of a calibrated liquid alloy
<b>MODE</b>	Body /Objects	Body /Objects	Rectal / Oral / Axillary	Rectal / Oral / Axillary	Rectal / Oral / Axillary	Rectal / Oral / Axillary	Rectal / Oral / Axillary
<b>MEASUREMENT TIME</b>	1 s	1 s	10 s	40 / 60 / 90 s	40 / 60 / 90 s	3 / 3 / 5 min	3 / 3 / 5 min
<b>ACCURACY</b>	<b>35 &gt; 42°C:</b> ±0,2 °C <b>Otherwise</b> ±0,3°C	<b>35 &gt; 42°C:</b> ±0,2 °C <b>Otherwise</b> ±0,3°C	<b>35 &gt; 42°C:</b> ±0,1 °C <b>Otherwise</b> ±0,2°C	<b>35 &gt; 42°C:</b> ±0,1 °C <b>Otherwise</b> ±0,2°C	<b>35-42°C:</b> ±0,1 °C <b>Otherwise</b> ±0,2°C	±0,1°C	±0,1°C
<b>IP CODE</b>	IP22	IP22	IP55	IP54 waterproof	IP54 waterproof	—	—
<b>POWER SOURCE</b>	2 x Alkaline AAA size, 1,5V batteries	2 x Alkaline AAA size, 1,5V batteries	CR1632 3,0V button battery	LR41 or AG3 1,5V button battery	LR41 or AG3 1,5V button battery	—	—
<b>BATTERY AUTONOMY</b>	- 1000 measurements	- 1000 measurements	- 600 measurements /2 years	- 1200 measurements /2 years	- 1200 measurements /2 years	—	—
<b>WARRANTY</b>	2 years	2 years	2 years	2 years	2 years	2 years	2 years
<b>SHIPPING CARTON</b>	50	50	288 units	400 units	400 units	12 units	12 units
<b>TIP</b>	—	—	Flexible, Waterproof	Rigid	Flexible	Rigid, Waterproof	Rigid, Waterproof
<b>NUMBER OF MEMORIES</b>	30	30	1	1	1	—	—
<b>END READING BEEPER</b>	▪	▪	▪	▪	▪	—	—
<b>UNITS OF MEASUREMENTS</b>	Celsius / Fahrenheit	Celsius / Fahrenheit	Celsius / Fahrenheit	Celsius / Fahrenheit	Celsius / Fahrenheit	Celsius	Celsius
<b>AUTO SHUT-OFF</b>	After 30 seconds	After 30 seconds	After 5 minutes	After 8 minutes	After 8 minutes	—	—
<b>LOW BATTERY INDICATOR</b>	▪	▪	▪	▪	▪	—	—
<b>PRODUCT CODE</b>	TR 100500	TR 100500/01	TR 200300	TR 200030	TR 200040	TR 100200	TR 100300