

Destination®

Peripheral Guiding Sheath



Destination® Guiding Sheath is designed to perform as a guiding catheter and an introducer sheath.

Destination® is designed to be used for the introduction of interventional and diagnostic devices into the human vasculature, including but not limited to lower extremity, renal arteries, and carotid arteries.

Product Characteristics

- Coil reinforcement inside the sheath which provides high anti-kinking characteristics
- Hydrophilic coating at the distal part of the sheath for good trackability
- Secured hemostasis tailored by Terumo's unique cross-cut valve (CCV items)
- Soft atraumatic tip
- PTFE inner layer which provides smooth device passage
- 5 different tip configurations available

General Specifications

Maximum guidewire size	0.038" / 0.97 mm
Radiopaque marker	Gold coil marker at 5 mm from the distal tip of the sheath
Reinforcement inside the sheath	Stainless steel coil
Sheath inner layer	PTFE polytetrafluoroethylene

Item Specifications

Inner diameter	Length	Shape	Valve	Hydrophilic coating length	Item reference
5 Fr / 0.076" / 1.9 mm	45 cm	Straight	CCV*	5 cm	GS*F5ST1C45
5 Fr / 0.076" / 1.9 mm	45 cm	Hockey stick	CCV	5 cm	GS*F5HS1C45
5 Fr / 0.076" / 1.9 mm	45 cm	Multipurpose	CCV	5 cm	GS*F5MP1C45
5 Fr / 0.076" / 1.9 mm	45 cm	Renal Double Curve	CCV	5 cm	GS*F5RDCC45
5 Fr / 0.076" / 1.9 mm	45 cm	Left Internal Mammary Artery	CCV	5 cm	GS*F5LIMC45
6 Fr / 0.087" / 2.2 mm	45 cm	Straight	CCV	5 cm	RSR01
6 Fr / 0.087" / 2.2 mm	45 cm	Hockey stick	CCV	5 cm	RSR02
6 Fr / 0.087" / 2.2 mm	45 cm	Multipurpose	CCV	5 cm	RSR03
6 Fr / 0.087" / 2.2 mm	45 cm	Renal Double Curve	CCV	5 cm	RSR13
6 Fr / 0.087" / 2.2 mm	45 cm	Left Internal Mammary Artery	CCV	5 cm	RSR14
7 Fr / 0.101" / 2.5 mm	45 cm	Straight	CCV	5 cm	RSR04
7 Fr / 0.101" / 2.5 mm	45 cm	Hockey stick	CCV	5 cm	RSR05
7 Fr / 0.101" / 2.5 mm	45 cm	Multipurpose	CCV	5 cm	RSR06
7 Fr / 0.101" / 2.5 mm	45 cm	Renal Double Curve	CCV	5 cm	RSR15
7 Fr / 0.101" / 2.5 mm	45 cm	Left Internal Mammary Artery	CCV	5 cm	RSR16
8 Fr / 0.115" / 2.9 mm	45 cm	Straight	CCV	35 cm	54-84501
6 Fr / 0.087" / 2.2 mm	65 cm	Straight	CCV	35 cm	RSP01
7 Fr / 0.101" / 2.5 mm	65 cm	Straight	CCV	35 cm	RSP02
8 Fr / 0.115" / 2.9 mm	65 cm	Straight	CCV	35 cm	54-86501
5 Fr / 0.076" / 1.9 mm	90 cm	Straight	TBV**	15 cm	GS*K5ST1T90B
5 Fr / 0.076" / 1.9 mm	90 cm	Multipurpose	TBV	15 cm	GS*K5MP1T90B
5 Fr / 0.076" / 1.9 mm	90 cm	Straight	CCV	15 cm	GS*K5ST1C90B
5 Fr / 0.076" / 1.9 mm	90 cm	Multipurpose	CCV	15 cm	GS*K5MP1C90B

*CCV = cross-cut valve. **TBV = Tuohy-Borst Valve.

Inner diameter	Length	Shape	Valve	Hydrophilic coating length	Item reference
6 Fr / 0.087" / 2.2 mm	90 cm	Straight	TBV	15 cm	RSC01
6 Fr / 0.087" / 2.2 mm	90 cm	Multipurpose	TBV	15 cm	RSC03
6 Fr / 0.087" / 2.2 mm	90 cm	Straight	CCV	15 cm	RSC05
6 Fr / 0.087" / 2.2 mm	90 cm	Multipurpose	CCV	15 cm	RSC07
7 Fr / 0.101" / 2.5 mm	90 cm	Straight	TBV	15 cm	RSC02
7 Fr / 0.101" / 2.5 mm	90 cm	Multipurpose	TBV	15 cm	RSC04
7 Fr / 0.101" / 2.5 mm	90 cm	Straight	CCV	15 cm	RSC06
7 Fr / 0.101" / 2.5 mm	90 cm	Multipurpose	CCV	15 cm	RSC08
8 Fr / 0.115" / 2.9 mm	90 cm	Straight	CCV	60 cm	54-89001
8 Fr / 0.115" / 2.9 mm	90 cm	Straight	TBV	60 cm	54-89006

All dilators are 0.038" (0.97 mm) wire compatible
Please quote above item reference codes when placing an order