



DM0636 Series

DLAB DM0636 Multi-Purpose Low-speed Centrifuge is ideal for the centrifugation of samples in clinical chemistry, cytology, research laboratories, industrial laboratories, etc.

This centrifuge is suitable for tubes with caps, blood collection or urine tubes. Swing-out bucket rotors and adapters can be compatible with standard tubes up to 100mL at low speed.

DM0636 Multi-Purpose Low-speed Centrifuge

Features

- Speed can be set from 300- 6000rpm
- Maximum capacity of the centrifuge: 100 mLx4
- 9 Acceleration/10 Brake speed settings to ensure optimal separation
- A wide range of accessories(fixed angle and swing-out bucket rotors)
- Automatic rotor identification
- Timers can be set up to 99 min. for short run/ continuous run
- 9 procedures stored in memory makes the operation much simplified
- Maintenance-free brushless DC motors



Specifications

DM0636	
Speed range	300-6000rpm increment:10rpm
Max. RCF	4300xg
Speed accuracy	±20rpm
Max. Capacity	100mLx4
Run Time	30sec-99mins/continuous
Motor	Brushless DC
Display	LCD
Program Memory	9
Safety Devices	Door Imbalance protection Over speed & Over temperature detection
Acceleration/Deceleration	9 ↑ /10 ↓ steps
Power	660W; Single-phase AC220V-240V, 50Hz/60Hz, 6.3A; AC110V-120V,50Hz/60Hz,10A
Dimension[WxDxH]	445x579x269mm
Weight	36kg
Certification	CE
Advanced features	speed/rcf switch; Rotor identification

DM0636 Series | Rotors and Adapters



Uncapping block

for S4-100 rotor



SE4-100(Standard accessory) for DM0636 & DM0636R

Cat. No. 19400041

Max. speed: 4000rpm

Max. RCF: 2950×g

Rotor material: stainless steel body and adapter



19400045



19400044



19400043



19400042

bucket	x 4										
tube	x 36		x 16			x 8	x 4	x 4	x 4	x 8	x 20
Nominal volume	3-7mL		10mL	12mL	15mL	50mL	100mL	85mL	50mL	15mL	3-7mL
φ×L mm	13×75	13×100	16×100	17×105	17×120	29.5×100	38×108	38×104	29.5×100	17×120 13×100 13×75	13×100 13×75
tube											
adapter	with plug										
								A100P80	A100P50	A100P15	A100P10
Package	36							4	4	8	4
Tubes per rotor	36	36	16	16	16	8	4	4	4	8	20
Radius(cm)	14	16.5	15.9	15.9	15.9	15.9	15.9	15.9	15.9	15.1	14.7
Max RCF (g-force)	2500	2950	2840	2840	2840	2840	2840	2840	2840	2700	2630

Available rotors



Cat. No. 19400062

S2-MP **DM0636**

Max. speed: 4000rpm
Max. RCF: 2200×g
Rotor capacity: Micro-plates 384-PCR; 96-PCR
Rotor material: stainless steel body and aluminum buckets



Cat. No. 19400036

AS12-PCR8 **DM0636**

Max. speed: 6000rpm
Max. RCF: 4020×g
Rotor capacity: PCR 8 trips×12
Rotor material: aluminum
Bio-safe(Biosealing): Yes



Cat. No. 19400034

AS30-2 **DM0636**

Max. speed: 6000rpm
Max. RCF: 4020×g
Rotor capacity: 2mL×30
Rotor material: aluminum
Bio-safe(Biosealing): Yes



Cat. No. 19400037

AS60-2 **DM0636**

Max. speed: 6000rpm
Max. RCF: 4020×g
Rotor capacity: 2mL×60
Rotor material: aluminum
Bio-safe(Biosealing): Yes

DM0636 Series | Rotors and Adapters

Available rotors



AS6-50V

DM0636

Cat. No. 19400038

Max. speed: 6000rpm
Max. RCF: 4020×g
Rotor capacity: 50mL×6 or 15mL×6
Rotor material: aluminum
Bio-safe(Biosealing): Yes



AS18-5V

DM0636

Cat. No. 19400035

Max. speed: 6000rpm
Max. RCF: 4020×g
Rotor capacity: 5mL×18
Rotor material: stainless steel body and aluminum buckets



A8-50

DM0636

Cat. No. 19400039

Max. speed: 5000rpm
Max. RCF: 3960×g
Rotor capacity: 50mL×8 or 15mL×16
Rotor material: aluminum body and stainless steel adapter



A30-15

DM0636

Cat. No. 19400040

Max. speed: 4500rpm
Max. RCF: 3210×g
Rotor capacity: 15mL×30
Rotor material: aluminum body and stainless steel adapter
Bio-safe(Biosealing): Yes

Capacity	3-7mL Blood collection tube	10mL Blood collection tube	12mL urine tube	15mL
φ×L mm	13×100	16×100	17×105	17×120
Tubes Quantity	30	30	30	30