

METALOIDAS

UŽDAROJI AKCINĖ BENDROVĖ

Rėkyvos str. 21a, 78109 Šiauliai, Lietuva, PVM kodas LT453761113,

Tel+370-68681234, rita@metaloidas.lt

AB Bankas "Swedbank", sąskaitos Nr. LT 227300010077178292

El.p.: metaloidas@metaloidas.lt ; <http://www.metaloidas.lt>

PADANGŲ PERDIRBIMO CECHAS

Pakruojo g. 44, 76126 Šiauliai, Lietuva, tel.(+370-41) 50-76-80, faks.(+370-41)50-76-81

CERTIFICATE OF CONFORMITY– TECHNICAL SPECIFICATION last revision – 2019.01.02

Producer:

JSC „Metaloidas“

Pakruojo str.. 44, Šiauliai, Lithuania

Production adress:

UAB „Metaloidas“

Pakruojo g. 44, Šiauliai, Lietuva

Institution of Certification:

TÜV SÜD Czech s.r.o.

Teslova 2

702 00 Ostrava

Czech Republic

Product review:

Rubber tiles are weather resistant, decorative, optimum fall safety, slip resistant, good sound absorbing properties inside and outside. Easy to install - does not take much time and effort.

Composition:

Rubber granules combined together with polyurethane binder and colouring pigment.

Tested according to:

EN 1176-1:2008; EN 1177:2008 standarts

Certificate No. :

11.509.270

Performance characteristic

Dimensions 500x500mm; 1000 x1000 mm;

Thickness: 20mm-80mm (characteristics could be different for other dimension and thickness of rubber tiles.)

Dimensional Stability Better than ± 2 mm

Flexibility 52 MN/m²

Residual Indentation None

Heat Conductivity 0.14 W/MK

Shore A Hardness 48

Heat Resistance Up to 300 °C

Freeze resistance below -30 °C

Colour Fastness Good UV resistance

Painting PU paint for UV protection

Hygiene Non-toxic

Sound Absorption 86.5 dB/100 Hz

Foot Comfort Excellent

Shear Strength 5.4 N/mm²

Weather Resistance Unaffected by frost and snow

Cigarette Burns Resistant

