



PRODUCT CODE **DESCRIPTION**

NUMBER ITEMS PER PALLET

BI/004 - BI/004/115

36V DC BIONIK BRUSHLESS barrier for 3 or 4 metre booms, with control unit and on-board native encoder, complete with a fastening base with tie rods and screws and boom fastening flanges.

8



FEATURES

MODEL	BI/004 - BI/004/115
Barriers	Up to 4 mt long
Power line supply	230V AC / 115V AC - 50 Hz
Motor power supply	36V DC
Electrical absorption	0-15A
Power rating	220W
Frequency of use	Continue use
Torque	0 - 200 N m
Operating temperature	-20 + 55 C°
Protection level	IP54
Reductor Type	Irreversible
Opening time at 90°	2-6 sec (up to 3 m) - 3-6 sec (up to 4 m)
Onboard control unit	CTRL Digital Controller 36V DC
Encoder	Digital native encoder + magnetic digital SENSORED, 4096 PPR
Accessories power supply	24V DC
Release system	STANDARD Key cylinder
Batteries recovery	Available (optional)
BUS synchronization Master/Slave	Yes
Operating cycles per day (opening/closing - 24 hours no stop)	5000 cycles
Maximum dimension product in mm (L x W x H)	287 x 310 x 1203
Product weight packed (Kg)	47,5



BRUSHLESS MOTOR



INTENSIVE USE



REVERSIBLE REDUCTOR



HIGH SPEED MOTOR



RESIDENTIAL USE



COMMERCIAL USE



INDUSTRIAL USE



PARKING