

# TIARA LED L PRO 18500LM 740 RM3 IP66 I CL. DALI (117W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	962646
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Rated power of the luminaire [W]*:</b>	117
<b>Luminous flux [lm]*:</b>	18500
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	> 70
<b>Electrical protection class:</b>	I
<b>Optics:</b>	RM3
<b>Control:</b>	Yes + 5-stage power reduction

## CHARACTERISTICS

TIARA LED PRO a family of LED road luminaires based on a proven form factor. It uses directional multi-lens matrices, made of PMMA, with each lens having the same optics, ensuring that the luminous characteristics remain constant over time. Components from renowned manufacturers and new LED panels contribute to the very high luminous efficacy achieved at the output of the luminaire - reaching 170 lm/W. The two-chamber construction of the luminaire maintains the tightness of the optical chamber during assembly work and allows tool-free access to the electrical equipment chamber. The upper part of the luminaire, has dedicated hinges and a safety cord. Using standard tools, quick and convenient servicing is possible, allowing the replacement of any component without having to dismantle the entire luminaire and make soldered connections. The body and handle are made of die-cast aluminium, powder-coated grey, and have a very high IP66 protection rating and IK09 mechanical impact resistance. Standard features: ergonomic light module suspension system; fully programmable DALI driver; CLO constant lumen maintenance and autonomous 5-stage power reduction functions available; NTC overheating protection; filter to prevent condensation; connection terminals; tool-free access. Additional options: NEMA, ZHAGA connectors; interfacing with control systems, RCR motion sensor; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; knife disconnecter to disconnect voltage if the electrical compartment is opened; design with cable terminated with quick disconnect; painting in any RAL colour. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

## APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: motorways, motorways, national roads, voivodeships, districts, communes, municipalities, housing estates, area lighting. Optics are also available to illuminate: pedestrian crossings, pavements and cycle paths.


# TIARA LED L PRO 18500LM 740 RM3 IP66 I CL. DALI (117W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	962646	Mounting dimensions [mm]:	ø60
EAN:	5905963962646	Impact resistance:	IK09
ETIM class:	EC000062	Ingress protection:	IP66
Category type:	street lighting	Mounting version:	Top, on pole / Side, on boom
Version:	L	Beam angle adjustment [°]:	-5 to +15 (peak); -15 to +5 (side)
Light source:	LED module	Lateral surface (SCx) [m2]:	0.034
Rated power of the luminaire [W]:	117	Working temperature [°C]:	from -40 to +50
Supply voltage [V]:	220 - 240	LED lifespan L90B10 [h]:	100000
AC voltage range [V]:	170 - 264	DIMM DALI:	yes
Frequency [Hz]:	50 - 60	Control:	Yes + 5-stage power reduction
Luminous flux [lm]:	18500	Protection type:	NTC
Luminous efficacy [lm/W]:	158	Net weight [kg]:	6.500
Energy efficiency class:	B	Warranty [years]:	10
Electrical protection class:	I	ULOR:	0%
Colour temperature [K]:	4000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour rendering index:	> 70	ENEC Certificate:	<a href="#">0228/ENEC/20/M1</a> <a href="#">0065/ENEC+/21/M1</a>
SDCM:	≤ 5	CE certificate:	<a href="#">63/2023</a>
Power factor:	0.98	Manual:	<a href="#">Manual</a>
Surge protection [kV]:	10		
Diffuser material:	toughened glass		
Diffuser type:	transparent		
Optics material:	PMMA		
Optics:	RM3		
Exchangeable source:	yes		
Material of the body:	powder coated aluminium		
Colour of the body:	grey		
Dimensions (H/W/T/S) [mm]:	870/262/122		

## LIGHT CURVES



# TIARA LED L PRO 18500LM 740 RM3 IP66 I CL. DALI (117W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00184	mounting grip 78 mm TIARA LED



wall holder (galvanized) (314049)



wall holder (grey) (314056)



mounting grip 78 mm TIARA LED (UL00184)

Card creation date: 11 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 63/2023