

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30  
Product code : 45020  
Type of product : Lubricant

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Function or use category : Lubricants and additives

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

77 Lubricants  
1761 JA - The Netherlands  
T +31 (0)78 6527652  
[technical@77lubricants.nl](mailto:technical@77lubricants.nl) - [www.77lubricants.nl](http://www.77lubricants.nl)

**1.4. Emergency telephone number**

Emergency number : +31 (0)78 6527652  
Monday to Friday: 09:00 - 16:00 (CET)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Not classified

**Adverse physicochemical, human health and environmental effects**

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

EUH-statements : EUH210 - Safety data sheet available on request.

**2.3. Other hazards**

Other hazards not contributing to the classification : Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Not applicable

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] substance with a Community workplace exposure limit (Note L)	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	50 – 75	Not classified
1-Decene, homopolymer, hydrogenated	(CAS-No.) 68037-01-4 (EC-No.) 500-183-1 (REACH-no) 01-2119486452-34	10 – 25	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based substance with a Community workplace exposure limit (Note L)	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (EC Index-No.) 649-483-00-5 (REACH-no) 01-2119474889-13	2,5 – 5	Not classified
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] substance with a Community workplace exposure limit (Note L)	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-27	1 – 5	Not classified
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	(CAS-No.) 125643-61-0 (EC-No.) 406-040-9 (EC Index-No.) 607-530-00-7 (REACH-no) 01-0000015551-76, 01-2119830067-43	0,5 – 2,5	Aquatic Chronic 4, H413
Bis(nonylphenyl)amine	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	0,5 – 2,5	Aquatic Chronic 4, H413 (M=0)
Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate	(CAS-No.) 93819-94-4 (EC-No.) 298-577-9 (REACH-no) 01-2119543726-33	0,5 – 2,5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate	(CAS-No.) 93819-94-4 (EC-No.) 298-577-9 (REACH-no) 01-2119543726-33	( 6,25 <C ≤ 100) Skin Irrit. 2, H315 ( 10 <C ≤ 12,5) Eye Irrit. 2, H319 ( 12,5 <C ≤ 100) Eye Dam. 1, H318

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after ingestion	: After adequate first aid, no further treatment is required unless symptoms reappear.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Eliminate all ignition sources if safe to do so.
Emergency procedures	: Ventilate spillage area.

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	--

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.  
Storage temperature : 40 °C  
Storage area : Store away from heat. Store in a well-ventilated place.  
Special rules on packaging : Keep only in original container. Store in a closed container.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

##### EU - Occupational Exposure Limits

IOELV TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
--------------------------------	---------------------

##### Belgium - Occupational Exposure Limits

Limit value (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
----------------------------------	---------------------

##### Bulgaria - Occupational Exposure Limits

OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
------------------------------	---------------------

##### Croatia - Occupational Exposure Limits

GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
--	---------------------

##### Czech Republic - Occupational Exposure Limits

Expoziční limity (PEL) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
---	---------------------

Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
---	----------------------

##### Denmark - Occupational Exposure Limits

Grænsevædi (8 timer) (mg/m <sup>3</sup> )	1
---	---

##### Netherlands - Occupational Exposure Limits

Grenswaarde TGG 8H (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
---	---------------------

##### USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
--------------------------------	---------------------

ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
---------------------------------	----------------------

##### Bis(nonylphenyl)amine (36878-20-3)

##### USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
--------------------------------	---------------------

ACGIH STEL (mg/m <sup>3</sup> )	10 fibers/cm <sup>3</sup>
---------------------------------	---------------------------

ACGIH STEL (ppm)	0 ppm
------------------	-------

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)

#### USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

#### EU - Occupational Exposure Limits

IOELV TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
IOELV STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

#### Bulgaria - Occupational Exposure Limits

OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

#### Croatia - Occupational Exposure Limits

GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

#### Czech Republic - Occupational Exposure Limits

Expoziční limity (PEL) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

#### Denmark - Occupational Exposure Limits

Grænsevædi (8 timer) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
---	---------------------

#### Netherlands - Occupational Exposure Limits

Grenswaarde TGG 8H (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
---	---------------------

### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

#### EU - Occupational Exposure Limits

IOELV TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
IOELV STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

## 8.2. Exposure controls

### Appropriate engineering controls:

Use adequate ventilation to keep oil mist below applicable standard. Use splash goggles when eye contact due to splashing is possible. Ocular shower with suitable liquid.

### Personal protective equipment:

Gloves. Safety glasses. Protective clothing. Avoid all unnecessary exposure.

### Materials for protective clothing:

Wear suitable protective clothing

### Hand protection:

Breakthrough time : refer to the recommendations of the supplier

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Eye protection:

Chemical goggles or safety glasses. Use splash goggles when eye contact due to splashing is possible. EN 166

### Skin and body protection:

Avoid prolonged and repeated contact with skin. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn

### Respiratory protection:

Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Particle filter. EN 143

### Personal protective equipment symbol(s):



### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -33 °C
Boiling point	: No data available
Flash point	: > 201 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 858 kg/m <sup>3</sup> @15°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 70 mm <sup>2</sup> /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5,53 mg/l/4h

### **1-Decene, homopolymer, hydrogenated (68037-01-4)**

LD50 oral (rat)	5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	5,2 mg/l/4h

### **reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)**

LD50 oral (rat)	> 2000 mg/kg bodyweight
LD50 dermal (rat)	> 2000 mg/kg bodyweight

### **Bis(nonylphenyl)amine (36878-20-3)**

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rat)	> 2000 mg/kg bodyweight

### **Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)**

LD50 oral (rat)	2600 mg/kg bodyweight Animal: rat, Animal sex: male
LD50 dermal (rabbit)	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5,53 mg/l/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
----------------------------	----------------------

### 1-Decene, homopolymer, hydrogenated (68037-01-4)

NOAEL (oral, rat, 90 days)	4159,4 mg/kg bodyweight/day
NOAEL (subacute, oral, animal/male, 28 days)	6245 mg/kg bodyweight

### reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

NOAEL (oral, rat, 90 days)	5 mg/kg bodyweight
----------------------------	--------------------

### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

LOAEL (dermal, rat/rabbit, 90 days)	≈ 70 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (oral, rat, 90 days)	160 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight

Aspiration hazard : Not classified

### 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

Viscosity, kinematic	70 mm <sup>2</sup> /s @40°C
----------------------	-----------------------------



# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l Daphnia magna
NOEC chronic fish	10 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata

#### **reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)**

LC50 fish 1	> 1000 mg/l Danio rerio
EC50 Daphnia 1	> 1000 mg/l Daphnia magna
EC50 72h algae (1)	> 3 mg/l Desmodesmus subspicatus
NOEC (chronic)	≤ 0,01 mg/l Daphnia magna Duration: '21 d'

#### **Bis(nonylphenyl)amine (36878-20-3)**

LC50 fish 1	> 100 mg/l Danio rerio
EC50 Daphnia 1	> 100 mg/l
EC50 72h algae (1)	100 mg/l Desmodesmus subspicatus

#### **Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)**

LC50 fish 1	4,5 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 Daphnia 1	5,4 mg/l Test organisms (species): Daphnia magna
EC50 72h algae (1)	2,1 mg/l Test organisms (species): other:Selenastrum capricornutum UTEX 1648
EC50 72h algae (2)	2 mg/l Test organisms (species): other:Selenastrum capricornutum UTEX 1648
EC50 96h algae (1)	2,1 mg/l Test organisms (species): other:Selenastrum capricornutum UTEX 1648
EC50 96h algae (2)	2 mg/l Test organisms (species): other:Selenastrum capricornutum UTEX 1648
ErC50 (algae)	2,1 mg/l

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h algae (1)	3 mg/l

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.2. Persistence and degradability

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

### reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Persistence and degradability	Not readily biodegradable.
Biodegradation	28D

### Bis(nonylphenyl)amine (36878-20-3)

Persistence and degradability	Not readily biodegradable.
Biodegradation	1 % 28d

### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

Persistence and degradability	Not readily biodegradable.
Biodegradation	1,5 % OECD-testrichtlijn 301 B

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

Persistence and degradability	Not biodegradable.
Biodegradation	31 % 28 d OECD 301F

### 12.3. Bioaccumulative potential

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

Partition coefficient n-octanol/water (Log Kow)	> 4
---	-----

### reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Bioconcentration factor (BCF REACH)	260 35 D, Oncorhynchus mykiss (regenboogforel)
Partition coefficient n-octanol/water (Log Pow)	9,2

### Bis(nonylphenyl)amine (36878-20-3)

Bioconcentration factor (BCF REACH)	1730
Partition coefficient n-octanol/water (Log Pow)	3,64 – 7,02
Bioaccumulative potential	Bioaccumulative potential.

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)

Partition coefficient n-octanol/water (Log Pow)	0,9 @23°C
---	-----------

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

Partition coefficient n-octanol/water (Log Pow)	9,2
---	-----

### 12.4. Mobility in soil

#### reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

#### Bis(nonylphenyl)amine (36878-20-3)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

#### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate) (93819-94-4)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : Not applicable

#### IMDG

Transport hazard class(es) (IMDG) : Not applicable

#### IATA

Transport hazard class(es) (IATA) : Not applicable

#### ADN

Transport hazard class(es) (ADN) : Not applicable

#### RID

Transport hazard class(es) (RID) : Not applicable

### 14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

No data available

#### Transport by sea

No data available

#### Air transport

No data available

#### Inland waterway transport

No data available

#### Rail transport

No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

##### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Netherlands

Ministry's list of carcinogens

: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate), Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed

Ministry's list of mutagens

: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate), Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed

NON-exhaustive list of reproductive toxins -

: None of the components are listed

Breastfeeding

NON-exhaustive list of reproductive toxins - Fertility

: None of the components are listed

NON-exhaustive list of reproductive toxins -

: None of the components are listed

Evolution

### Denmark

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level

# 45020 - ENGINE OIL SYNTHETIC UHPD 5W-30

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PNEC	Predicted No-Effect Concentration
PBT	Persistent Bioaccumulative Toxic
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness