

**PHILIPS****Lighting**

# Fortimo FastFlex gen 4+



## Fortimo FastFlex LED 2x6/840 DA G5

Fortimo FastFlex DA & DP gen 5 is our 'one-fits-all-solution' for outdoor applications. The new generation comes with an efficiency upgrade and a larger selection.

### Product data

General Information	
Lighting Technology	LED
Light Technical	
Luminous Flux	2,680 lm
Life to 70% Lumen Maintenance	100.000 hour(s)
Color Consistency Initial	5
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	150 lm/W
Color rendering index (CRI)	80
Temperature	
T-Case Lifetime (Max)	85 °C
T-Case Maximum (Max)	95 °C
Mechanical and Housing	
Overall length	172.20 mm
Overall width	49.50 mm
Overall height	1.60 mm
Dimensions (Height x Width x Depth)	2 x 50 x 172 mm
Net Weight (Piece)	30.000 g

Approval and Application	
Energy Efficiency Class	D
Approval Marks	CE marking ENEC certificate UL certificate Zhaga compliant
EPREL Registration Number	1008237
Remarks	Please download the Lighting - Product Data Sheet for more information and ordering options
Product Data	
Order product name	Fortimo FastFlex LED 2x6/840 DA G5
Full product name	Fortimo FastFlex LED 2x6/840 DA G5
Full product code	871951431834200
Order code	929002867306
Material Nr. (12NC)	929002867306
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514318342
Numerator - Packs per outer box	25
EAN/UPC - Case	8719514318359

## Fortimo FastFlex gen 4+



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

[www.lighting.philips.com](http://www.lighting.philips.com)  
2024, September 30 – data subject to change