








Specificații tehnice




[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă - în coloanele 1, 5]

Numărul procedurii de achiziție: Informația o găsiți în SIA RSAP.
Obiectul achiziției: Sistemul video de supraveghere în incinta Casei Radio din str. Miorița 1

Denumirea bunurilor/ serviciilor	Denumirea modelului bunului/ serviciului	Țara de origin e	Produ că torul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standar de de referin ță
1	2	3	4	5	6	7
Sistemul video de supraveghere în incinta Casei Radio din str. Miorița 1						
<p style="text-align: center;">Lotul nr. 1 1.1. Cameră IP PoE</p> <div style="text-align: center;">   </div> <div style="text-align: center;">  </div>	<p>Camera IP Tiandy TC-C38WS 3LRA-28 (8MP, externa, Mic)</p>	CHINA	TIANDY	<p>ColorNIGHT + HikConnect 8mpx 1/2.7" Progressive Scan CMOS (3840 × 2160), Intelligence G2: Human / Auto detection, video sabotage (camera shift, lens covering, defocus), area of interest (increased control). Matrix 1/3 Progressive Scan CMOS, sensitivity 0.001 Lux (F1.0). Compression codecs H.265+ Built-in sensitive microphone and SPEAKER with environmental noise filter and MP2L2, AAC audio codec. Slot for microSD cards up to 512 GB. Hibrid (IR+LED) illumination up to 40 meters. <i>Garanția minimă: 2 ani</i></p>	<p>Caracteristici principale:</p> <ul style="list-style-type: none"> Rezoluție: 8MP (3840×2160@20fps) Compresie: S+265/H.265/H.264/M otion JPEG Sensibilitate: 0.002 Lux@(F1.6, AGC ON), 0 Lux cu IR activ Distanță iluminare IR: până la 50m Microfon încorporat Stocare: microSD/microSDHC/m icroSDXC până la 512GB Funcții inteligente: clasificare persoane/vehicule Condiții de funcționare: -35°C ~ +65°C, ≤95%RH 	

					<ul style="list-style-type: none"> Alimentare: DC12V ±25% / PoE (IEEE 802.3af) Carcasă: Metal, IP67
<p>1.2. Digital video recorder</p>  	<p>Network video recorder Tiandy TC-R3440 (40ch, 4HDD) Spec: I/B/N/H/C /V4.0</p>	<p>CHINA</p>	<p>TIANDY</p>	<p>HikConnect 32 Channels, 8Mpx. Real-time! H265/H264+ HDMI (4K 3840x2160), VGA (1920x1080), 2*USB 2.0, Gigabit LAN. 1 HDD SATA-II 6 TB 32 Channels, Bitrate - 256 Mbps, H.265+/H.265/ H.264+/H.264, HDMI 4K (3840x2160), VGA (1920x1080), Va include additional HDD de 4 tb. <i>Garanția minimă: 2 ani</i></p>	<p>HD Input</p> <ul style="list-style-type: none"> ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Up to 40 IP cameras can be connected ·Supports live view, storage, and playback of the connected camera at up to 12MP resolution <p>HD Output</p> <ul style="list-style-type: none"> ·HDMI and VGA independent outputs ·HDMI Video output at up to 4K (3840 × 2160) resolution <p>HD Storage</p> <ul style="list-style-type: none"> ·4 SATA interfaces connectable for recording and backup, up to 10TB for each HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% <p>HD Transmission</p> <ul style="list-style-type: none"> ·2×RJ45 self-adaptive 10/100/1000 Mbps network interfaces <p>Various Applications</p> <ul style="list-style-type: none"> ·Centralized management of IP cameras, including configuration, information import/export, real-time

					<p>information display, two-way audio, upgrade, etc.</p> <ul style="list-style-type: none"> ·Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VCA alarms can be realized ·VCA detection alarm is supported ·Smart search for the selected area in the video and smart playback to improve the playback efficiency ·Web6 supports plug-in-free browsing and can preview videos on all browsers
<p>1.3. Switch PoE</p> 	<p>Switch POE ZKTeco PE082-120-C (8 POE + 2 uplink)</p>	<p>CHINA</p>	<p>ZK TECO</p>	<p>10/100M 8 ports+ 2 Uplink SMART POE Switch,AF Standard, 15.4W each port, Support Solid Vlan & Extend 250meters, External Power Supply, METAL CASE! <i>Garanția minimă: 2 ani</i></p>	<p>8*10/100M RJ-45(POE)+2*10/100M RJ-45</p> <ul style="list-style-type: none"> • Conforms to IEEE 802.3,IEEE 802.3u and IEEE802.3af/at • The max. PoE power output is 15.4 W (IEEE 802.3af)/ 30 W (IEEE 802.3at) • 250 meters of PoE transmission distance of power and data (Cat 6) • MDI/MDIX self-adaptation • Store-and-forward switching • Lightning protection
<p>1.4. Cable UTP</p> 	<p>Cablu computer CAT 5 UTP Cupru cu tross (305m/rol 1) UNV</p>	<p>CHINA</p>	<p>UNV</p>	<p>UTP cable Cat5e CUPRU 100% Exterior BC 4*2*0.5BC+ID 0.9HDPE+Rip Cord+OD5.1PVC (305m in Box). FLUKE test PASS! <i>Garanția minimă: 2 ani</i></p>	<p>UTP cable Cat5e CUPRU 100% Exterior BC 4*2*0.5BC+ID 0.9HDPE+Rip Cord+OD5.1PVC (305m in Box). FLUKE test PASS! <i>Garanția minimă: 2 ani</i></p>

<p>1.5. Doza 116/116/50 Special pentru camera</p> 	<p>5 Cutie de distributie 100C 100*100*70</p>	<p>CHINA</p>	<p>ZOLL</p>	<p>Doza 116/116/50 Special pentru camere supraveghere protectie ip64</p>	<p>Cutie de distributie 100C 100*100*70</p>	
<p>1.6. Consumabile Elemente de fixare, canal de cablu, conectori</p> 				<p>Șuruburi (lemn/metal), dibluri, șuruburi de ancorare și tije filetate Canale de cablu și accesorii: Jgheaburi PVC, coturi și capace tub flexibil PVC cu suporturi de fixare și cleme coliere din plastic (șoricei), cleme și doze de ramificație pentru conexiuni Cablul electric tub gofrat conector rj45</p>		
<p>1.7. Servicii</p> 				<p>Lucrări de instalare: Pozarea cablurilor, montarea camerelor, a înregistratoarelor, controllerelor și echipamentelor de rețea Conexiuni și comutare: Instalarea surselor de alimentare, sertizarea și conectarea fizică a dispozitivelor Configurare și punere în funcțiune: Setare parametri rețea, funcții inteligente, acces la distanță și notificări. Finalizare: Testarea funcționalității sistemului, instruirea utilizatorilor, predarea obiectivului la cheie. Instalare / configurare</p>		

Pelipetchi Boris

În calitate de: Administrator

Ofertantul: LISNIC ALARM SRL

Adresa: Chisinau, str. Pietrarilor 2/1

06/05/2026