

Laboratory Incubator

- ◆Microprocessor control,
- ◆Digital display setting and actual temperature
- ◆Over temperature alarm, PID self-tuning
- ◆Digital display running timer,
- ◆Stainless steel interior
- ◆Electricity leakage protection.
- ◆With glass inner door, With hidden door locks,
- ◆Mechanical overheat protection, cut off the heating sources
- ◆Automatic alarm after operation



• IB-9052A



- ◆Microprocessor control
- ◆Digital display setting and actual temperature
- ◆Over temperature alarm, PID self-tuning
- ◆Digital display running timer,
- ◆Stainless steel interior
- ◆With glass observe window
- ◆Automatic alarm after operation

• DNP-9052A

Model	IB-9025A	IB-9052A	IB-9082A	IB-9162A	IB-9272A
Capacity	15L	50L	80L	160L	270L
Working size (mm)	250x250x250	350x350x410	400x400x500	500x500x650	600x600x750
Power	150W	250W	300W	400W	600W
Temperature range	RT+5~65°C				
Temperature resolution	0.1°C				
Temperature fluctuation	±0.5°C				
Timer	0-9999min				
Voltage	110V 60Hz / 220V 50Hz				
Dimension(mm)	380x370x580	480x470x740	530x530x840	640x630x1000	730x720x1090
Weight	21kg	35kg	38kg	64kg	86kg