

# Pharmacy Refrigerator

**HYC-290**



#### Frequency Conversion Energy Saving

Variable frequency compressor with optimized cooling system, more energy efficient.



#### Environmentally Friendly

Hydrocarbon compressor and refrigerant, the refrigerant does not contain any fluorine or chlorine which is super friendly to the environment.



#### Large Space, Superior Uniformity

The space is efficiently used, and the utilization rate is high and the temperature uniformity is  $\pm 3$  C.



#### Low Noise

Optimized system and noise reduction design to reduce the noise level to 41dB(A) (220V/50Hz).



#### Stable performance, multiple alarm modes

Three alarm modes (light, sound, remote); six types of alarm.



#### Microprocessor Control System



#### Self Closing Door with 90° Stay Open Feature.



#### Precise Temperature Control



#### Security lock



#### Optional USB and Printer

CCAT Scientific

0800 222 812

info@ccat.co.nz

More pharmacy fridges at  
haiermedical.co.nz

**Qingdao Haier Biomedical Co.,Ltd.**

No.280 Feng Yuan Road, High-tech Zone,  
Qingdao, 266109, P.R. China  
Tel: +86-0532-88935955  
Website: www.haiermedical.com



Haier Biomedical  
International



Haier Biomedical  
International



@haiermedicalint



@haierbiomedicalint



Haier Biomedical  
International

## Scope of Application



*This product is suitable for pharmacy, pharmaceutical manufacturers, anti-epidemic stations, health centers and hospitals as key examples, which is used to store biological products and articles that need to be stored at 2~8°C.*

## Specifications



### HYC-290

#### Technical Data

Cabinet Type	Upright, glass door	
Climate Class	N	
Cooling Type	Forced air cooling	
Defrost Mode	Auto	
Refrigerant	HC	
Noise((dB(A))	43	43

#### Performance

Temp Range(°C)	2~8	
----------------	-----	--

#### Control

Controller	Microprocessor	
Display	LED	

#### Electrical Data

Power Supply(V/Hz)	220~240/50&60	115/60
Power(W)	350	200
Electrical Current(A)	1.8	2.2

#### Dimensions

Capacity(L/Cu.Ft)	290/10.2	
Net/Gross Weight(approx)	(kg)	105/127
	(lbs)	231.6/280.1
Interior Dimension(W*D*H)	(mm)	530*555*1080
	(in)	20.9*21.9*42.5
Exterior Dimension(W*D*H)	(mm)	665*710*1665
	(in)	26.2*28.0*65.6
Packing Dimension(W*D*H)	(mm)	690*790*1810
	(in)	27.1*31.0*71.1
Container Load(20'/40'/40'H)	21/42/42	



#### Accessories

Caster	Y	
Foot	Y	
Porthole	Y	
Shelves/Drawers	5/-	
USB Interface	Optional	Y
Temperature Recorder	Optional	

#### Alarms

High/Low Temp	Y	
Remote System	Y	
Power Failure	Y	
Sensor Error	Y	
Low Battery	Y	
Door Ajar	Y	

#### Other

Certificate	CE	UL
-------------	----	----