

Specificații tehnice (F4.1)

Numărul licitației:	21008898	Data: „18” iunie 2019	Alternativa nr.: _____
Denumirea licitației:	Echipament de rețea	Lot: _____	Pagina: 1 din 5

Cod CPV	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7	8
	Bunuri/Servicii:						
	Lotul 1						
32420000-3	Router ethernet	MIKROTIK CCR1036-8G-2S+	Letonia	Mikrotik	Ethernet Router; Rack mount carcasa; 8x Gigabit Ethernet ports; 2xSFP+ ports (DDMI support); CPU Minim 36 cores x 1.2GHz; Minim 4GB SODIMM DDR3 RAM; Storage size minim 1 GB; AC input range 100-240; Memory card support (microSD); 1x Serial port DB9 RS232C; 1x USB slot type microUSB type AB; CPU temperature monitor; Current Monitor; PCB temperature monitor; Voltage Monitor; Fan speed controlled; 41.5mpps; Up to 28Gbit/s throughput; Garantie minim 36 luni NBD	Ethernet Router; Rack mount carcasa; 8x Gigabit Ethernet ports; 2xSFP+ ports (DDMI support); CPU Minim 36 cores x 1.2GHz; Minim 4GB SODIMM DDR3 RAM; Storage size minim 1 GB; AC input range 100-240; Memory card support (microSD); 1x Serial port DB9 RS232C; 1x USB slot type microUSB type AB; CPU temperature monitor; Current Monitor; PCB temperature monitor; Voltage Monitor; Fan speed controlled; 41.5mpps; Up to 28Gbit/s throughput; Garantie minim 36 luni NBD	
	Total lot 1						

	Lotul 2						
32420000-3	Switch	MIKROTIK CRS326-24G-2S+RM	Letonia	Mikrotik	Switch cu management ; Rack mount carcasa; 24x 10/100/1000 Ethernet ports; 2x SFP+ port suport 1.25 Gb SFP si 10 Gb SFP+, 26 port non blocking wire speed Switch Chip; 1x RJ45 serial port; Minimum 800 Mhz CPU; Minimum 512 MB RAM; Storage size minim 16MB; Passive PoE in 11-30 V; OS featuring: Non-blocking Layer 2 switching capacity, 16K host table, IEEE 802.1Q VLAN, suport pina la 4K simultan VLANs, Port isolation, Port security, Broadcast storm control, Port mirroring of ingress/egress traffic, Rapid Spanning Tree Protocol, Access Control List, neighbor discovery, SNMP v1, Web-based GUI, Telnet, SSH, Garantie minim 36 luni NBD	Switch cu management ; Rack mount carcasa; 24x 10/100/1000 Ethernet ports; 2x SFP+ port suport 1.25 Gb SFP si 10 Gb SFP+, 26 port non blocking wire speed Switch Chip; 1x RJ45 serial port; Minimum 800 Mhz CPU; Minimum 512 MB RAM; Storage size minim 16MB; Passive PoE in 11-30 V; OS featuring: Non-blocking Layer 2 switching capacity, 16K host table, IEEE 802.1Q VLAN, suport pina la 4K simultan VLANs, Port isolation, Port security, Broadcast storm control, Port mirroring of ingress/egress traffic, Rapid Spanning Tree Protocol, Access Control List, neighbor discovery, SNMP v1, Web-based GUI, Telnet, SSH, Garantie minim 36 luni NBD	
32420000-3	Switch	MIKROTIK CRS309-1G-8S+IN	Letonia	Mikrotik	Switch cu management; min 8x SFP+ ports cu support suport 1.25 Gb SFP si 10 Gb SFP+, Min 1x 10/100/1000 Ethernet ports; Minimum 800 Mhz CPU; Minimum 512 MB RAM; Storage size minim 16MB; Min 1x Serial port RS232; PoE in 802.3af/at; OS featuring: Non-blocking Layer 2 switching capacity, 16K host	Switch cu management; min 8x SFP+ ports cu support suport 1.25 Gb SFP si 10 Gb SFP+, Min 1x 10/100/1000 Ethernet ports; Minimum 800 Mhz CPU; Minimum 512 MB RAM; Storage size minim 16MB; Min 1x Serial port RS232; PoE in 802.3af/at; OS featuring: Non-blocking Layer 2 switching capacity, 16K host	

					table, IEEE 802.1Q VLAN, suport pina la 4K simultan VLANs, Port isolation, Port security, Broadcast storm control, Port mirroring of ingress/egress traffic, Rapid Spanning Tree Protocol, Access Control List, neighbor discovery, SNMP v1, Web-based GUI, Telnet, SSH, Garantie minim 36 luni NBD	table, IEEE 802.1Q VLAN, suport pina la 4K simultan VLANs, Port isolation, Port security, Broadcast storm control, Port mirroring of ingress/egress traffic, Rapid Spanning Tree Protocol, Access Control List, neighbor discovery, SNMP v1, Web-based GUI, Telnet, SSH, Garantie minim 36 luni NBD	
	Total lot 2						
	Lotul 3						
32420000-3	SFP Transceiver	SFP Transceiver 1.25G WDM pereche (2 buc) (1310TX + 1550TX), MIKROTIK compatibil	China	Eoptolink	SFP 1.25G Tx1310/Rx1550nm 5KM SC WDM / SFP 1.25G Tx1550/Rx1310nm 5KM SC WDM, Compatibile cu routere si switch solicitate la Lotul 1, 2 Garantie minim 36 luni NBD	SFP 1.25G Tx1310/Rx1550nm 5KM SC WDM / SFP 1.25G Tx1550/Rx1310nm 5KM SC WDM, Compatibile cu routere si switch solicitate la Lotul 1, 2 Garantie minim 36 luni NBD	
	Total lot 3						
	Lotul 4						
32420000-3	ACCES POINT	Ubiquiti UAP-AC-HD	USA	Ubiquiti	Tip: 802.11ac Wave 2 Enterprise Wi-Fi Access Point; dirijarea cu ajutorul Wireless Controller; Posibilitatea de montare pe tavan si perete cu toate materialele necesare in complet; Beamforming; Radio Hardware Acceleration; Simultaneous Dual-Band 4x4 Multi-User MIMO	Tip: 802.11ac Wave 2 Enterprise Wi-Fi Access Point; dirijarea cu ajutorul Wireless Controller; Posibilitatea de montare pe tavan si perete cu toate materialele necesare in complet; Beamforming; Radio Hardware Acceleration; Simultaneous Dual-Band 4x4 Multi-User MIMO	

					<p>Specificatie tehnica: 2,4 GHz MIMO (4x4 800 Mbps) + 5 Ghz MIMO (4x4 1733 Mbps); 2x Dual-Port, Dual-Polarity Antennas 2,4GHz 3 dBi each; 2x Dual-Port, Dual-Polarity Antennas 5GHz 4 dBi each; Suport: Multiple SSID, VLAN, Advanced QoS, WMM, Hotspot; Guest Traffic Isolation; 802.3at PoE+ 44to57VDC; Maximum TX Power: 2.4 GHz - 25 dBm; 5 GHz - 25 dBm</p> <p>Porturi: 2x 10/100/1000 Ethernet Port</p> <p>Performanta: Sa fie asigurate minim 200 conexiuni paralele.</p> <p>Protocoale: 802.11 a/b/g/n/ac/ac-wave2</p> <p>Wireless Security: WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)</p> <p>802.11w/PMF</p> <p>Garanție: minim 24 luni NBD</p>	<p>Specificatie tehnica: 2,4 GHz MIMO (4x4 800 Mbps) + 5 Ghz MIMO (4x4 1733 Mbps); 2x Dual-Port, Dual-Polarity Antennas 2,4GHz 3 dBi each; 2x Dual-Port, Dual-Polarity Antennas 5GHz 4 dBi each; Suport: Multiple SSID, VLAN, Advanced QoS, WMM, Hotspot; Guest Traffic Isolation; 802.3at PoE+ 44to57VDC; Maximum TX Power: 2.4 GHz - 25 dBm; 5 GHz - 25 dBm</p> <p>Porturi: 2x 10/100/1000 Ethernet Port</p> <p>Performanta: Sa fie asigurate minim 200 conexiuni paralele.</p> <p>Protocoale: 802.11 a/b/g/n/ac/ac-wave2</p> <p>Wireless Security: WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)</p> <p>802.11w/PMF</p> <p>Garanție: minim 24 luni NBD</p>	
	Total lot 4						
	Lotul 5						
32420000-3	Router Wi-Fi	TP-LINK Archer C60	China	TP-LINK	<p>Router</p> <p>Porturile WAN: 1 x RJ-45</p> <p>Porturi LAN: 4 x RJ-45 (10/100 Mbps)</p> <p>USB Host: 1 x USB</p> <p>Wi-Fi</p>	<p>Router</p> <p>Porturile WAN: 1 x RJ-45</p> <p>Porturi LAN: 4 x RJ-45 (10/100 Mbps)</p> <p>USB Host: 1 x USB</p> <p>Wi-Fi</p>	

					<p>Frecvența: 2,4/5 GHz Viteza maximă: 867Mbps on 5GHz + 300Mbps on 2.4GHz Standartele de comunicare: 802.11 a/b/g/n/ac Cifrare: da Puterea de ieșire: 20 dBm Amplificarea antenei: 2 x 5 dBi Conector pentru antenă: SMA Interfețe Gestionarea: web-interfața</p>	<p>Frecvența: 2,4/5 GHz Viteza maximă: 867Mbps on 5GHz + 300Mbps on 2.4GHz Standartele de comunicare: 802.11 a/b/g/n/ac Cifrare: da Puterea de ieșire: 20 dBm Amplificarea antenei: 2 x 5 dBi Conector pentru antenă: SMA Interfețe Gestionarea: web-interfața</p>	
	Total lot 5						
	TOTAL						

Semnat: _____ Numele, Prenumele: **Alexandrov Tatiana** În calitate de: **Administrator**

Ofertantul: „ENTEGRA-PLUS” SRL Adresa: **str. Petru Zadnipru 10, of. 96, Chisinau, R. Moldova**