

PANTHER

AS350

**Fast, Furious, Accurate
Dominate Your PC World**

Read Up to
560 MB/s

Write Up to
540 MB/s

3D TLC



AS350 SATA III SSD

AS350 operates at SATA III interface with the sequential read and write speed of up to 560/540 MB/s, making it a perfect companion for budding gamers on a budget.

Features

- Compatible with SATA III 6.0 Gb/s Interface
- Sequential Read/Write Speed up to 560/540MB/s
- Supports SATA Power Management
- Supports S.M.A.R.T. Command
- Supports TRIM & NCQ Command
- Advanced Wear Leveling & ECC Function

Specifications

- Form Factor : 2.5"
- Interface : SATA III 6Gb/s
- Capacity : 128GB / 256GB / 512GB / 1TB
- NAND Flash : 3D TLC
- MTBF : 1,500,000 hours
- Temperature Range
 - Standard Operating : 0°C ~ +70°C
 - Storage : -40 ~ +85°C
- Shock : 1500G/0.5msec
- Dimensions (L x W x H)
 - (L)100 x (W)69.9 x (H)7 mm
- Weight : 48g
- Warranty : 3 Years Limited


Performance*

Capacity	Sequential Performance (Up to)		4K Random (Up to)		Endurance (TBW)
	Read (MB/s)	Write (MB/s)	Read (IOPS)	Write (IOPS)	
128GB	560	540	38K	75K	75
256GB	560	540	81K	74K	180
512GB	560	540	87K	80K	320
1TB	560	540	93K	80K	600

*The performance may vary due to host hardware, software, usage and storage capacity.

Ordering Information

Capacity	Part Number	EAN Code
128GB	AP128GAS350-1	4712389916952
256GB	AP256GAS350-1	4712389916969
512GB	AP512GAS350-1	4712389916228
1TB	AP1TBAS350-1	4712389916945



Apacer Technology Inc.

1F, No.32, Zhongcheng Rd., Tucheng Dist.
New Taipei City 236, Taiwan R.O.C.
Tel: +886-2-2267-8000
Fax: +886-2-2267-3410

Разъем-вилка 8P8C для сетевого кабеля

LC-8P8C-002/100



Особенности

- Разъем-вилка 8P8C для кабеля локальной сети, золоченые контакты 30 микродюймов
- Наилучшая поддержка одножильных проводов кабелей категории 6

Спецификация

Max. insulated wire diameter: 1.05 mm
Not suitable for thicker FTP CAT6 LAN cables like FPC-6004-SO

Упаковка

Кол-во в коробке, шт	50
Объем коробки, куб.м.	0.02774
Вес коробки, кг	8.5
Размеры индивидуальной упаковки ДхШхВ:	140x115x50 mm
Размеры картонной коробки ДхШхВ:	380x365x200 mm
Страна происхождения	CN
Баркод	8716309101387
Таможенный код	8536699099

Содержимое упаковки

Carton contains bags with 100 pcs

Сертификаты



AC1300 Wireless Dual Band Gigabit Router

Model: AC12G



// Highlights


- Lag-Free Dual Band Wi-Fi – 867 Mbps on 5 GHz + 400 Mbps on 2.4 GHz[†]
- Premium Wired Performance – Full Gigabit ports for ultra-fast data transfer speeds
- Maximized Wi-Fi Coverage – 4× High-Gain Antennas with Beamforming
- Connect More at Once – MU-MIMO creates more simultaneous connections[‡]



// Applications



Ideal for large homes with multiple rooms and multiple users



Ideal for average internet users seeking fast downloads, seamless streaming audio, uninterrupted streaming video, and lag-free online gaming

// Features



Access Point Mode

Extends a wired network and makes it wireless



Parental Controls

Establish appropriate policies to protect children with responsible, safe internet access



IPTV Supported

Supports IGMP Proxy/Snooping, Bridge, and Tag VLAN to optimize IPTV streaming



Guest Network

Provides a separate network for guests to ensure your security and privacy



Quality of Service

Prioritizes devices you select to perform better




IPv6 Supported

Allows you to enjoy IPv6 services provided by your ISP and visit IPv6 websites

// Premium Wired Performance

Take full advantage of your broadband speed up to 1 Gbps with Gigabit ports—10× faster than standard Ethernet. Plug your PCs, IPTVs, and game consoles into the Gigabit LAN ports for fast, reliable wired connections.



Gigabit LAN Ports:
Connect to IPTVs,
Desktops, TV Boxes,
Game Consoles, etc.


**Gigabit
WAN Port:**
Connect to
the Internet

Power

WPS/Reset

// Boosted Wi-Fi Coverage

Four external 5 dBi antennas provide larger wireless coverage throughout your home or office. Advanced Beamforming technology automatically locates wireless devices and forms targeted, highly efficient wireless connections.



// Lag-Free Dual Band Wi-Fi

AC12G delivers blazing fast Wi-Fi speeds up to 1300 Mbps. Choose the 2.4 GHz band (400 Mbps) for internet browsing, email, and social media or the 5 GHz band (867 Mbps) for bandwidth-intensive tasks like HD streaming and gaming.[†]




// MU-MIMO Technology

MU-MIMO lets AC12G serve multiple devices simultaneously to reduce wait time, allowing connected devices to achieve faster speeds and more efficient communication.[‡]



AC12G with
MU-MIMO



Regular Router
without MU-MIMO

// Specifications

Physical Specifications

Ports

1 Gigabit WAN Port
3 Gigabit LAN Ports

Button

WPS/Reset Button

External Power Supply

12V/1A

Dimensions (W x D x H)

8.7 × 5.5 × 1.3 in (222 × 140 × 32 mm)

Antennas

4 × 5 dBi Fixed Omni-Directional Antennas

Package Contents

- AC1300 Wi-Fi Router AC12G
- Power Adapter
- RJ45 Ethernet Cable
- Quick Installation Guide

Wireless Specifications

Wireless Standards

IEEE 802.11a/n/ac 5GHz, IEEE 802.11b/g/n 2.4GHz

Frequency

EU: 2.4-2.5GHz, 5.17-5.25GHz
US: 2.4-2.5GHz, 5.17-5.25GHz, 5.73-5.83GHz

Signal Rate

400 Mbps at 2.4GHz, 867 Mbps at 5 GHz

Transmit Power

<20dBm (EIRP)

Reception Sensitivity

5GHz	2.4GHz
• 11a 6M: -96dBm	• 11g 6M: -97dBm
• 11a 54M: -77dBm	• 11g 54M: -80dBm
• 11ac 20M MCS8: -72dBm	• 11n 20M MCS7: -78dBm
• 11ac 40M MCS9: -67dBm	• 11n 40M MCS7: -75dBm
• 11ac 80M MCS9: -63dBm	

Wireless Function

Enable/Disable Wireless Radio, Wireless Statistics

Wireless Security

WPA-PSK / WPA2-PSK / WPA3-Personal[§]

Operation Specifications

Advanced Feature

- MU-MIMO: Communicates with multiple same time[†]
- AP Mode: Extends a wired network and makes it wireless
- Smart Connect: Intelligently chooses the best available band for each device
- QoS: Prioritizes devices you select to perform better

Port Forwarding

Virtual Server, UPnP, DMZ

Management

Access Control
Local Management
Remote Management

Firewall Security

IP and MAC Address Binding

Guest Network

2.4GHz Guest Network, 5GHz Guest Network

Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Operating Humidity: 10%~90% Non-Condensing
- Storage Humidity: 5%~90% Non-Condensing



cAP ax

The best-selling ceiling access point is back – stronger than ever!

A new generation of wireless greatness for your office,
hotel, mall, or any other setups in crowded areas.



FAST AND RELIABLE
802.11AX WIRELESS



MODERN QUAD-CORE
1.8 GHZ CPU



2X GIGABIT ETHERNET PORTS



POE-IN & POE-OUT TO POWER OTHER
DEVICES (LIKE CCTV CAMERAS!)



1GB OF RAM



ROUTEROS V7



MULTIPLE POWERING
OPTIONS



REMAINS HIDDEN IN
PLAIN SIGHT



MANAGE HUNDREDS OF
DEVICES EASILY WITH CAPsMAN
MANAGEMENT SYSTEM!



GEN
6

802.11ax
Wireless

When it comes to wireless network in the office, **you can't afford to cut corners and risk inhibiting your team's performance.** You need excellent coverage throughout the premises. You need a device that can handle a large number of clients. **You need a reliable, flexible, cost-effective solution: the cAP ax!**



Both open office and cubicle layouts usually encounter a variety of network issues: signal gets absorbed, reflected, it becomes unstable. Mirrors, tinted glass, TVs, metal file cabinets – all sorts of things can get in the way. Our solution is simple, effective, and elegant: let your access point rise above all the obstacles! In other words, **a ceiling access point is a great way to prevent signal loss in large, crowded areas with many obstacles.**

There is another benefit to this form-factor: cAP ax **remains hidden in plain sight**, attracting **less unwanted attention** than a smoke sensor. Your clients, guests, or colleagues won't even notice it. But they will definitely notice the blazing-fast wireless connection!

With the Generation6 802.11ax wireless standard, we're looking at up to **40% higher speed in the 5 GHz** and **up to 90% higher speed in the 2.4 GHz spectrum**, if we compare it to the previous generations! But what's more important than speed is the stability. Our latest AX devices can withstand and navigate even the toughest wireless interference scenarios, offering **the most stable and uninterrupted signal** to date!


cAP ax features a modern quad-core CPU running at 1.8 GHz, NAND storage, and a gigabyte of RAM. Enough to harvest the full potential of the most powerful networking software on the market – RouterOS v7! Complex firewall rules, IPsec hardware encryption, Wireguard, BGP, advanced routing, or multiple remote work VPN tunnels – cAP ax can do it all!



Compared to the previous generation, cAP ax offers multiple enhanced authentication types: OWE, WPA3-PSK, WPA3-EAP, and 802.11r roaming.


cAP ax is also a great way to make your office network installation and maintenance so much easier, as it features **PoE-in and PoE-out**. That's right – you can **use cAP ax to power other devices**, such as network switches, CCTV cameras, or even another cAP ax! And, speaking of easy office networks... **Just a few clicks** in our latest **wifiwave2 CAPsMAN central management system** - and you're done setting up **hundreds of cAP ax devices**! You can use all sorts of MikroTik devices to run CAPsMAN effortlessly, for example - your main gateway.

Use PoE-in and PoE-out to power cAP ax and other devices - like network switches!



We've included a 48V PSU.
That means you can power your IP-cameras
or another cAP ax right out of the box!

Quick cAP tip: the customizable mode button in the center will turn off cAP's lights, but you can reconfigure it to launch any RouterOS script.



• Specifications

Product code	cAPGi-5HaxD2HaxD
CPU	Quad core IPQ-6010 1.8 GHz
Size of RAM	1 GB
RAM type	DDR3L
Storage	128 MB, NAND
Number of 1G Ethernet ports	2
Wireless interface model	QCN-5022 (2.4 GHz), QCN-5052 (5 GHz)
Wireless	2.4 GHz 802.11b/g/n/ax dual-chain, 5 GHz 802.11a/n/ac/ax dual-chain
Antenna gain	5.5 dBi
Operating system	RouterOS v7, License level 4
Switch chip model	IPQ-6010
Dimensions	228 x 48 mm
Operating temperature	-40°C to +70°C tested

• Powering

PoE-in	802.3af/at
PoE-Out	Passive PoE up to 57V (<30V DC jack must be used, >30V PoE-In and DC jack can be used)
PoE-Out ports	Ether2, max out per port output (input < 30 V): 600 mA, max out per port output (input > 30 V): 400 mA. Over 300 mA current, please use DC jack for powering device.
Number of DC inputs	2
Supported input voltage	18-57 V (DC jack) 18-57 (PoE-In)
Max power consumption (without attachments)	11 W
Max power consumption	36 W

• Included parts



48 V 0.95 A
power adapter



Gigabit
PoE injector



Ceiling mount



Mounting bracket



Fastening
set

CRS326-24G-2S+RM

We are announcing a special version of the CRS326-24G-2S+RM switch, with added RouterOS as a second boot option, the new CRS326-24G-2S+RM.

This is a SwOS/RouterOS powered 24 port Gigabit Ethernet switch with two SFP+ ports, wire speed connectivity with several new switching features!

The “Dual boot” feature that allows you to choose which operating system you prefer to use, RouterOS or SwOS. If you prefer to have a simplified switch only OS with more switch specific features, use SwOS. If you are used to Winbox and would like the ability to use routing and other Layer 3 features on some ports in your CRS, boot and use RouterOS. You can select the desired operating system from RouterOS, from SwOS or from the RouterBOOT loader settings.

It gives you all the basic functionality for a managed switch, plus more: allows to manage port-to-port forwarding, apply MAC filter, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields. SFP cage supports both 1.25 Gb SFP and 10 Gb SFP+ modules.

Specifications

Product code	CRS326-24G-2S+RM
CPU	98DX3236A1 800 MHz
RAM	512 MB
Storage type	Flash, 16 MB
Switch chip model	98DX3236A1
10/100/1000 Ethernet ports	24
SFP+ cages	2
Operating system	SwOS /RouterOS (Dual boot)
Supported input voltage	9 - 30 V (jack or passive PoE)
Dimensions	443 x 144 x 44 mm
Operating temperature	-40°C .. +60°C tested
Max power consumption	24 W
Serial port	RJ45

Features

- Non-blocking Layer 2 switching capacity
- 16K host table
- IEEE 802.1Q VLAN
- Supports up to 4K VLANs
- Port isolation
- Port security
- Broadcast storm control
- Port mirroring of ingress/egress traffic
- Rapid Spanning Tree Protocol
- Access Control List
- MikroTik neighbor discovery
- SNMP v1
- Web-based GUI

Included



24 V 1.2 A power adapter



Rack ears



Screw set





CSS318-16G-2S+IN

Compact, efficient, and designed for effortless scalability.



Multiple mounting options supported:
10-inch racks, 19-inch racks, and two units side-by-side!



16 x

**1 GIGABIT
ETHERNET PORTS**

(SUPPORT 10M / 100M / 1G SPEEDS)



2 x

**10 GIGABIT
SFP+ PORTS**

(SUPPORT 1G / 2.5G / 10G SPEEDS,
depending on module)



MAC FILTERING &
VLANs



EASY TO STACK IN
1U RACK SPACE



CAN BE CONFIGURED
FROM YOUR WEB
BROWSER



PORT-TO-PORT
FORWARDING




TRAFFIC MIRRORING



SILENT FANLESS
PERFORMANCE

The CSS318-16G-2S+IN is a perfect fit for setups where **24 ports are too many** and **8 ports just aren't enough**. Its compact 10-inch form factor and cost-effective design make it the ideal solution for small and medium-sized offices, home networks, or rackmount environments where space and efficiency are key.

With **16 Gigabit Ethernet ports** and **2 SFP+ 10G uplink ports**, you get all the connectivity you need without unnecessary bulk. With its versatile mounting options, the CSS318-16G-2S+ **can be installed in 10-inch racks**, standard **19-inch racks**, or even side-by-side—fitting **two switches in a single 1U 19-inch space**.



Configuration is effortless with MikroTik's lightweight **SwOS**. Accessible directly from your web browser, SwOS gives you the core functionality of a managed switch and more:



- Port-to-port forwarding
- Broadcast storm control
- MAC filtering
- VLAN configuration
- Traffic mirroring
- Bandwidth limitation
- Adjustment of MAC and IP header fields



The CSS318 consumes just **10W without attachments** and **up to 13W under full load**, keeping your network reliable while saving power.

Compact, scalable, and simple to configure — the CSS318-16G-2S+IN is ready to enhance your network at an unbeatable price.

• Specifications

Product code	CSS318-16G-2S+IN
Storage	16 MB Flash
Number of 1G Ethernet ports	16
Number of 10G SFP+ ports	2
Switch chip model	98DX2518
Dimensions	218 x 157 x 44 mm
Operating system	SwOS (Min. version 2.17)
Operating temperature	-40°C to +70°C

• Powering

Number of AC inputs	1
Max current	0.197 A
AC input range	100-240 V
Max power consumption (without attachments)	10 W
Max power consumption	13 W

• Included parts



Power cord



Fastening set



Rack ears

RB260GS series

The RB260GS is a small SOHO switch. Two models are available, the RB260GS, and the RB260GSP, which features power output on its ethernet ports. Ports 2-5 can power other PoE capable devices with the same voltage as applied to the unit.


Both devices have five Gigabit Ethernet ports and one SFP cage, switching is done by an Atheros Switch Chip.

The devices are running an operating system designed specifically for MikroTik Switch products - SwOS.

SwOS is configurable from your web browser. It gives you all the basic functionality for a managed switch, plus more: Allows to manage port-to-port forwarding, apply MAC filter, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields.

Tested and recommended to use with MikroTik SFP modules: S-85DLC05D, S-31DLC20D and S-35/53LC20D (not included)

CPU	Taifatech TF470
Memory	Embedded 96K SRAM
Ethernet	Five 10/100/1000 Ethernet ports, Atheros switch AR8327
PoE output	RB260GSP only: Passive PoE output on ports 2-5. Max current 1A per port
SFP	One fixed Gigabit Ethernet SFP cage with DDMI support (Mini-GBIC; SFP module not included)
Serial port	No serial port
LEDs	Power, NAND activity, 5 Ethernet activity LEDs
Extras	Hardware watchdog
Power options	PoE: 8-30V DC on Ether1 (Non 802.3af). Jack: 8-30V DC
Dimensions	113x138x29mm. Without packaging and PSU: 212g
Power consumption	Up to 6W
Operating Temperature	-25C .. +65C
Operating System	MikroTik SwOS



Philips
LCD monitor

V Line

22 (21.5" / 54.6 cm diag.)
1920 x 1080 (Full HD)

221V8



Vivid, crisp images beyond boundaries

Philips V line wide-view monitor gives viewing beyond boundaries, great value with essential features. Adaptive-Sync provides flawless viewing without screen tearing. Features like LowBlue mode and flicker-free for easy-on-the eyes.

Vivid pictures every time

- VA display delivers awesome images with wide viewing angles
- 16:9 Full HD display for crisp detailed images
- SmartContrast for rich black details
- SmartImage presets for easy optimized image settings
- Effortlessly smooth action with Adaptive-Sync technology

Easy on the eyes

- Less eye fatigue with Flicker-free technology
- LowBlue Mode for easy on-the-eyes productivity
- EasyRead mode for a paper-like reading experience

Experience true multimedia

- HDMI-ready for Full HD entertainment

Perfectly designed for your space


- Compact design saves space
- VESA mount allows for flexibility

PHILIPS

LCD monitor
V Line 22 (21.5" / 54.6 cm diag.), 1920 x 1080 (Full HD)


Highlights

VA display



Philips VA LED display uses an advanced multi-domain vertical alignment technology which gives you super-high static contrast ratios for extra vivid and bright images. While standard office applications are handled with ease, it is especially suitable for photos, web-browsing, movies, gaming, and demanding graphical applications. Its optimized pixel management technology gives you 178/178 degree extra wide viewing angle, resulting in crisp images.

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 x 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colors expect a true to life picture.

SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying,


automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

SmartImage



SmartImage is an exclusive leading edge Philips technology that analyzes the content displayed on your screen and gives you optimized display performance. This user friendly interface allows you to select various modes like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, SmartImage dynamically optimizes the contrast, color saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time with the press of a single button!

Adaptive-Sync technology



Gaming shouldn't be a choice between choppy gameplay or broken frames. Get fluid, artifact-free performance at virtually any framerate with Adaptive-Sync technology, smooth quick refresh and ultra-fast response time.


221V8/00

Flicker-free technology




Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-free Technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

EasyRead mode



EasyRead mode for a paper-like reading experience



Specifications

Picture/Display

- LCD panel type: VA LCD
- Backlight type: W-LED system
- Panel Size: 21.5 inch / 54.6 cm
- Display Screen Coating: Anti-glare, 3H, Haze 25%
- Effective viewing area: 476.64 (H) x 268.11 (V)
- Aspect ratio: 16:9
- Maximum resolution: 1920 x 1080 @ 75 Hz*
- Pixel Density: 102 PPI
- Response time (typical): 4 ms (GtG)*
- Brightness: 250 cd/m²
- Contrast ratio (typical): 3000:1
- SmartContrast: Mega Infinity DCR
- Pixel pitch: 0.24825 x 0.24825 mm
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- Display colors: 16.7 M
- Picture enhancement: SmartImage
- Scanning Frequency: 30 - 85 kHz (H) / 48 - 75 Hz (V)
- sRGB
- Flicker-free
- LowBlue Mode
- EasyRead
- Adaptive sync

Connectivity

- Signal Input: VGA (Analog), HDMI (digital, HDCP)
- Sync Input: Separate Sync, Sync on Green
- Audio (In/Out): Audio out

Convenience

- User convenience: Power On/Off, Menu/OK, Brightness/UP, Input/Down, SmartImage/Back
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian
- Other convenience: Kensington lock, VESA mount (100x100mm)
- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7

Stand

- Tilt: -5/20 degree

Power

- Energy Label Class: E
- On mode: 13.3 W (typ.) (EnergyStar test method)
- Standby mode: < 0.5 W (typ.)
- Off mode: < 0.3 W (typ.)
- Power LED indicator: Operation - White, Standby mode- White (blinking)
- Power supply: Built-in, 100-240VAC, 50-60Hz

Dimensions

- Product with stand (mm): 493 x 376 x 220 mm
- Product without stand (mm): 493 x 294 x 45 mm
- Packaging in mm (WxHxD): 565 x 440 x 111 mm

Weight

- Product with stand (kg): 2.58 kg
- Product without stand (kg): 2.20 kg
- Product with packaging (kg): 3.71 kg

Operating conditions

- Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Non-operation: +40,000ft (12,192m)
- MTBF: 50,000 (Excluded backlight) hour(s)

Sustainability

- Environmental and energy: EnergyStar 8.0, RoHS, Mercury Free
- Recyclable packaging material: 100 %

Compliance and standards

- Regulatory Approvals: CE Mark, CB, TUV/GS, TUV Ergo, CU-EAC, EPA, PSB, MEPS, RCM

Cabinet

- Color: Black
- Finish: Textured

What's in the box?

- Monitor with stand
- Cables: HDMI cable, Power cable
- User Documentation



Issue date 2022-06-22

Version: 3.0.1

12 NC: 8670 001 60737
EAN: 87 12581 76017 5

© 2022 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com

* The maximum resolution works for HDMI input only.
* Response time value equal to SmartResponse
* The monitor may look different from feature images.

Кабельный тестер для разъемов RJ-45 и RG-58

NCT-1



Особенности

- Обеспечит быстрое и эффективное тестирование
- Предназначен для тестирования экранированной и неэкранированной витой пары и коаксиального кабеля

Спецификация

Supported cables:

EIA/TIA 568A/568B RJ45 twisted pair cable
BNC coaxial (10Base-T) cable
100Base-TX, 1000Base-TX twisted pair cables
Token Ring, AT&T 258A, Coaxial cable
Max cable length: 100 m
Battery: 9 V DC (not included)
Net weight: 0.16 kg

Упаковка

Кол-во в коробке, шт	100
Объем коробки, куб.м.	0.075922
Вес коробки, кг	19.21
Размеры индивидуальной упаковки ДхШхВ:	145x115x35 mm
Размеры картонной коробки ДхШхВ:	580x340x385 mm
Страна происхождения	CN
Баркод	8716309016919
Таможенный код	9030310090

Содержимое упаковки

Multi-functional Network Cable Tester
Remote terminator
User manual

Сертификаты





5/8-Port Gigabit Desktop Switch

Gigabit Wired Network
Expansion Solution

TL-SG1005D/TL-SG1008D



QoS



Plug and Play




Green Tech

Overview

The TL-SG1005D/TL-SG1008D Gigabit Desktop Switches provide you an easy way to upgrade your network to 1000 Mbps network. Since all ports supports auto MDI/MDIX, there's no need to worry about the cable type to use.

Moreover, with the innovative energy-efficient technology, TL-SG1005D/TL-SG1008D can save power consumption, making them an eco-friendly solution for your business network.

TL-SG1005D is used for demonstration here.



Features



Gigabit Expansion Solution

- TL-SG1005D equips 5 10/100/1000 Mbps ports, providing up to 10Gbps switching capacity
- TL-SG1008D equips 8 10/100/1000 Mbps ports, providing up to 16Gbps switching capacity
- IEEE 802.3x flow control provides reliable data transfer



Highlight Performance

- 802.1p and DSCP QoS enables smooth traffic
- Fanless design ensures quiet operation
- Green technology reduces power consumption



Easy to Use

- Just plug and play, no configuration required
- Auto MDI/MDIX eliminates the need for crossover cables
- Auto-negotiation intelligently adjusts for compatibility and optimal performance

Specifications

- Interface:

TL-SG1005D: 5 10/100/1000Mbps RJ45 Ports, Auto Negotiation, Auto MDI/MDIX

TL-SG1008D: 8 10/100/1000Mbps RJ45 Ports, Auto Negotiation, Auto MDI/MDIX
- Standards: IEEE 802.3, IEEE 802.3i, IEEE 802.3u, IEEE802.3ab, IEEE 802.3x, IEEE 802.1p
- Transmission Method : Store and Forward
- Advanced Functions: Green Technology, 802.3x Flow Control, 802.1p/DSCP QoS
- Max Power Consumption (220V/50Hz):

TL-SG1005D: 3.25W; TL-SG1008D: 4.06W
- Power Supply:

TL-SG1005D: External Power Adapter (Output: 5VDC / 0.6A)

TL-SG1008D: External Power Adapter (Output: 5VDC / 0.6A)
- Certification: FCC, CE, RoHs
- Environment:

Operating Temperature: 0°C~40°C (32°F ~104°F)

Storage Temperature: -40°C~60°C (-40°F ~140°F)

Operating Humidity: 10%~90%RH, non-condensing;

Storage Humidity: 5%~90%RH, non-condensing



For more information, please visit
<https://www.tp-link.com/en/products/details/TL-SG1005D.html> & <https://www.tp-link.com/en/products/details/TL-SG1008D.html>
or scan the QR code left and search for your product.


Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. © 2023 TP-Link

- Dimensions (W x D x H):


TL-SG1005D: 5.5 × 3.5 × 0.9 in. (140 × 88 × 23 mm)

TL-SG1008D: 7.1 × 3.5 × 1.0 in. (180 × 90 × 25.5 mm)

- TL-SG1005D:



- TL-SG1008D:




- Package Contents:

5/8-Port Gigabit Desktop Switch TL-SG1005D/TL-SG1008D

Power Adapter

Installation Guide

<https://www.tp-link.com>



WD Elements®

Портативный жесткий диск

Простой, быстрый и портативный.



Корпус более чем
на 50 % состоит из
переработанного пластика

Оцените надежность и внушительную емкость портативных жестких дисков WD Elements®. Быстрая передача данных и бесперебойное соединение с устройствами USB 3.2 Gen 1/USB 3.0 позволят легко создавать резервные копии фотографий, видео и других файлов в любых условиях.

ОСНОВНЫЕ ХАРАКТЕРИСТИКИ

- Автоматическое подключение
- Емкость до 6 ТБ* для хранения фотографий, видео, музыки, важных документов и многого другого
- SuperSpeed USB 3.2 Gen 1 (5 Гбит/с)

WD Elements®

Портативный жесткий диск



ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Варианты емкости*	6 ТБ, 5 ТБ, 4 ТБ, 2 ТБ, 1 ТБ
Габариты (Д x Ш x В)	6 ТБ, 5 ТБ, 4 ТБ: 110,5 x 82,0 x 23,7 мм 2 ТБ, 1 ТБ: 110,5 x 82,0 x 15,0 мм
Вес	6 ТБ, 5 ТБ, 4 ТБ: 0,23 кг 2 ТБ, 1 ТБ: 0,13 кг
Интерфейс	USB 3.2 Gen 1/USB 3.0 (совместим с USB 2.0)
Рабочая температура	от 5 °C до 35 °C
Температура хранения	от -20 °C до 65 °C
Совместимость	Windows® 10+ Для других операционных систем может потребоваться переформатирование На совместимость влияют аппаратная конфигурация компьютера и версия операционной системы
Гарантия ¹	2 года (во всем мире), 3 года (только Китай)
Содержимое упаковки	Портативный жесткий диск WD Elements® Кабель SuperSpeed USB-A (5 Гбит/с) Памятка по установке и настройке

МЕЖДУНАРОДНЫЕ НОМЕРА ПРОДУКТОВ

Емкость*	Цвет	Артикул	UPC	EAN-13
6 ТБ	Черный	WDBHJS0060BBK-WESN	7 18037 90431 3	07 18037 90431 3
5 ТБ	Черный	WDBU6Y0050BBK-WESN	7 18037 87189 9	07 18037 87189 9
4 ТБ	Черный	WDBU6Y0040BBK-WESN	7 18037 85598 1	07 18037 85598 1
2 ТБ	Черный	WDBU6Y0020BBK-WESN	7 18037 85536 3	07 18037 85536 3
1 ТБ	Черный	WDBUZG0010BBK-WESN	7 18037 85544 8	07 18037 85544 8

НОМЕРА ИЗДЕЛИЙ В ЯПОНИИ

Емкость*	Цвет	Артикул	UPC	EAN-13
6 ТБ	Черный	WDBHJS0060BBK-JESN	7 18037 90430 6	07 18037 90430 6
5 ТБ	Черный	WDBHJS0050BBK-JESN	7 18037 90426 9	07 18037 90426 9
4 ТБ	Черный	WDBHJS0040BBK-JESN	7 18037 90841 0	07 18037 90841 0
2 ТБ	Черный	WDBUZG0020BBK-JESE	7 18037 88203 1	07 18037 88203 1
1 ТБ	Черный	WDBUZG0010BBK-JESE	7 18037 88202 4	07 18037 88202 4

НОМЕРА ИЗДЕЛИЙ В КИТАЕ

Емкость*	Цвет	Артикул	UPC	EAN-13
6 ТБ	Черный	WDBHJS0060BBK-CESN	7 18037 90429 0	07 18037 90429 0
5 ТБ	Черный	WDBU6Y0050BBK-CESN	7 18037 87185 1	07 18037 87185 1
4 ТБ	Черный	WDBU6Y0040BBK-CESN	7 18037 85602 5	07 18037 85602 5
2 ТБ	Черный	WDBUZG0020BBK-CESN	7 18037 86122 7	07 18037 86122 7
1 ТБ	Черный	WDBUZG0010BBK-CESN	7 18037 82537 3	07 18037 82537 3

* 1 ТБ равен одному триллиону байт. Фактическая доступная емкость зависит от операционной среды и может быть меньше.

¹ Срок ограниченной гарантии зависит от того, в какой стране было приобретено изделие. С подробными условиями ограниченной гарантии WD и перечнем стран, входящих в упомянутые регионы, можно ознакомиться на странице <http://support.wdc.com/warranty/policy.asp>.

Western Digital, дизайн Western Digital, логотип Western Digital, WD, логотип WD и WD Elements — зарегистрированные знаки (или товарные знаки) корпорации Western Digital Corporation и аффилированных лиц в США и (или) других странах. Windows — зарегистрированный товарный знак Microsoft Corporation в США и/или других странах. macOS — товарный знак корпорации Apple Inc. Все прочие знаки являются собственностью соответствующих владельцев. Характеристики изделий могут быть изменены без уведомления. Приведенные изображения изделий могут не совпадать с их реальным внешним видом.

© Western Digital Corporation и аффилированные лица, 2025. Все права сохранены.



DATASHEET

SIGNATURE MK650 COMBO FOR BUSINESS

A versatile, comfortable combo with a full-size keyboard and mouse for improved productivity. The keyboard includes useful shortcut keys like mute mic, voice, and web tools. The Signature mouse provides dual-mode scrolling — line-by-line precision for documents and super fast scrolling for long web pages.

- **Designed for productivity:** Includes a full-size keyboard with pre-programmed function keys (F-keys) and a mouse with SilentTouch and SmartWheel technology.
- **Combo for comfort:** The integrated palm rest on the keyboard and contoured mouse mean more comfort for long days at the desk.
- **Enterprise-grade security:** Logi Bolt secure wireless technology provides a reliable connection even in congested wireless environments. Fully encrypted and FIPS compliant when paired with a Logi Bolt USB receiver.
- **Two ways to connect:** Choose between the Logi Bolt USB receiver when security is the priority, or *Bluetooth®* Low Energy wireless technology when cross-platform flexibility is needed.
- **Multi-OS layout:** Compatible with leading operating systems and platforms, so it's easy to deploy and manage in a multi-platform environment.
- **Support a more sustainable world:** Made with at least 21% post-consumer recycled plastic for the keyboard and 26% post-consumer recycled plastic for the mouse.¹

PRODUCT SPECIFICATIONS

Connectivity	2 ways to connect	Logi Bolt Receiver, <i>Bluetooth</i> ® (Version 5.0+)	Product dimensions & weight	Signature M650 for Business H x W x D 108.2 x 61 x 38.8 mm 4.26 x 2.4 x 1.52 in Weight: 101.4 g (4.46 oz) - with batteries (25 g) and receiver (1.8 g) Signature K650 for Business H x W x D 193.5 x 457.3 x 24 mm 7.62 x 18 x 0.94 in Weight: 700.23 g (24.7 oz) (with batteries) USB-A receiver H x W x D 18.4 x 23.1 x 6.6 mm 0.72 x 0.91 x 0.26 in Weight: 1.8 g (0.07 oz)
	Wireless range	Up to 10 m (33 ft) range ² (with open line of sight)		
	Easy-Switch	No		
Durability (Keypresses)	Service life	5 million keystrokes	General	Packaging dimension & weight
Battery	Battery type	Mouse: 1 AA battery, up to 1 year ³ KB: 2 AA batteries, up to 3 years ³		
	Mouse battery indicator	Yes		
Keyboard type	Size	Full-size		What's in the box
	Number of keys	118 (US layout)		
	Number pad	10-key		
	Typing	Plunger		Master Shipper Units
	Backlit keys	No		
	Illuminated caps lock	No		
	Illuminated num lock	No		Operating temperature
	Tilt legs	Yes		
	Tilt angles	+4°, +8°		Warranty
Certification & Compatibility	Certification	Certified for Works With Chromebook	Sustainability	Responsible packaging
	Compatibility	Logi Bolt USB Receiver • Windows 10, 11, or later⁴ • macOS 10.15 or later • ChromeOS • Linux <i>Bluetooth</i>® Low Energy Wireless (BLE) Technology • Windows 10, 11, or later⁴ • macOS 10.15 or later⁴ • iPadOS 14 or later⁵ • iOS 14 or later • ChromeOS⁵ • Linux⁵ • Android 8.0 or later⁵		Made with recycled plastic
Software	Logitech Options+	Enables custom key assignment	21% Recycled Plastic  21% post-consumer recycled material¹ FSC™ certified paper packaging	
	Logitech Sync	Enables remote monitoring		

PART NUMBERS

Part Number	Region	Country	Keyboard Layout	Color	Part Number	Region	Country	Keyboard Layout	Color
920-010909	SAMR	US	English U.S. (Qwerty)	Graphite	920-011018	SAMR	US	English U.S. (Qwerty)	Off-White
920-011403		Canada	FRC	Graphite	920-011404		Canada	FRC	Off-White
920-010991		Mexico (LAT)	Spanish – LAT (Qwerty)	Graphite	920-011019		Mexico (LAT)	Spanish – LAT (Qwerty)	Off-White
920-010992		Brazil	International English (U.S.)	Graphite	920-011020		Brazil	International English (U.S.)	Off-White
920-010994	EMEA	Germany, Austria	German (Qwerty)	Graphite	920-011022	EMEA	Germany, Austria	German (Qwerty)	Off-White
920-010995		France	French (Azerty)	Graphite	920-011023		France	French (Azerty)	Off-White
920-010993		Switzerland	Swiss (Qwerty)	Graphite	920-011021		Switzerland	Swiss (Qwerty)	Off-White
920-010996		Italy	Italian (Qwerty)	Graphite	920-011024		Italy	Italian (Qwerty)	Off-White
920-010998		Spain, Portugal	Spanish – EUR (Qwerty)	Graphite	920-011026		Spain, Portugal	Spanish – EUR (Qwerty)	Off-White
920-011010		Denmark, Finland, Iceland, Norway, Sweden	Pan Nordic (Qwerty)	Graphite	920-011038		Denmark, Finland, Iceland, Norway, Sweden	Pan Nordic (Qwerty)	Off-White
920-010999		UK, Ireland	English UK (Qwerty)	Graphite	920-011027		UK, Ireland	English UK (Qwerty)	Off-White
920-011004		EMEA Region	International English (U.S.)	Graphite	920-011032		EMEA Region	International English (U.S.)	Off-White
920-011001		Belgium	NLB	Graphite	920-011029		Belgium	NLB	Off-White
920-011003		United Arab Emirates	Arabic (Qwerty)	Graphite	920-011031		United Arab Emirates	Arabic (Qwerty)	Off-White
920-011006		Czech	CZE-SKY	Graphite	920-011034		Czech	CZE-SKY	Off-White
920-011008		Hungary	HUN	Graphite	920-011036		Hungary	HUN	Off-White
920-011009		Ukraine	Russian (Qwerty)	Graphite	920-011037		Ukraine	Russian (Qwerty)	Off-White
920-011000		Turkey	Turkey (Qwerty)	Graphite	920-011028		Turkey	Turkey (Qwerty)	Off-White
920-011014		AP region, India, Hong Kong	English U.S. (Qwerty)	Graphite	920-011042	APJ	AP region, India, Hong Kong	English U.S. (Qwerty)	Off-White
920-011012		Taiwan	Chinese - Traditional	Graphite	920-011040		Taiwan	Chinese - Traditional	Off-White
920-011011		Korea	Korean	Graphite	920-011039		Korea	Korean	Off-White
920-011013		China	English U.S. (Qwerty)	Graphite	920-011041		China	English U.S. (Qwerty)	Off-White
920-011015		Thailand	THAI	Graphite	920-011043		Thailand	THAI	Off-White
920-012342		Japan	Japanese	Graphite	920-011045		Japan	Japanese	Off-White

logitech®

www.logitech.com/mk650-signature-combo-for-business

Contact your reseller or contact us at
www.logitech.com/business

Logitech Americas
3930 North First Street,
San Jose, CA 95134 USA

Logitech Europe S.A.
EPFL - Quartier de l'Innovation
Daniel Borel Innovation Center
CH - 1015 Lausanne

Logitech Asia Pacific Ltd.
Tel : 852-2821-5900
Fax : 852-2520-2230

¹ Excludes plastic in printed wiring assembly (PWA) and packaging.
² Wireless range may vary based on users and computing conditions.
³ Battery life may vary based on users and computing conditions.
⁴ Customize device by installing the Logi Options+ app, available on *Windows* and *macOS* at logitech.com/optionsplus
⁵ Logi Options+ App is currently not supported. The device's basic functions will work without it.