

Model	S-M-160kva
Rated Capacity (KVA)	160kva
H.V	10kv
L.V	0.4kv
H.V Current (A)	9.24
L.V Current (A)	230.94
Impedance	4.5%
No Load Loss (W)	300
On Load Loss (W)	2136
Winding Material	Aluminum to Aluminum
Frequency	50HZ
Vector Group	Yyn0
Phase	3 phase
Type	Oil immersed type
Oil	Mineral Oil
Core	Silicon steel sheet
Tapping Changer	OCTC, 5 steps; $\pm 2 \times 2.5\%$
Ambient Temperature	-25° C to +50° C
Cooling Type	ONAN
Insulation Class	A
Transformer Color	Ral7032
Max Altitude	1000m
Oil Level Indicator	Equipped
Pressure Relief Device	Equipped
Lifting lugs	Equipped
Nameplate	Equipped

Model	S-M-250kva
Rated Capacity (KVA)	250kva
H.V	10kv
L.V	0.4kv
H.V Current (A)	14.43
L.V Current (A)	360.84
Impedance	4.5%
No Load Loss (W)	425
On Load Loss (W)	2955
Winding Material	Aluminum to Aluminum
Frequency	50HZ
Vector Group	Yyn0
Phase	3 phase
Type	Oil immersed type
Oil	Mineral Oil
Core	Silicon steel sheet
Tapping Changer	OCTC, 5 steps; $\pm 2 \times 2.5\%$
Ambient Temperature	-25° C to +50° C
Cooling Type	ONAN
Insulation Class	A
Transformer Color	Ral7032
Max Altitude	1000m
Oil Level Indicator	Equipped
Pressure Relief Device	Equipped
Lifting lugs	Equipped
Nameplate	Equipped

Model	S-M-400kva
Rated Capacity (KVA)	400kva
H.V	10kv
L.V	0.4kv
H.V Current (A)	23.09
L.V Current (A)	577.35
Impedance	4.5%
No Load Loss (W)	780
On Load Loss (W)	5900
Winding Material	Aluminum to Aluminum
Frequency	50HZ
Vector Group	Yyn0
Phase	3 phase
Type	Oil immersed type
Oil	Mineral Oil
Core	Silicon steel sheet
Tapping Changer	OCTC, 5 steps; $\pm 2 \times 2.5\%$
Ambient Temperature	-25° C to +50° C
Cooling Type	ONAN
Insulation Class	A
Transformer Color	Ral7032
Max Altitude	1000m
Oil Level Indicator	Equipped
Pressure Relief Device	Equipped
Lifting lugs	Equipped
Nameplate	Equipped

Model	S-M-630kva
Rated Capacity (KVA)	630kva
H.V	10kv
L.V	0.4kv
H.V Current (A)	36.37
L.V Current (A)	909.33
Impedance	5.5%
No Load Loss (W)	1070
On Load Loss (W)	8500
Winding Material	Aluminum to Aluminum
Frequency	50HZ
Vector Group	Yyn0
Phase	3 phase
Type	Oil immersed type
Oil	Mineral Oil
Core	Silicon steel sheet
Tapping Changer	OCTC, 5 steps; $\pm 2 \times 2.5\%$
Ambient Temperature	-25° C to +50° C
Cooling Type	ONAN
Insulation Class	A
Transformer Color	Ral7032
Max Altitude	1000m
Oil Level Indicator	Equipped
Pressure Relief Device	Equipped
Lifting lugs	Equipped
Nameplate	Equipped