

### Specificații tehnice

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție: ocds-b3wdp1-MD-1705502538213 din 17.01.2024

Obiectul achiziției: Echipament tehnic pentru producția TV și Radio

Denumirea bunurilor/serviciilor	Denumirea modelului bunului/serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Microfon	AVX-835	Romania	Sennheiser	System Wireless Technology Digital 1.9 GHz Included Transmitters 1 x Handheld Diversity Antenna Diversity RF Frequency Band 1920 to 1930 MHz RF Bandwidth 10 MHz RF Channel Scanning Auto-Scan Max Operating Range 29.9 m (Line of Sight) Max Transmitters per Band 8 Sample Rate/Resolution 48 kHz / 24-Bit Latency 19 ms Dynamic Range >120 dBA Encryption AES 256 Modulation GFSK (with Back Channel) Receiver Receiver Type Camera-Mount Mounting Options- Plug-In, Shoe-Mount(with Included Hardware) Antenna 1 x External, Fixed (Top-Mount) Number of Audio Channels 1 Audio I/O 1 x XLR 3-Pin Male Balanced Mic Output Audio Output Level - XLR Output:-30 to 0 dB (Balanced) Frequency Response 20 Hz to 20 kHz USB/Lightning Connectivity 1 x Micro-USB Female (Bus Power, Charging) Power Requirements Battery, Bus Power (USB) Battery Type 1 x Battery Pack (Included)	System Wireless Technology Digital 1.9 GHz Included Transmitters 1 x Handheld Diversity Antenna Diversity RF Frequency Band 1920 to 1930 MHz RF Bandwidth 10 MHz RF Channel Scanning Auto-Scan Max Operating Range 29.9 m (Line of Sight) Max Transmitters per Band 8 Sample Rate/Resolution 48 kHz / 24-Bit Latency 19 ms Dynamic Range >120 dBA Encryption AES 256 Modulation GFSK (with Back Channel) Receiver Receiver Type Camera-Mount Mounting Options- Plug-In, Shoe-Mount(with Included Hardware) Antenna 1 x External, Fixed (Top-Mount) Number of Audio Channels 1 Audio I/O 1 x XLR 3-Pin Male Balanced Mic Output Audio Output Level - XLR Output:-30 to 0 dB (Balanced) Frequency Response 20 Hz to 20 kHz USB/Lightning Connectivity 1 x Micro-USB Female (Bus Power, Charging) Power Requirements Battery, Bus Power (USB) Battery Type 1 x Battery Pack (Included)	

				<p>Approx. Battery Life - 4 Hours (Lithium Rechargeable)</p> <p>Display &amp; Indicators - 1 x LED (Battery Status, Level)</p> <p>Housing Metal</p> <p>Transmitter</p> <p>Transmitter Type Handheld</p> <p>RF Output Power Up to 250 mW</p> <p>Muting Mute Switch</p> <p>Frequency Response 50 Hz to 20 kHz (Mic)</p> <p>Antenna 1 x External, Fixed (Handheld)</p> <p>Power Requirements- Battery, Bus Power (USB)</p> <p>Battery Type 1 x Battery Pack (Included)</p> <p>Approx. Battery Life - 15 Hours (Lithium Rechargeable)</p> <p>USB/Lightning I/O 1 x Micro-USB (Bus Power, Charging)</p> <p>Display &amp; Indicators 1 x LCD (Battery Status, Signal Strength)</p> <p>Housing Metal</p> <p>Microphone</p> <p>Microphone Type Handheld Capsule</p> <p>Color Black</p> <p>Sound Field Mono</p> <p>Capsule Dynamic</p> <p>Polar Pattern Cardioid</p> <p>Maximum SPL 154 dB SPL Peak</p> <p>Sensitivity 2.1 mV/Pa</p> <p>Garanție 24 luni</p>	<p>Approx. Battery Life - 4 Hours (Lithium Rechargeable)</p> <p>Display &amp; Indicators - 1 x LED (Battery Status, Level)</p> <p>Housing Metal</p> <p>Transmitter</p> <p>Transmitter Type Handheld</p> <p>RF Output Power Up to 250 mW</p> <p>Muting Mute Switch</p> <p>Frequency Response 50 Hz to 20 kHz (Mic)</p> <p>Antenna 1 x External, Fixed (Handheld)</p> <p>Power Requirements- Battery, Bus Power (USB)</p> <p>Battery Type 1 x Battery Pack (Included)</p> <p>Approx. Battery Life - 15 Hours (Lithium Rechargeable)</p> <p>USB/Lightning I/O 1 x Micro-USB (Bus Power, Charging)</p> <p>Display &amp; Indicators 1 x LCD (Battery Status, Signal Strength)</p> <p>Housing Metal</p> <p>Microphone</p> <p>Microphone Type Handheld Capsule</p> <p>Color Black</p> <p>Sound Field Mono</p> <p>Capsule Dynamic</p> <p>Polar Pattern Cardioid</p> <p>Maximum SPL 154 dB SPL Peak</p> <p>Sensitivity 2.1 mV/Pa</p> <p>Garanție 24 luni</p>
Microfon	ECM-W3	China	Sony	<p>Microphone Channel Audio Output 2ch</p> <p>Shoe type Multi Interface Shoe</p> <p>Power Supply from Main Unit Multi Interface Shoe</p> <p>Battery Type Built-in lithium-ion battery</p> <p>Number of Battery Required 1</p> <p>Monaural / Stereo Monaural</p> <p>Directivity omni-directional</p> <p>Frequency Response 20 Hz to 20 000 Hz</p> <p>Front sensitivity</p> <p>-20 dBFS (0.1 Pa, 1 kHz)* * Acquired while "10dB" is selected by the ATT switch.</p> <p>Intrinsic noise</p> <p>16 dB SPL or less (0 dB = <math>2 \times 10^{-5}</math> Pa)* * Acquired while "10dB" is selected by the ATT switch. *</p> <p>Acquired while "DIGITAL" is selected by the slide switch.</p> <p>Maximum Input Sound Pressure Level</p> <p>120 dB SPL* * Acquired while "10dB" is selected by the ATT switch. *</p> <p>Equivalent sound pressure level value converted from the input level value that is acquired when 1% waveform distortion is produced by 1 kHz output signals from the microphone. (0 dB = <math>2 \times 10^{-5}</math> Pa)</p> <p>Microphone out jack (3.5 mm mini jack (stereo))</p>	<p>Microphone Channel Audio Output 2ch</p> <p>Shoe type Multi Interface Shoe</p> <p>Power Supply from Main Unit Multi Interface Shoe</p> <p>Battery Type Built-in lithium-ion battery</p> <p>Number of Battery Required 1</p> <p>Monaural / Stereo Monaural</p> <p>Directivity omni-directional</p> <p>Frequency Response 20 Hz to 20 000 Hz</p> <p>Front sensitivity</p> <p>-20 dBFS (0.1 Pa, 1 kHz)* * Acquired while "10dB" is selected by the ATT switch.</p> <p>Intrinsic noise</p> <p>16 dB SPL or less (0 dB = <math>2 \times 10^{-5}</math> Pa)* * Acquired while "10dB" is selected by the ATT switch. *</p> <p>Acquired while "DIGITAL" is selected by the slide switch.</p> <p>Maximum Input Sound Pressure Level</p> <p>120 dB SPL* * Acquired while "10dB" is selected by the ATT switch. *</p> <p>Equivalent sound pressure level value converted from the input level value that is acquired when 1% waveform distortion is produced by 1 kHz output signals from the microphone. (0 dB = <math>2 \times 10^{-5}</math> Pa)</p> <p>Microphone out jack (3.5 mm mini jack (stereo))</p>

				External microphone input jack(3.5 mm mini jack (monaural)) USB Type-C® Terminal Garanție 24 luni	External microphone input jack(3.5 mm mini jack (monaural)) USB Type-C® Terminal Garanție 24 luni	
<b>Microfon</b>	SM58-LC	China	Shure	Form Factor Stand/Boom Mount Intended Sound Sources Vocals, Speech/Voice-Over Sound Field Mono Operating PrinciplePressure Operated Element Type Dynamic Polar Pattern Cardioid Performance Frequency Range 50 Hz to 20 kHz Sensitivity -59 dBV/Pa at 1 kHz Physical Color Gray Mounting Thread Size 5/8"-27 Female Garanție 24 luni	Form Factor Stand/Boom Mount Intended Sound Sources Vocals, Speech/Voice-Over Sound Field Mono Operating PrinciplePressure Operated Element Type Dynamic Polar Pattern Cardioid Performance Frequency Range 50 Hz to 20 kHz Sensitivity -59 dBV/Pa at 1 kHz Physical Color Gray Mounting Thread Size 5/8"-27 Female Garanție 24 luni	
<b>Set de Lavaliera Wireless</b>	ew112p G4 A	Romania	Sennheiser	System Wireless Technology Analog UHF Number of RF Channel Frequencies 1680 Included Transmitters 1 x Bodypack with Microphone Diversity Antenna Diversity RF Frequency Band A: 516 to 558 MHz RF Bandwidth 42 MHz Frequency Step Size 25 kHz Max Operating Range 100.6 m (Line of Sight) Max Transmitters per Band 12 Deviation 48 kHz (Peak) Modulation Wideband FM Receiver Receiver Type Camera-Mount Mounting Options Shoe-Mount (with Included Hardware) Antenna 1 x Flexible Whip, Fixed Number of Audio Channels 1 Audio I/O 1 x 3.5 mm TRS Female Unbalanced Output (Lockable) Gain Range 42 dB (6 dB Steps) Audio Output Level +12 dBu Squelch 5 to 25 dBµV Adjacent Channel Isolation >65 dB Power Requirements Battery Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Battery Status, Output Level, RF Level) Housing Metal Transmitter Transmitter Type Bodypack RF Output Power 30 mW Audio I/O 1 x 3.5 mm TRS Female Unbalanced Input (Lockable) Muting Mute Switch Audio Input Level 3 V RMS (Max)	System Wireless Technology Analog UHF Number of RF Channel Frequencies 1680 Included Transmitters 1 x Bodypack with Microphone Diversity Antenna Diversity RF Frequency Band A: 516 to 558 MHz RF Bandwidth 42 MHz Frequency Step Size 25 kHz Max Operating Range 100.6 m (Line of Sight) Max Transmitters per Band 12 Deviation 48 kHz (Peak) Modulation Wideband FM Receiver Receiver Type Camera-Mount Mounting Options Shoe-Mount (with Included Hardware) Antenna 1 x Flexible Whip, Fixed Number of Audio Channels 1 Audio I/O 1 x 3.5 mm TRS Female Unbalanced Output (Lockable) Gain Range 42 dB (6 dB Steps) Audio Output Level +12 dBu Squelch 5 to 25 dBµV Adjacent Channel Isolation >65 dB Power Requirements Battery Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Battery Status, Output Level, RF Level) Housing Metal Transmitter Transmitter Type Bodypack RF Output Power 30 mW Audio I/O 1 x 3.5 mm TRS Female Unbalanced Input (Lockable) Muting Mute Switch Audio Input Level 3 V RMS (Max)	-

				Gain Range 60 dB (3 dB Steps) Frequency Response 80 Hz to 18 kHz (Mic) 25 Hz to 18 kHz (Line) Sync Method IR Antenna 1 x Flexible Whip, Fixed (Beltpack) Power Requirements Battery Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Audio Level, Battery Status, Signal Strength) Housing Metal Microphone Microphone Type Lavalier Sound Field Mono Capsule Electret Condenser Polar Pattern Omnidirectional Frequency Range 50 Hz to 18 kHz Equivalent Noise Level 36 dB Maximum SPL 130 dB SPL Peak Sensitivity 20 mV/Pa Output Connectors 1 x 3.5 mm TRS Male Unbalanced (Lockable) Cable Length 1.6 m Garanție 24 luni	Gain Range 60 dB (3 dB Steps) Frequency Response 80 Hz to 18 kHz (Mic) 25 Hz to 18 kHz (Line) Sync Method IR Antenna 1 x Flexible Whip, Fixed (Beltpack) Power Requirements Battery Battery Type 2 x AA (Included) Approx. Battery Life 8 Hours (Alkaline) Display & Indicators 1 x Backlit LCD (Audio Level, Battery Status, Signal Strength) Housing Metal Microphone Microphone Type Lavalier Sound Field Mono Capsule Electret Condenser Polar Pattern Omnidirectional Frequency Range 50 Hz to 18 kHz Equivalent Noise Level 36 dB Maximum SPL 130 dB SPL Peak Sensitivity 20 mV/Pa Output Connectors 1 x 3.5 mm TRS Male Unbalanced (Lockable) Cable Length 1.6 m Garanție 24 luni	
--	--	--	--	---	---	--

Semnăt: Semnăt electronic, Numele, Prenumele: Carabut Vladislav, În calitate de: Director

Ofertantul: SC “Muzic-Prod” S.R.L.

Adresa: Moldova, Chisinau, Durlesti, str-la II Vovinteni 15