

Specificații tehnice

Numărul procedurii de achiziție: [ocds-b3wdp1-MD-1739369651562](#) din 12.02.2025

Obiectul achiziției: Lumini, becuri și piese de rezervă pentru Balizajul luminos RWY 08-26

Denumirea bunurilor/ serviciilor	Denumirea modelului bunului/ serviciului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Becuri						
Bec cu halogen RCL, TDZ, SIGNS	48W 6,6A,DICHT ROIC female	Germania	Vosla GmbH	48W 6,6A,DICHTROIC female	48W 6,6A,DICHTROIC female	- ICAO Ann.14, Vol.1,Vol.2; -FAA AC 150/5345- 46E - EASA CS-ADR-DSN
Bec cu halogen REH INSET	105W 6,6A DICHTROI C female	Germania	Vosla GmbH	105W 6,6A DICHTROIC female	105W 6,6A DICHTROIC female	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
Bec cu halogen APS, PAPI	HLX-C 200W-15 6,6A PK 30d	Germania	Vosla GmbH	HLX-C 200W-15 6,6A PK 30d male	HLX-C 200W-15 6,6A PK 30d male	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
Bec cu halogen RGL	HLX 100W- 15 6,6A PK 30d	Germania	Vosla GmbH	HLX 100W-15 6,6A PK 30d female	HLX 100W-15 6,6A PK 30d female	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
Bec cu halogen APL	EWR 150W 6,6A GY9,5	Germania	Vosla GmbH	EWR 150W 6,6A GY9,5	EWR 150W 6,6A GY9,5	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN

Lumini

Inset Lights (W/R) RCL	RCL-S-I-31- W00R00-2- 1O-1100	Olanda	TKH Airport Solution	Runway Centerline Straight Photometrics: ICAO CAT III 8 Inch inset Side A: White, no toe-in Side B: Red, no toe-in Sapphire prism Cable: 250 mm, one plug Plug: standard FAA 2-pole plug With fail-open (relay) No heater No special options 011.633-717	Runway Centerline Straight Photometrics: ICAO CAT III 8 Inch inset Side A: White, no toe-in Side B: Red, no toe-in Sapphire prism Cable: 250 mm, one plug Plug: standard FAA 2-pole plug With fail-open (relay) No heater No special options 011.633-717	- ICAO Ann.14, Vol.1,Vol.2- FAA AC 150/5345-46E - EASA CS-ADR- DSN
Inset Lights (G/G) TCL	TCL-S-I-31- G00G00-2- 1O-1100	Olanda	TKH Airport Solution	Taxiway Centerline Straight Photometrics: ICAO CAT III 8 Inch inset Side A: Green, no toe-in Side B: Green, no toe-in Sapphire prism Cable: 250 mm, one plug Plug: standard FAA 2-pole plug With fail-open (relay) No heater No special options 011.635-537	Taxiway Centerline Straight Photometrics: ICAO CAT III 8 Inch inset Side A: Green, no toe-in Side B: Green, no toe-in Sapphire prism Cable: 250 mm, one plug Plug: standard FAA 2-pole plug With fail-open (relay) No heater No special options 011.635-537	- ICAO Ann.14, Vol.1,Vol.2- FAA AC 150/5345-46E - EASA CS-ADR-DSN
Inset Lights (G/0) RTP	TCL-S-I-31- G00000-2- 1O-1100	Olanda	TKH Airport Solution	Taxiway Centerline Straight Photometrics: ICAO CAT III 8 Inch inset Side A: Green, no toe-in Side B: Blank Sapphire prism Cable: 250 mm, one plug Plug: standard FAA 2-pole plug With fail-open (relay) No heater No special options 011.637-077	Taxiway Centerline Straight Photometrics: ICAO CAT III 8 Inch inset Side A: Green, no toe-in Side B: Blank Sapphire prism Cable: 250 mm, one plug Plug: standard FAA 2-pole plug With fail-open (relay) No heater No special options 011.637-077	- ICAO Ann.14, Vol.1,Vol.2- FAA AC 150/5345-46E - EASA CS-ADR- DSN
LED HIRE Elevated REH	REH-S-I-34- W40Y40-3- 5O-1000- HIRE-LED- A	Olanda	TKH Airport Solution	Runway Edge Straight Photometrics: ICAO CAT III Elevated Side A: White, 4,0° toe-in Side B: Yellow, 4,0° toe-in Glass for elevated lights Cable: 110 mm, one plug Plug: standard FAA 2-pole plug No fail-open No heater No special options HIRE-Family LED Coupling Type A 012.765-002	Runway Edge Straight Photometrics: ICAO CAT III Elevated Side A: White, 4,0° toe-in Side B: Yellow, 4,0° toe-in Glass for elevated lights Cable: 110 mm, one plug Plug: standard FAA 2-pole plug No fail- open No heater No special options HIRE-Family LED Coupling Type A 012.765-002	- ICAO Ann.14, Vol.1,Vol.2- FAA AC 150/5345-46E - EASA CS-ADR- DSN

LED HIRE Elevated REH	REH-S-I-34-Y40W40-3-50-1000-HIRE-LED-A	Olanda	TKH Airport Solution	Runway Edge Straight Photometrics: ICAO CAT III Elevated Side A: Yellow, 4,0° toe-in Side B: White, 4,0° toe-in Glass for elevated lights Cable: 110 mm, one plug Plug: standard FAA 2-pole plug No fail-open No heater No special options HIRE-Family LED Coupling Type A 012.765-003	Runway Edge Straight Photometrics: ICAO CAT III Elevated Side A: Yellow, 4,0° toe-in Side B: White, 4,0° toe-in Glass for elevated lights Cable: 110 mm, one plug Plug: standard FAA 2-pole plug No fail-open No heater No special options HIRE-Family LED Coupling Type A 012.765-003	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
792 LED Green Elevated THR	THR-S-I-34-G00000-3-40-1100-792-LED-A	Olanda	TKH Airport Solution	Threshold Straight Photometrics: ICAO CAT III Elevated Side A: Green, no toe-in Side B: Blank Glass for elevated lights Cable: 400mm, one plug Plug: standard FAA 2-pole plug With fail-open (relay) No heater No special options 792 LED Coupling Type A NOTE: Old model, elevated light 792 has been superseded by elevated light 797 792.LED.3.FO.A	Threshold Straight Photometrics: ICAO CAT III Elevated Side A: Green, no toe-in Side B: Blank Glass for elevated lights Cable: 400mm, one plug Plug: standard FAA 2-pole plug With fail-open (relay) No heater No special options 792 LED Coupling Type A NOTE: Old model, elevated light 792 has been superseded by elevated light 797 792.LED.3.FO.A	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
Piese de schimb						
RCL, TCL, TCC	EHG-20W-20W-1x250mm-P1-8-FO	Olanda	TKH Airport Solution	Electronic Housing Group 20 W / 20 W 1 cable 250 mm standard FAA plug 8 inch With fail-open (relay)	Electronic Housing Group 20 W / 20 W 1 cable 250 mm standard FAA plug 8 inch With fail-open 190.774-587	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
REH Elevated	EHG-40W-1-0-0x0-0-HIRE-H0-0	Olanda	TKH Airport Solution	Electronic Housing Group 40 W No cable Heatsink HIRE	Electronic Housing Group 40 W No cable Heatsink HIRE No fail-open 204.114-007	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
REH Inset	EHG-40W-40W-1x250mm-P1-12-FO	Olanda	TKH Airport Solution	Electronic Housing Group 40 W / 40 W 1 cable 250 mm standard FAA Plug 12 inch With fail-open (relay)	Electronic Housing Group 40 W / 40 W 1 cable 250 mm standard FAA Plug 12 inch With fail-open 205.954-507	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN

TCL (G)	MHG-TCL-8-1xG-CAT3-00-FO-0	Olanda	TKH Airport Solution	LED module Taxiway Centerline 8 inch Green CAT III No heating No special options With fail-open 6.6 A	LED module Taxiway Centerline 8 inch Green CAT III No heating No special options With fail-open 6.6 A 213.641-857	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
TCL (Y) Stright	MHG-TCL-8-1xY-CAT3-00-FO-0	Olanda	TKH Airport Solution	LED module Taxiway Centerline / Intermediate Holding Position 8 inch Yellow CAT III No heating No special options With fail-open 6.6 A	LED module Taxiway Centerline / Intermediate Holding Position 8 inch Yellow CAT III No heating No special options With fail-open 6.6 A 213.641-867	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
TCL (Y) Curved	MHG-TCC-8-1xY-CAT3-00-FO-0	Olanda	TKH Airport Solution	LED module Taxiway Centerline Curved 8 inch Yellow CAT III No heating No special options With fail-open 6.6 A	LED module Taxiway Centerline Curved 8 inch Yellow CAT III No heating No special options With fail-open 6.6 A 213.641-007	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
RCL ®	MHG-RCL-8-1xR-CAT3-00-FO-0	Olanda	TKH Airport Solution	LED module Runway Centerline / Touch Down Zone 8 inch Red CAT III No heating No special options With fail-open 6.6 A	LED module Runway Centerline / Touch Down Zone 8 inch Red CAT III No heating No special options With fail-open 6.6 A 213.641-307	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
REH Elevated	MHG-HIRE-A-1xY-CAT3-00-0	Olanda	TKH Airport Solution	LED module HIRE side A Yellow CAT III No fail-open No special options	LED module HIRE side A Yellow CAT III No heating No special options No fail-open 6.6 A 204.125-027	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
REH Elevated	MHG-HIRE-B-1xY-CAT3-00-0	Olanda	TKH Airport Solution	LED module HIRE side B Yellow CAT III No fail-open No special options	LED module HIRE side B Yellow CAT III No heating No special options No fail-open 6.6 A 204.125-037	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
REH Inset	MHG-REH-12-1xW-CAT3-00-FO-0	Olanda	TKH Airport Solution	LED module Runway Edge 12 inch White CAT III No heating No special options With fail-open 6.6 A	LED module Runway Edge 12 inch White CAT III No heating No special options With fail-open 6.6 A 205.916-497	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
REH Inset	MHG-REH-12-1xY-CAT3-00-FO-0	Olanda	TKH Airport Solution	LED module Runway Edge 12 inch Yellow CAT III No heating No special options With fail-open 6.6 A	LED module Runway Edge 12 inch Yellow CAT III No heating No special options With fail-open 6.6 A 205.917-047	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN

PAPI	952210/60-120	Olanda	TKH Airport Solution	PAPI 801 cod 952210/60-120 Breakable coupling	Breakable coupling for PAPI 120 kgm (spare part) 952210/60-120	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
PAPI	801202	Olanda	TKH Airport Solution	PAPI 801 cod 801202 Ball bearing	Relief plate for ball joint for PAPI 801 801202	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
792 Family	O-ring 792	Olanda	TKH Airport Solution	O-ring gasket 8 inch for elevated lights 792-Family	O-ring gasket 8 inch for elevated lights 792-Family 792014/2	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
RGL	LED-RGL921-follow-driver	Olanda	TKH Airport Solution	Cod 792886206 Spare light unit for 921 LED RGL follow without fail-open with driver	Spare light unit for 921 LED RGL follow without fail-open with driver 792886.206	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN
RGL	LED-RGL921-on/off-driver	Olanda	TKH Airport Solution	Cod 792887206 Spare light unit for 921 LED RGL on/off without fail-open with driver	Spare light unit for 921 LED RGL on/off without fail-open with driver 792887.206	- ICAO Ann.14, Vol.1,Vol.2-FAA AC 150/5345-46E - EASA CS-ADR-DSN

Garantia – 12 luni din data livrării.

Termen de livrare: 3 luni din data semnării Contractului.

Ofertantul: Solis Energo SRL

Adresa: R.Moldova, mun.Chisinau, bd.Dacia 49/14-12

Semnat Victor Ianioglo În calitate de director _____