



Sisteme Informationale Integrate
Интегрированные Системные Решения
Integrated System Solutions

Numărul cererii a ofertelor de prețuri: ocbs-b3wdp1-MD-1623914420571	Data: 28/06/2021	Alternativa nr.: -
Denumirea licitației: Echipament de telecomunicații	Lot: 1	

SPECIFICAȚII TEHNICE (F4.1)

nr. d/o	Cod CPV	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
	1	2	3	4	5	6	7	8
1.1	32500000-8	Convertoare optice tip I	Video multiplexer transmitter, 1 forward video channels // Video multiplexer receiver, 1 forward video channels (set)	China	Shenzhen Optostar Co., LTD	Video- 1 channel Video connector - BNC Input/output impedance :75 Ω (unbalanced) Bandwidth:8MHz Differential Gain: 1% Differential Phase 10 Video sampling PAL/NTSC/SECAM fully compatible Interface rate 10/100Mbps(AUTO) Interface type RJ-45 Work mode:full duplex or half duplex Optical Interface FC Wavelength single-mode (Bi - direction) 1490/1310-1550nm Transmission distance >10 KM (SM) Power input AC100~240V, DC12V	Video- 1 channel Video connector - BNC Input/output impedance :75 Ω (unbalanced) Bandwidth:8MHz Differential Gain: 1% Differential Phase 10 Video sampling PAL/NTSC/SECAM fully compatible Interface rate 10/100Mbps(AUTO) Interface type RJ-45 Work mode:full duplex or half duplex Optical Interface FC Wavelength single-mode (Bi - direction) 1490/1310-1550nm Transmission distance >10 KM (SM) Power input AC100~240V, DC12V	-

Republica Moldova, mun. Chisinau, MD-2002, str. Cetatea Alba 43
C/F: 1002600027262
TVA:0305086
IBAN: MD91PR002251109768001498 la BC ProCreditBank SA
BIC: PRCBMD22
tel.: 0-22-57-31-31; fax: 0-22-57-30-00



Sisteme Informatiionale Integrate
 Итегрированные Системные Решения
 Integrated System Solutions

1.2	325000 00-8	Convertoare optice tip II	Video multiplexer transmitter, 4 forward video channels (witch RS485, reverse direction) // Video multiplexer receiver, 4 forward video channels (witch RS485, reverse direction) (set)	China	Shenzhen Optostar Co., LTD	<p>Video- 4 channel Video connector - BNC Input/output impedance :75 Ω (unbalanced) Bandwidth:8MHz Differential Gain: 1% Differential Phase 10 Video sampling PAL/NTSC/SECAM fully compatible Data RS485, reverse direction Connector Terminals block (2 wires) Control equipment PTZ decoder, control keyboard, matrix control data interface, high speed dome, industrial equipment Interface rate 10/100Mbps(AUTO) Interface type RJ-45 Work mode:full duplex or half duplex Optical Interface FC Wavelength single-mode (Bi - direction) 1490/1310-1550nm Transmission distance >10 KM (SM) Power input AC100~240V, DC12V</p>	<p>Video- 4 channel Video connector - BNC Input/output impedance :75 Ω (unbalanced) Bandwidth:8MHz Differential Gain: 1% Differential Phase 10 Video sampling PAL/NTSC/SECAM fully compatible Data RS485, reverse direction Connector Terminals block (2 wires) Control equipment PTZ decoder, control keyboard, matrix control data interface, high speed dome, industrial equipment Interface rate 10/100Mbps(AUTO) Interface type RJ-45 Work mode:full duplex or half duplex Optical Interface FC Wavelength single-mode (Bi - direction) 1490/1310-1550nm Transmission distance >10 KM (SM) Power input AC100~240V, DC12V</p>	
-----	----------------	---------------------------	---	-------	----------------------------	---	--	--

Republica Moldova, mun. Chisinau, MD-2002, str. Cetatea Alba 43
 C/F: 1002600027262
 TVA:0305086
 IBAN: MD91PR002251109768001498 la BC ProCreditBank SA
 BIC: PRCBMD22
 tel.: 0-22-57-31-31; fax: 0-22-57-30-00



Sisteme Informatiionale Integrate
 Итегрированные Системные Решения
 Integrated System Solutions

1.3	325000 00-8	Convertoare optice tip III	Video multiplexer transmitter, 8 forward video channels (witch RS485, reverse direction) // Video multiplexer receiver, 8 forward video channels (witch RS485, reverse direction) (set)	China	Shenzhen Optostar Co., LTD	Video- 8 channel Video connector - BNC Input/output impedance :75 Ω <i>(unbalanced)</i> Bandwidth:8MHz Differential Gain: 1% Differential Phase 10 Video sampling <i>PAL/NTSC/SECAM fully compatible</i> Data RS485, reverse direction Connector Terminals block (2 wires) Control equipment PTZ <i>decoder, control keyboard, matrix control data interface, high speed dome, industrial equipment</i> Interface rate <i>10/100Mbps(AUTO)</i> Interface type RJ-45 Work mode:full duplex or half duplex Optical Interface FC Wavelength single-mode (Bi - direction) 1490/1310-1550nm Transmission distance >10 KM (SM) Power input AC100~240V, DC12V	Video- 8 channel Video connector - BNC Input/output impedance :75 Ω <i>(unbalanced)</i> Bandwidth:8MHz Differential Gain: 1% Differential Phase 10 Video sampling <i>PAL/NTSC/SECAM fully compatible</i> Data RS485, reverse direction Connector Terminals block (2 wires) Control equipment PTZ <i>decoder, control keyboard, matrix control data interface, high speed dome, industrial equipment</i> Interface rate <i>10/100Mbps(AUTO)</i> Interface type RJ-45 Work mode:full duplex or half duplex Optical Interface FC Wavelength single-mode (Bi - direction) 1490/1310- 1550nm Transmission distance >10 KM (SM) Power input AC100~240V, DC12V	
-----	----------------	-------------------------------	--	-------	----------------------------------	--	---	--

Republica Moldova, mun. Chisinau, MD-2002, str. Cetatea Alba 43
 C/F: 1002600027262
 TVA:0305086
 IBAN: MD91PR002251109768001498 la BC ProCreditBank SA
 BIC: PRCBMD22
 tel.: 0-22-57-31-31; fax: 0-22-57-30-00



Sisteme Informativale Integrate
Интегрированные Системные Решения
Integrated System Solutions

1.4	325000 00-8	Convertoare optice tip IV	Media Converter, one port cooper port 10/100/1000, second port hole for Gigabit SFP, with BiDi SFP modules 1310/1550	China	Shenzhen Optostar Co., LTD	Interface rate 10/100/1000 Mbps (Full duplex 2000Mbps) Interface type RJ-45 Work mode: full duplex or half duplex Optical Interface SFP port, SFP modules, WDM/SM, 9/125 Wavelength single-mode (Bi - direction) 1310/1550 Transmission distance >10 KM (SM) Power input AC100~240V, DC5V	Interface rate 10/100/1000 Mbps (Full duplex 2000Mbps) Interface type RJ-45 Work mode: full duplex or half duplex Optical Interface SFP port, SFP modules, WDM/SM, 9/125 Wavelength single-mode (Bi - direction) 1310/1550 Transmission distance >10 KM (SM) Power input AC100~240V, DC5V	
1.5	325000 00-8	Patch- corduri	SC/UPC- SC/UPC-SM-SX- 3M	China	Shenzhen Optostar Co., LTD	SC-SC SM 3m simplex	SC-SC SM 3m simplex	

Termenul de livrare - pina la 60 zile de la data semnarii contractului.

Semnat: _____
Numele, Prenumele: Alexandru Grițco
În calitate de: Director
Ofertantul: SRL Lanitron
Adresa: mun. Chișinău, str. Cetatea Albă 43
Data: 28/06/2021

Republica Moldova, mun. Chisinau, MD-2002, str. Cetatea Alba 43
C/F: 1002600027262
TVA:0305086
IBAN: MD91PR002251109768001498 la BC ProCreditBank SA
BIC: PRCBMD22
tel.: 0-22-57-31-31; fax: 0-22-57-30-00