

# PROWLER<sup>®</sup>

microcatheter



## PROWLER® microcatheter

### PRODUCT SPECIFICATIONS

- Construction: Proprietary braid / coil reinforced technology  
Proximal braided shaft / distal reinforced coil
- Inner coating: PTFE
- Outer coating: hydrophilic
- Hub material: nylon
- Max. guidewire:  
PROWLER® 10 microcatheter: 0.012"  
PROWLER® 14 microcatheter: 0.014"  
PROWLER® Plus microcatheter: 0.018"  
PROWLER® 27 microcatheter: 0.018"
- Min. guiding catheter ID:  
PROWLER® 10 and PROWLER® 14 microcatheters: 0.035"  
PROWLER® Plus microcatheter: 0.042"  
PROWLER® 27 microcatheter: 0.048"



Catalog No.	Usable Length (cm)	Total Length (cm)	Distal Flexible Length (cm)	Outer Diameter (prox./distal)	Inner Diameter (in)	Shape	Marker Bands
<b>PROWLER 10</b>							
606051X	150	155	50	2.3F/1.7F	0.015"	Straight	2
606051FX	150	155	50	2.3F/1.7F	0.015"	45°	2
606051MX	150	155	50	2.3F/1.7F	0.015"	90°	2
606051JX	150	155	50	2.3F/1.7F	0.015"	J	2
<b>PROWLER 14</b>							
606151X	150	155	50	2.3F/1.9F	0.0165"	Straight	2
606151FX	150	155	50	2.3F/1.9F	0.0165"	45°	2
606151MX	150	155	50	2.3F/1.9F	0.0165"	90°	2
606151JX	150	155	50	2.3F/1.9F	0.0165"	J	2
606171	170	175	50	2.3F/1.9F	0.0165"	Straight	1
<b>PROWLER Plus</b>							
6062510	150	155	20	2.8F/2.3F	0.021"	Straight	1
6062511	150	155	45	2.8F/2.3F	0.021"	Straight	1
6062510X	150	155	20	2.8F/2.3F	0.021"	Straight	2
6062510FX	150	155	20	2.8F/2.3F	0.021"	45°	2
6062510MX	150	155	20	2.8F/2.3F	0.021"	90°	2
6062510JX	150	155	20	2.8F/2.3F	0.021"	J	2
6062511X	150	155	45	2.8F/2.3F	0.021"	Straight	2
6062511FX	150	155	45	2.8F/2.3F	0.021"	45°	2
<b>PROWLER 27</b>							
MST27000000	150	154	35	3.0F/2.6F	0.027"	Straight	2



## PROWLER® SELECT® microcatheter

### PRODUCT SPECIFICATIONS

- Construction: Proprietary braid/coil reinforced technology  
Proximal braided shaft/distal reinforced coil
- Inner coating: PTFE
- Outer coating: hydrophilic
- Hub Material: nylon
- Max. guidewire:  
PROWLER® SELECT® LP-ES microcatheter: 0.014"  
PROWLER® SELECT® Plus microcatheter: 0.018"
- Min. guiding catheter ID:  
PROWLER® SELECT® LP-ES microcatheter: 0.035"  
PROWLER® SELECT® Plus microcatheter: 0.042"
- Shorter distal coil length + longer proximal braid length is designed to provide increased stability over standard Prowler catheters



Catalog No.	Usable Length (cm)	Total Length (cm)	Distal Flexible Length (cm)	Outer Diameter (prox./distal)	Inner Diameter (in)	Shape	Marker Bands
<b>PROWLER SELECT LP-ES</b>							
606S155X	150	155	5	2.3F/1.9F	0.0165"	Straight	2
606S155FX	150	155	5	2.3F/1.9F	0.0165"	45°	2
606S155MX	150	155	5	2.3F/1.9F	0.0165"	90°	2
606S155JX	150	155	5	2.3F/1.9F	0.0165"	J	2
<b>PROWLER SELECT Plus</b>							
606S255X	150	155	5	2.8F/2.3F	0.021"	Straight	2
606S255FX	150	155	5	2.8F/2.3F	0.021"	45°	2
606S255MX	150	155	5	2.8F/2.3F	0.021"	90°	2
606S255JX	150	155	5	2.8F/2.3F	0.021"	J	2

