



K - SERIES
GN 2/1 SIZE
 700-1400 LT
 REFRIGERATOR

OUTER BODY
 AISI 430
INSIDE CABINET
 AISI 304

TEMPERATURE
0 / +10 °C



OPTIONAL ACCESSORIES

- REMOTE CONDENSING UNIT
- WIFI MONITORING KIT
- BLUETOOTH MONITORING KIT
- RS 485 / RS 232 ADAPTER
- GRID SHELF
- DOOR/DRAWER LOCK
- H:50MM / Ø:125MM. CASTER



06

















	REFRIGERANT		ENERGY EFFICIENCY (R290)	L	W/P	H	CAPACITY	INSULATION	SHELF	TEMP.	VOLTAGE	WEIGHT	
	(R134A)	(R290)											
	79K4.07NMV.00	72K4.07NMV.00		C	654	830	2000	700 lt	60 mm	3	0.21 kW	220-240 / 50-60 Hz	107 kg
											0.19 kW	230V / 50 Hz	
	79K4.14NMV.00	72K4.14NMV.00		C	1344	830	2000	1400 lt	60 mm	6	0.37 kW	220-240 / 50-60 Hz	176 kg
											0.35 kW	230V / 50 Hz	
	79K4.07NMV.10	72K4.07NMV.10		C	654	830	2000	700 lt	60 mm	3	0.21 kW	220-240 / 50-60 Hz	107 kg
											0.19 kW	230V / 50 Hz	
	79K4.14NMV.10	72K4.14NMV.10		C	1344	830	2000	1400 lt	60 mm	6	0.37 kW	220-240 / 50-60 Hz	171 kg
											0.35 kW	230V / 50 Hz	
	79K4.07NMV.01	72K4.07NMV.01		D	654	830	2000	700 lt	60 mm	3	0.21 kW	220-240 / 50-60 Hz	114 kg
											0.19 kW	230V / 50 Hz	
	79K4.14NMV.01	72K4.14NMV.01		D	1344	830	2000	1400 lt	60 mm	6	0.37 kW	220-240 / 50-60 Hz	185 kg
											0.35 kW	230V / 50 Hz	
	79K4.07NMV.11	72K4.07NMV.11		D	654	830	2000	700 lt	60 mm	3	0.21 kW	220-240 / 50-60 Hz	114 kg
											0.19 kW	230V / 50 Hz	
	79K4.14NMV.11	72K4.14NMV.11		D	1344	830	2000	1400 lt	60 mm	6	0.37 kW	220-240 / 50-60 Hz	185 kg
											0.35 kW	230V / 50 Hz	
















Boiling Tops		Electric Boiling Tops	
			

7865.N1.40903.20

7865.N1.12903.21



	CODE	BURNER	L	W	H	BURNER POWER	TOTAL POWER	VOLTAGE
	7865.N1.40903.20		400	900	280	6 + 10 kW	16 kW	-
	7865.N1.80903.20		800	900	280	2 x 6 + 2 x 10 kW	32 kW	-
	7865.N1.80903.20P		800	900	280	4 x 10 kW	40 kW	-
	7865.N1.12903.20		1200	900	280	3 x 6 + 3 x 10 kW	48 kW	-
	7865.N1.12903.20P		1200	900	280	6 x 10 kW	60 kW	-
	7865.N1.40903.21		400	900	280	2x4 kW	8 kW	400 V 3 NPE 50/60 Hz
	7865.N1.80903.21		800	900	280	4x4 kW	16 kW	400 V 3 NPE 50/60 Hz
	7865.N1.12903.21		1200	900	280	6x4 kW	24 kW	400 V 3 NPE 50/60 Hz

Wok Burners																							
																							
<p>High power cast iron burners</p> <p>Durable and strong cast iron cooking ring designed to meet heavy load</p>	<p>Removable cooking ring ensures easier cleaning on the top</p> <p>Removable drip tray under the burners for easy cleaning</p>																						
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr style="background-color: #cccccc;"> <th style="width: 10%;"></th> <th style="width: 15%;">CODE</th> <th style="width: 5%;">BURNER</th> <th style="width: 5%;">L</th> <th style="width: 5%;">W</th> <th style="width: 5%;">H</th> <th style="width: 10%;">POWER</th> </tr> </thead> <tbody> <tr> <td></td> <td>7865.N1.40903.WK</td> <td></td> <td>400</td> <td>900</td> <td>280</td> <td>14 kW</td> </tr> <tr> <td></td> <td>7865.N1.80903.WK</td> <td></td> <td>800</td> <td>900</td> <td>280</td> <td>28 kW</td> </tr> </tbody> </table>		CODE	BURNER	L	W	H	POWER		7865.N1.40903.WK		400	900	280	14 kW		7865.N1.80903.WK		800	900	280	28 kW		7865.N1.40903.WK
	CODE	BURNER	L	W	H	POWER																	
	7865.N1.40903.WK		400	900	280	14 kW																	
	7865.N1.80903.WK		800	900	280	28 kW																	