

ARAL SuperTronic K 5W-30

High-performance engine oil for extended service intervals



Description

ARAL SuperTronic K 5W-30 is designed for petrol and diesel engines, offering the following benefits:

- Meets the highest standards for wear protection
- Aral Low SAPS technology for extended lifespan of the diesel particulate filter
- Suitable for vehicles with and without LongLife service
- Improved fuel economy

Application

ARAL SuperTronic K 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA C3, API SN 5W-30 Lubricant.

ARAL SuperTronic K 5W-30 is approved for use in vehicles from leading manufacturers please refer to the specifications section, and your owner's handbook.

Typical Characteristics

Name	Method	Units	ARAL SuperTronic K 5W-30
Density @ 15C, Relative	DIN 51757	g/ml	0.85
Viscosity, Kinematic 100C	DIN 51562	mm ² /s	11.6
Viscosity, CCS -30C (5W)	DIN 51377	mPa.s (cP)	5950
Viscosity, Kinematic 40C	DIN 51562	mm ² /s	65
Viscosity Index	DIN ISO 2909	None	175
Pour Point	ASTM D5950	°C	-45
Flash Point, PMCC	ASTM D93	°C	196
Ash, Sulphated	ASTM D874	% wt	0.8

Product Performance Claims

ACEA C3
API SN
BMW Longlife-04
MB-Approval 229.31/ 229.51
Porsche C30
VW 504 00/ 507 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

ARAL SuperTronic K 5W-30

14 Jun 2019

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

www.aral-lubricants.de