

Procleix NAT Manager

Procleix solutions – Improving safety & operational efficiency

Procleix NAT Manager software is designed to centralize and integrate all steps of Grifols Procleix NAT blood and plasma screening solutions



Procleix NAT Manager version 1.2

AVAILABLE CONFIGURATIONS

Single user system	1 workstation with Procleix NAT Manager (NATM) application and master dongle
Multi-user system with server supplied by Grifols	1 workstation with NATM application and master dongle, multiple workstations with NATM application and terminal dongles, 1 server with database
Multi-user system with server supplied by user	1 workstation with NATM application and master dongle, multiple workstations with NATM application and terminal dongles, 1 database to install on user server

PRODUCT COMPATIBILITY*

NAT Systems	Procleix Tigris and Panther systems
Pooling Systems	Procleix Xpress, SP and CPT pooling systems
Assays	Procleix Ultrio, Ultrio Plus, WNV, Dengue, Zika, Parvo/HAV, Babesia, Ultrio Elite, HEV assays

* Not all products described in the Procleix NAT Manager Software product compatibility table are approved for use in all countries. Procleix NAT Manager Software should be used only with assays approved in their respective countries.

SCREENING

Technical specifications

WORKSTATION SPECIFICATION (SUPPLIED BY GRIFOLS)

The workstation used to run Procleix NAT Manager software is provided by Grifols, and is configured specifically for this use. The minimum requirements for this workstation are as follows:

Computer type	IBM compatible
Processor	Intel 2.40 GHz or greater
Memory (RAM)	8 GB
Hard drive(s)	500 GB 7200 RPM
Operating system	Microsoft Windows 7 64-bit or Windows 10
Network card	Gigabit Ethernet
Optical drive	CD/DVD-RW
Monitor	22" display with a resolution of 1680 x 1050. Aspect ratio 16:10
Keyboard	USB keyboard, English
USB	2.0 or higher USB port
Mouse	USB mouse
Additional software	Microsoft SQL Server 2014 Standard (optional, included in the software installation on a stand-alone workstation), Adobe Acrobat Reader 10
Other	Master dongle installed on at least one workstation in the laboratory, Terminal dongle(s) (one per each additional workstation), Symbol Barcode Scanner Model No. LS4208

MINIMUM SERVER SPECIFICATION (SUPPLIED BY GRIFOLS OR THE USER)

The server for multi-user configurations is provided by Grifols, and is configured specifically for this use. Alternatively, users can supply their own server. The server must meet the following minimum requirements:

Computer type	IBM compatible or Hyper-V VMware virtual machine
Processor	2-gigahertz (GHz) or faster 32-bit (x86) or 64-bit (x64) processor
Memory (RAM)	4 GB
Hard drive(s)	500 GB
Operating system	Microsoft Windows 2008 R2 Server 64-bit or 2012 R2 Server 64-bit (or later versions as they are qualified by Grifols) or Windows 2016
Additional software	An instance of Microsoft SQL Server 2008 R2, 2012, or 2014 (or later versions as they are qualified by Grifols)

Product registration and availability vary by country.
For more information, ask your local Grifols representative.

Learn more about Procleix products
at www.procleix.com

GRIFOLS

Grifols International, S.A.
Av. de la Generalitat, 153-159
08174 Sant Cugat del Vallès
Barcelona, Spain
Tel: +34 935 710 500

Grifols Diagnostic Solutions Inc.
4560 Horton Street
Emeryville, CA 94608
USA
Tel: +1 800 452 6877