

LABMATE PRO pipette series

The LABMATE PRO pipette family offers a wide variety of volume models for different laboratory applications. Its durable, UV resistant and autoclavable body is coupled with high accuracy and precision performance to ensure many years of reliable service in laboratories all over the world.




- Contoured shape of the handle and light weight
- Proven accuracy and precision
- UV resistant & fully autoclavable
- 5 & 10 mL shaft protected by filter
- Available in 8- & 12-channel version
- Colour coded shafts for easy volume identification



The adjustable ejector height system – to accommodate virtually all brands of tips




Dual volume setting using the pushbutton or the thumbwheel



Soft spring system for smooth, effortless pipetting

Multichannel LABMATE PRO pipette version feature a revolutionary suspension system which allows the shafts to retract slightly when pressed against a row of pipette tips. Each shaft moves independently, resulting in an even sealing force being applied to all 8 or 12 tips. The suspension system not only ensures secure tip sealing but also eliminates the common incident of tips being jammed. The 360° rotating manifold guarantees optimal working comfort.



5484

Carousel stand

5449

Multiple stand

5480

Plexi 4-position stand

5479

Plexi 1-position stand

Model	Cat. no.	Colour code	Volume (µL)	A (%)	P (%)	Standard tips, non-filtered
LMP2*	5661	●	0.2 1.0 Max 2.0	± 12.0 ± 2.7 ± 1.5	± 6.0 ± 1.3 ± 0.7	10 µL
LMP10	5662	●	Min 0.5 5.0 Max 10.0	± 4.0 ± 1.0 ± 0.5	± 2.8 ± 0.6 ± 0.4	
LMP20	5663	●	Min 2 10 Max 20	± 3.0 ± 1.0 ± 0.8	± 1.5 ± 0.5 ± 0.3	200 µL
LMP50	5667	●	Min 5 25 Max 50	± 2.5 ± 1.0 ± 0.8	± 2.0 ± 0.6 ± 0.4	
LMP100	5664	●	Min 10 50 Max 100	± 1.6 ± 0.8 ± 0.8	± 0.80 ± 0.24 ± 0.20	
LMP200	5665	●	Min 20 100 Max 200	± 1.2 ± 0.8 ± 0.6	± 0.60 ± 0.25 ± 0.20	300 µL
LMP250	5660	●	Min 50 125 Max 250	± 1.0 ± 0.8 ± 0.6	± 0.4 ± 0.3 ± 0.3	
LMP1000	5666	●	Min 100 500 Max 1,000	± 1.6 ± 0.7 ± 0.6	± 0.40 ± 0.20 ± 0.15	1,000 µL
LMP5000	5668	○	Min 500 2,500 Max 5000	± 1.2 ± 0.6 ± 0.5	± 0.5 ± 0.20 ± 0.15	5,000 µL
LMP10000	5669	○	Min 1,000 5,000 Max 10,000	± 2.5 ± 0.8 ± 0.5	± 0.6 ± 0.3 ± 0.2	10,000 µL

* LMP2 – minimum volume is 0.1 µL.

Model	Cat. no.	Colour code	Volume (µL)	A (%)	P (%)	Standard tips, non-filtered
LMP8-10 LMP12-10	6281 6285	●	Min 0.5 5 Max 10	± 10.0 ± 4.0 ± 2.0	± 8.0 ± 2.0 ± 1.2	10 µL
LMP8-50 LMP12-50	6282 6286	●	Min 5 25 Max 50	± 4.0 ± 3.0 ± 1.6	± 2.5 ± 1.2 ± 0.6	200 µL
LMP8-200 LMP12-200	6283 6287	●	Min 20 100 Max 200	± 3.0 ± 1.5 ± 1.0	± 1.5 ± 0.8 ± 0.6	300 µL
LMP8-300 LMP12-300	6284 6288	●	Min 50 150 Max 300	± 1.6 ± 1.2 ± 1.0	± 1.5 ± 1.0 ± 0.6	

Note: The HTL maximum permissible errors are guaranteed only when HTL pipette tips are used.

Starter LABMATE PRO 4 pack

Economy set of 4 pipettes and accessories.

Product	Cat. no.	Model	Accessories
LABMATE PRO STARTER 4 PACK	7905	LMP10 LMP20 LMP200 LMP1000	Plexi 4-position stand Tips 10 µL, 96 pcs Tips 200 µL, 96 pcs Tips 1,000 µL, 96 pcs Calibration tool x 4 Pipette hanger x 4 Instruction manual

