SPECIFICAŢII TEHNICE (F4.1)

Nr. ocds-b3wdp1-MD-1565348882268	01 octombrie 2019	Alternativa nr.-
Denumirea licitaţiei: Serviciul de Informaţii şi Securitate al RM	Lot 1-25	Pagina 1 din 1

LOT	Denumirea bunurilor şi/sau a serviciilor	Modelul articolului	Ţara de origine	Produ-cătorul	Specificarea tehnică deplină solicitată	Specificarea tehnică deplină propusă de către ofertant	Standarde de referinţă
1	2	3	4	5	6	7	8
Lot 1	Bloc de alimentare (PWR-C2-250WAC)	PWR-C2-250	China	Cisco	Power Supply Rated Maximum: 250W; Total Output BTU (Note: 1000 BTU per hr = 293 W): 853 BTU/hr, 250W; Input-Voltage Range and Frequency (Note: ±10% of "Input-Voltage Range"): 100-240VAC, 50-60 Hz; Input Current: 4-2A;Output Ratings: 12V @ 20.83AOutput Holdup Time: 16.7 ms minimum @ 100VAC;Power-Supply Input Receptacles: IEC 320-C13 (IEC60320-C13);Power Cord Rating: 10A;Physical Specifications: (H x W x D): 1.58 X 3.75 X 11.75 in (4.0 x 9.5 x 29.8 cm) ±1%; Weight: 2.55 lb (1.16 kg) ±5%;Storage Temperature: -40 to 158°F (-40 to 70°C); Relative Humidity Operating and Non-operating: Non-condensing 5 to 95% non-condensing; LED Indicator: -40 to 158°F (-40 to 70°C) Origin: Ideas Cost plus WS 2060XB	PWR-C2-250WAC= Catalyst 3650 Series Spare Power Supply	
Lot 2	HDD for server						
Lot 3	Memorie de stocare						
Lot 4	Calculator staţionar	Atol G5400	Moldova	Accent Electronic	Carcasa: Black, ATX/MicroATX, USB 3.0, USB 2.0, HD Audio, microfon, 3,5 drive bays, 2,5 drive bays, buclă pentru lacăt pe ambele parti. Bloc de alimentare:ATX 12 V, v2.31, 700 W, 220-240V, 20+4 pin 1PCS/CPU 12V 4+4pin minimum, minimum 4 xSata, minimum 4xPCI-E, 1x120 mm cooler/Active PFC, Inteligent fan speed control, PWM auto fan speed temp-controlled, 25 dBA. Placa mamă:ATX/mATX, 1151, Suport windows 7/10 x32/x64, DDR4 minimum 2xSlots, 1xVGA, 1xDVI, 1xHDMI, PCI-E X1, PCI-E x16, 4xSATAIII 6.0 Gb/s, minimum 1xPS/2, minimum 2xUSB 3.1, minimum 2xUSB2.0/GLAN RJ-45 with led/ Audio HD, all solid state capacitors. Procesor:2x3.7GHz, 4 Mb, 1151, 8GT/s, HD Graphics, 14 nm, 54-58 W, DDR4, VT-x, (Dual core)/Suport windows 7/10 x32/x64. Cooler CPU:1151/ fan 120x25 mm/900-1600 rpm/55,5 cfm/125 W/ 17.8-26,1 dBA/ input 1,56 W. RAM:4 GB DDR4 2400 MHz PC19200. HDD: HDD 500GB, SATA-III (6 Gb/s), 7200RPM, 32MB, 3,5".	Calculator Atol G5400 Mainboard: ASUS PRIME H310M-R R2.0-SI, Socket 1151, Intel® H310 (9th/8th Gen CPU), Dual 2xDDR4-2666, 1xPCIe X16, CPU Intel graphics, VGA, DVI, HDMI, 4xSATA3, 1xPCIe X1, ALC887 HDA, GbE LAN, 4xUSB3.1, mATX, CPU: Intel® Pentium® Gold G5400, S1151, 3.7GHz (2C/4T), 4MB Cache, Intel® UHD Graphics 610, 14nm 54W, tray, RAM: 4GB DDR4-2400 Kingston ValueRam, PC19200, CL17, 1.2V, HDD: 3.5" HDD 500GB Toshiba DT01ACA050, Desktop™, 7200rpm, 32MB, SATAIII Case: DEEPCOOL "SMARTER" Micro-ATX Case, without PSU, fully black painted interior, VGA Compatibility: 320mm, CPU Cooler Compatibility: 165mm, 1x 2.5" Drive Bays, 1xUSB3.0, 1xUSB2.0 /Audio, Black, Back Lock PSU: XDC-DA700N - PSU DEEPCOOL "DA700", 700W, ATX 2.31, 80 PLUS® Bronze, Active PFC, 120mm Silent fan with PWM, Double Layer EMI Filter, +12V (54A), 20+4 Pin, 1xEPS(4+4Pin), 5x SATA, 4xPCI-E(6+2pin), 4x Periph., MTBF100000Hours, Black XDC-GAMMAXX300 DEEPCOOL Cooler "GAMMAXX 300", Socket 775/1150/1151/2011 & AM4/FM2/AM3, up to 130W, 120õ120õ25mm, 900~1600rpm, 17.8~21dBA, 55.5CFM, 4 pin, PWM, Hydro Bearing, 3 heatpipes direct contact	
Lot 5	Calculator staţionar asamblat la uzina producătorului	M720	China	Lenovo	Carcasa: Carcasa şi componente interne asamblate la uzina producătorului Destkop Black . tower, 5.25" ODD bays, 3.5" external bays, internal bays 3.5", 2.5", USB2.0, USB3.0, audio jack.; Bloc de alimentare:minim 300 W. Placa mamă:PCI Express x1, PC Express x16, DVI, VGA, USB 2.0, USB 3.1, Audio IN/AUT,m Gigabit Ethernet, No WLAN. Procesor şi Cooler CPU:minim CPU 2x3.5 Ghz, 3 MB, 1151, Cooler CPU. RAM:minim Memory 4GB (Up to 32 GB of Dual-channel DDR4 2400 MHz. HDD:minim 1 TB 3.5/2.5-inch 7200 RPM. Monitor (cu boxe incluse):În set cu blocul de sistema asamblat de la uzina producătorului. nu mai mic de 21,5" black 1920x1080 full HD, twisted nematic+film, LED, minim 200 cd/m2, mat, 5 ms, 100000000:1, unghiul observării pe laturile 100/70, 1xD-sub, 1xDVI, 1xHDMI, ajustarea poziţiei ecranului înclinare, cablu VGA, DVI, cablu de alimentare. Tastieră/mouse:Mouse, keyboard în complet cu blocul de sistem asamblat de la uzina producătorului. Sistem de operare licenţiat:Microsoft Windows 10 pro x32/x64, En.	Lenovo Desktop TC M720t, Intel Pentium Gold G5400 Processor (4MB Cache, 3.70GHz), 4GB DDR4 2666MHz UDIMM, 1TB Hard Drive, 7200RPM, 3.5", SATA3, Integrated Graphic Card, Integrated Ethernet, Internal Speaker Tower, TW B360 CFL-R 210W 85%, Windows 10 Pro 64 English, USB Calliope Keyboard Black Russian, USB Calliope Mouse Black, 3 Year Depot or Carry-in Monitor Lenovo ThinkVision T22v-10 21.5 inch Wide FHD VOIP Monitor FHD, In-Plane Switching panel with 1920 X 1080 resolution CR 1000:1, Brightness 250 cd/m2, DCR 3M:1 4ms fast response time, VGA+HDMI 1.4+DP 1.2+ Audio In/Out USB 3.0 Hub, Integrated speakers, dual-array microphone,	
Lot 6	Tastieră	K120	China	Logitech	Keyboard BLACK ErgoComfort, RoundEdge Keycaps PS/2 (US+RO+RU), lungime fir 180 cm, ajustare înălţime, compatibile Win 7/8/10, rezistenţă la umeditate.	LO 920-002522 Logitech Keyboard K120	
Lot 7	Mouse	RX-30	China	Sven	Black, Optical Wheel 1000 dpi, 2 taste+Scroll button, USB, lungime fir 180 cm.	SV RX-30 USB - SVEN RX-30, Optical Mouse, 1000 dpi, USB, 2m, Black	
Lot 8	UPS	Pro 1000	China	Sven	Line Interactive/600w/1000va/220-240V/ AVR/CPU controled, battery 12v/7A sau (7,2A), minim 2 puteri de ieşire/alarmă sonoră, protecţie la suprasarcină, protecţie la puls de înaltă tensiune, protecţie împotriva scurtcircuitelor.	SVEN Pro 1000 (USB), Line-interactive UPS with AVR, 1000VA /720W, 3x Schuko outlets, 2x7AH, AVR: 175-280V, USB, RJ-45, Cold start function, Black	
Lot 9	Imprimantă	MF631CN	China	Canon	color/tehnologie laser, A4, minim 30000 foi\luna, 4 culori, minim 600x600 dpi, minim 18 foi/min, 52-220 g/m2, posibilitate de printare pe carton, foi fotografice, etichete, 4 cartuşe, 16MB si mai mare, GLAN, USB 2.0, max 600 W, max 65 db, no WI-FI. Suplimentar set de cărtuşe originale de rezervă.	MFD Canon i-Sensys MF631CN, Color Printer/Copier/Scanner,Net,USB-Host, A4,18ppm,1GB,1200x1200dpi, 52-163g/m2,Scan 9600x9600dpi,150+1-sheet tray,UFRII,Max.30k pages per month, Cart 045HBk(2800p)/045Bk(1400p)+045HC/M/Y(2200p)/045C/M/Y(1300p)	
Lot 10	Scaner						
Lot 11	Aplicaţie de video redactare						
Lot 12	Aplicaţie prelucrare text						
Lot 13	Memorie de stocare	M3	China	Maxtor	Portable HDD 4 TB si mai mare, 2.5", USB 3.0/3.1, minim 480 mb/s write, 8 mb cache minim, compatibil Microsoft Windows 7/10, antishock protection.	2.5" External HDD 4.0TB (USB3.0) Seagate "Maxtor M3 Portable" STSHX-M401TCBM, Durable Black design	
Lot 14	Memorie de stocare	230	China	Transcend	SSD 256 GB, SATA III, minim write 520 mb/s , minim read 560 mb/s, 2,5".	2.5" SSD 256GB Transcend Premium 230 Series SATAIII, Aluminum case, Sequential Reads 560 MB/s, Sequential Writes 520 MB/s, Max Random 4k: Read 65,000 IOPS / Write 85,000 IOPS (IOmeter)*, SMI SM2258, 7mm, DDR3 DRAM cache, 3D NAND TLC	
Lot 15	Hîrtie pentru plotter	36"	China	Canon	Bright White Inkjet Paper/ (914 mm x 45,7 m, 90 g/m, 119 microns), compatibil cu Plotter HP DesignJet T795.	Paper Canon Standard Rolle 36" - A0 (914mm), 90 g/m2, 50m, Standard Paper (General USE, CAD / GIS, Proofing and Production markets)	
Lot 16	Cartuşe pentru imprimantă	729	China	Canon	Set Cartuse originale pentru Canon i-Sensys LBP7018C.	Laser Cartridge Canon 729 (HP CE310A, CE311A, CE312A, CE313A), black (1200 pages) for LBP-7010C/7018C	
Lot 17	Cartuşe pentru imprimantă	731	China	Canon	Set Cartuse originale pentru Canon i-Sensys LBP7100Cn.	Laser Cartridge Canon 731 (HP CF210A, CF211A, CF212A, CF213A (131A)), cyan (1500 pages) for LBP7100C/ 7110C, MF-8230/8280 & HP LaserJet Pro 200 Color	
Lot 18	Pastă termica						
Lot 19	Televizor						
Lot 20	Televizor						
Lot 21	Suport pentru TV LCD	WM-65T	China	Gembird	XDC-GAMMAXX300 DEEPCOOL Cooler "GAMMAXX 300", Socket 775/1150/1151/2011 & AM4/FM2/AM3, up to 130W, 120õ120õ25mm, 900~1600rpm, 17.8~21dBA, 55.5CFM, 4 pin, PWM, Hydro Bearing, 3 heatpipes direct contact	TV-Wall Mount for 32-65"- Gembird "WM-65T-01", Tilt, max. 40 kg, Tilting angle 15°, Distance TV to Wall: 50 mm, max. VESA 600 x 400, Black	
Lot 22	Suport pentru TV LCD	WM-70T	China	Gembird	Tip: montare;P/u modele cu diagonala (inch): 37 – 70;Tipul de suspensie: suport pe perete;Reglare pe înălţime: Da;Material: metal;Greutate maximă (kg): ≥35.	TV-Wall Mount for 32-70"- Gembird "WM-70T-01", Tilt, max. 50 kg, Tilting angle 15°, Distance TV to Wall: 40 mm, max. VESA 600 x 400, Black	
Lot 23	Acumulatori	12V7AH	China	Gembird	Tensiunea nominală: 12V;Capacitatea:7Ah;Destinaţie: UPS, calculatoare şi tehnică digitală;Protecţie: Etanşat cu supapă de protecţie fără mentenanţă ;Anul producerii: 2019;Tip borne: T2;Temperatură de operare: -15 ° ~ +50 °C;Curent maxim de încărcare: ≤ 3 ADimensiuni: ≤ 151x100x65mm;Garanţie– 24 luni;	GMB BAT-12V7AH - Gembird Battery 12V 7AH	
Lot 24	UPS-1500VA	SMT1500RMI2U	China	APC	Voltaj nominal input: 230V, 50/60;Gama voltaj input: 160-283 V Voltaj nominal output: 230V; Voltaj regulat output: 220V, 230V, 240V ;Puterea de ieşire: 1500 VA; Tip: Line interactive;Timp de transfer: ≤3 ms;Port comunicare: RJ-45, SmartSlot, USB;Dotări: Placă de management al reţelei cu monitorizarea mediului;Destinaţie: Rack mount 2U;Interfaţă: LCD;Culoare: Negru;Dimensiuni(h,w,d): ≤ 90x435x460 mm;Timp de menţinere: minim 25 minute la 50% sarcină;Alarmă audio: Da;Nivel zgomot de la 1 metru:≤48 dB;Temperatura de operare: 0 °~40 ° C;Greutatea: ≤ 30 kg;Certificare: IEC 62040-1; Directiva EC;Software pentru management: Da;Baterie inclusă: Da;Garanţie– 36 luni;	SMT1500RMI2U - APC Smart-UPS 1500VA LCD Rack Mount 2U, Black, 230V, line-interactive, PowerChute Business Edition, RS-232, USB, SmartSlot (option RBC133 battery)	
Lot 25	Bloc de alimentare 24V						
	TOTAL						

Semnat: _____
Nume: Eugeniu Cobilas
În calitate de: Director general
Ofertantul: **„Accent Electronic" SA**
Adresa: or. Chişinău, str. Bulgară 33/1
Data: 01 octombrie 2019

Digitally signed by Cobîlaş Eugeniu
Date: 2019.09.30 15:56:18 EEST
Reason: MoldSign Signature
Location: Moldova