

We **iDEAL MAKINA ENDÜSTRİ ÜRÜNLERİ SAN. VE TİC. A.Ş.,** who are official manufacturers of Oxygen Generator System & accessories, IDEAL MAKİNA Company having factories at Emek, Ordu Cd. No:16, 34785 Dudullu Osb/Sancaktepe/İstanbul do hereby confirm that the offered **IDEAL IM-GO 200 OXYGEN GENERATOR SYSTEM** with all of its components, work altogether efficiently. Thus the combination between the air compressor & air dryer & filters, allows the adequate generation of compressed air necessary for the oxygen generator with the pressure, temperature, flow necessary for creating oxygen of 93%±3.

Alpaslan Tekin General Manager Dated on 10.02.2023



İdeal Makina Endüstri Ürünleri San. ve Tic. A.Ş. Esenkent Mh. Nato Yolu Cd. No:277 34776 Ümraniye - İstanbul - Türkiye/Turkey T +90 216 540 88 55 F +90 216 540 88 18 E info@idealmakina.com



### compliance with the parameters of the Dalgakıran Inversys 22 Plus Compressor of the IDEAL IM-GO 200 Oxygen Generator System

This certifies that the compressor with the parameters specified in the table will provide the necessary amount of compressed air with the specified working pressure and flow for the needs of the oxygen generator: IDEAL IM-GO 200 Oxygen Generator

Name parameters	Characteristics
Model	INVERSYS 22 PLUS
Compressor type	Variable Speed Direct Drive Screw Air
	Compressor
Maximum air pressure	10 bar
Compressed air capacity	78 – 228 m³/h
Nominal pressure, bar	9,5 bar
Performance regulation	Using a frequency converter
Power of the main drive, kW	22
Supply voltage/current frequency, V/Hz	380/50
Compressor cooling	Air
Compressor drive	Direct Drive

Alpaslan Tekin **General Manager** Dated on 10.02.2023

> idea IDEAL MAKINA END Esenkent Mh. Nato Yolux Sarigazi V.D 470 09 530388 Tic Sic No www.idealmakina.com

İdeal Makina Endüstri Ürünleri San. ve Tic. A.Ş. Esenkent Mh. Nato Yolu Cd. No:277 34776 Ümraniy<u>e - İstanbul - Türkiye/Turkey T +90 216 540</u> 88 55 **F** +90 216 540 88 18 **E** info@idealmakina.com



compliance with the parameters of the Friulair AMD 61 Refrigerant Dryer of the IDEAL IM-GO 200 Oxygen Generator System

This certifies that the refrigerating dryer with the parameters specified in the table will provide drying of the compressed air produced by the screw compressor INVERSYS 22 PLUS for the needs of the oxygen generator: IDEAL IM-GO 200 Oxygen Generator

Name parameters	Characteristics
Model	FRIULAIR AMD 61 REFRIGERANT AIR DRYER
Type of dryer	Refrigerant dryer
Working environment	Compressed atmospheric air
Dryer capacity	366 Nm <sup>3</sup> /h
Dew point temperature (at a temperature of compressed air at the inlet of 35°C and a pressure of 7 bar),	3°C
Maximum air pressure	14 bar
Maximum air temperature at the entrance to the dryer	55°C
Power Supply	230V/1Ph/50Hz
Nominal Electric Consumption	820 W – 4.2 A
Cooling	Air
Cooling Air Flow	400 m <sup>3</sup> /h

Alpaslan Tekin **General Manager** Dated on 10.02.2023



İdeal Makina Endüstri Ürünleri San. ve Tic. A.Ş. Esenkent Mh. Nato Yolu Cd. No:277 34776 Ümraniy<u>e - İstanbul - Türkiye/Turkey T +90 216 540</u> 88 55 **F** +90 216 540 88 18 **E** info@idealmakina.com



compliance with the parameters of the filtration system of the IDEAL IM-GO 200 Oxygen **Generator System** 

This certifies that the number and brand of filters, depending on the type of filter elements with the parameters specified in the table, will ensure the required air purity class at the entrance to the IDEAL IM-GO 200 Oxygen Generator.

### Filters;

Name parameters	Characteristics
Model	IDEAL AF0306M,
	IDEAL AF0306P,
	IDEAL AF0306S,
Working environment	Compressed air
Maximum working pressure	16 bar
Capacity	335 Nm3/h
Degree of filtration of filter elements,	type M – 0,1 μm
	type P – 3 μm
	type S – 0,01 μm

### Carbon tower;

Name parameters	Characteristics
Model	IDEAL ICT 250,
Working environment	Compressed air
Maximum working pressure	16 bar
Capacity	250 Nm3/h
Residual oil vapour content	<0,003 µm

### **Antibacterial Filter;**

Name parameters	Characteristics
Model	WALKER A30125MS,
Working environment	Compressed air
Maximum working pressure	16 bar
Capacity	212 Nm3/h
DOP efficiency	>99.9999%

Alpaslan Tekin **General Manager** Dated on 10.02.2023



İdeal Makina Endüstri Ürünleri San. ve Tic. A.Ş. Esenkent Mh. Nato Yolu Cd. No:277 34776 Ümraniy<u>e - İstanbul - Türkiye/Turkey T +90 216 540</u> 88 55 **F** +90 216 540 88 18 **E** info@idealmakina.com



compliance with the parameters of the **ideal IM-GO 200 Oxygen Generator** of the **IDEAL IM-GO 200 Oxygen Generator System** 

This certifies that the oxygen generator with the parameters specified in the table will provide the necessary amount of oxygen gas with the specified parameters of tender specifications.

Name parameters	Characteristics
Model	IDEAL IM-GO 200 OXYGEN GENERATOR
The method of obtaining oxygen	PSA – Pressure Swing Adsorption
The required class of air cleanliness at the	1.4.1
entrance in accordance with ISO 8573-1-2013	
The final product	Oxygen Gas
Capacity	17 Nm3/h
Oxygen purity	93±3%
Oxygen pressure	5-6 bar
Power	0,15 kW
Power Supply	230V/1Ph/50Hz
Adsorbent	Zeolite
*Service life of zeolite	60000 hours
Volume of each column	500 L

\*Service life under conditions of compliance with the class of air cleanliness at the entrance to the oxygen generator class 1.4.1 according to ISO 8573-1-2013.

Alpaslan Tekin General Manager Dated on 10.02.2023



İdeal Makina Endüstri Ürünleri San. ve Tic. A.Ş.

Esenkent Mh. Nato Yolu Cd. No:277 34776 Ümraniye - İstanbul - Türkiye/Turkey T +90 216 540 88 55 F +90 216 540 88 18 E info@idealmakina.com