



■ FD5000B

ULTRASONIC POCKET DOPPLER

- Compact design with easy one-hand operation, plug-and-play
- Bright OLED screen with real-time FHR display
- Hi-Fi speaker
- Supplied with 2 MHz probe (waterproof and replaceable)
- Automatic power-off
- Powered by standard AA batteries (not included)
- Charger stand (optional)
- Other probes are available on demand: 3/4/5/8 MHz

CARDIOTOCOGRAFHE - MONITEUR FOETAL

- Design compacte, facile à utiliser d'une seule main, plug-and-play
- Écran OLED lumineux avec affichage FHR en temps réel
- Haut-parleur Hi-Fi
- Fourni avec une sonde de 2 MHz (étanche et remplaçable)
- Mise hors tension automatique
- Alimenté par des piles AA standard (non inclus)
- Support de charge (optionnel)
- Autres sondes sont disponibles sur demande: 3/4/5/8 MHz



■ FD5000B PLUS

ULTRASONIC POCKET DOPPLER

- Compact design with easy one-hand operation, plug-and-play
- Bright OLED screen with real-time FHR display
- Hi-Fi speaker
- Supplied with 2 MHz probe (waterproof and replaceable)
- Automatic power-off
- Powered by built-in Li-ion rechargeable battery and battery charger (included)
- Charger stand (optional)
- Other probes are available on demand: 3/4/5/8 MHz

CARDIOTOCOGRAFHE - MONITEUR FOETAL

- Design compacte, facile à utiliser d'une seule main, plug-and-play
- Écran OLED lumineux avec affichage FHR en temps réel
- Haut-parleur Hi-Fi
- Fourni avec une sonde de 2 MHz (étanche et remplaçable)
- Mise hors tension automatique
- Alimenté par batterie rechargeable Li-ion intégrée et chargeur (inclus)
- Support de charge (optionnel)
- Autres sondes sont disponibles sur demande: 3/4/5/8 MHz

CODE	FD5000B	FD5000BPLUS	FM5000C	FM5000PLUS	FM5000E
Dimensions	16,8 x 3 x 6,7 mm	16,8 x 3 x 6,7 mm	34 x 26,5 x 10 cm	34 x 26,5 x 10 cm	28,5 x 23 x 10 cm
Alternate current	-	-	100V-250V, 50/60Hz	100V-250V, 50/60Hz	100V-250V, 50/60Hz
Battery Type	AA battery/piles	Li-ion	Lithium	Lithium	Lithium
Rated Voltage	-	-	(V - Ah) 14.8V, 2.0Ah	(V - Ah) 14.8V, 2.0Ah	(V - Ah) 14.8V, 2.0Ah
Working Time	≥ 10 hours	≥ 16 hours	2 hrs	2 hrs	4 hrs
Charging Time	Auto shut off	Auto shut off	4 hrs max	4 hrs max	4 hrs
Built-in	-	-	•	•	•
Paper dimension	-	-	112mm x 90mm-150P	152mm thermal printer	112mm x 90mm-150P
Display	OLED	OLED	Colour touch LCD screen	Colour touch LCD screen	Colour LCD screen
Resolution	0,96"	0,96"	800*600	800*600	320*240
Available languages	-	-	ITA/ENG/FR/SPA/ PORT	ITA/ENG/FR/SPA/ PORT	ITA/ENG/FR/SPA/ PORT
Central station software	-	-	•	•	•
Password protection	-	-	-	-	•
USB OUTPUT	-	-	•	•	•
Time	-	-	Power-off data protection for 300 cases, 96 hours	Power-off data protection for 300 cases, 96 hours	Power-off data protection for 300 cases, 60 hours
FHR1 Probe	-	-		Qty 1	
TOCO Probe	-	-		Qty 1	
Event Marker	-	-		Qty 1	
Belt	-	-		Qty 2	
Ultrasound Gel	-	-		Qty 1	
Recording Paper	-	-		Qty 1	
T1.6AL Fuse	-	-		Qty 2	
Power Cord	-	-		Qty 1	
Ground Cable	-	-		Qty 1	