# **Laboratory Service PHYSICAL TEST REPORT**



Rue de Mons 3 - B-4000 Liège - Belgium Tel.: +32 4 224 71 40 - Fax: +32 4 224 25 90 Member of Schréder Group

Subject: VOLTANA-0 / 6 led's / Moons PU025H105AQ 0-10V driver


Sample n°: P-E16371, P-E16375

Test purpose: Thermal test @ 1050 mA following IEC/EN 60598-1 Standard

Remarks: <u>Test request n°</u>: P-D16541 <u>Folder n°</u>: P-F16041

## **TEST CONDITIONS:**

**Operator**: CLOSSET Frédérick



Load: 6 Led's

Driver: Moon's PU025H105AQ 0-10V Series

Tc: 90°C

Working temperature:  $-40 \sim +60^{\circ}$ C according

To datasheet.

#### **Measurement device:**

Yokogawa TX10: thermal measurement

Yokogawa WT 210: primary EM

Fluke 87: Led's EM

#### **Junction Temperature measurement method**

Junction temperature measurement by base temperature measurement and electrical measurement.  $T^{\circ}_{j} = T^{\circ}_{b} + R_{jb} \times P_{led}$ 

## **CONCLUSIONS:**

Ta (IEC): 55 °C limited by Driver Tq<sub>(IEC)</sub>: 35 °C limited by Driver

Tq given for 100 khrs of lifetime

T° given without wind effect to comply with IEC 62722-2-1

Duplicate to: Mr M. Thijs

LAB 06/10/2016

L. Maghe

//P-16CR541