

BCS-P-EIP26FSR3L3-Ai2

Index: **13063** GTIN13/EAN13: 5904890716872

URL: <https://bcs.pl/gb/6mpx/4680-bcs-p-eip26fsr3l3-ai2-5904890716872.html>



BCS-P-EIP26FSR3L3-Ai2

Product Details

Product	BCS-P-EIP26FSR3L3-Ai2
Brand	BCS POINT
NDAA	National Defense Authorization Act
Camera type	Dome
Resolution	6 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	3200(H)×1800(V)
Lens	fixed
Focal length	2.8 mm
Aperture	F1.4
Focus	fixed
Iris	fixed
Angle of view	H: 110.1° V: 59° D: 128.5°
DORI	Detect 63m / Observe 25.2m / Recognize 12.6m / Identify 6.3m
Min illumination	0.003Lux(F1.4,AGC) 0Lux(B/W,IR)
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	130dB
Backlight compensation	BLC / HLC / WDR(130dB)
Shutter	Auto / manual 1~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	2D/3D DNR
Roi	Region of Interest
Defog	Digital
Image rotate	Mirror, Flip 0°/90°(corridor mode)/180°/270°
Stream support	3
Resolutions	6M(3200×1800) / 4M(2560×1440) / 3M(2304×1296) / 2M(1920×1080) / 720P(1280×720) / D1(720×576) / (640×360) / 2CIF(704×288) / CIF(352×288)
Main stream	3200×1800@25fps 2560×1440@25fps 2304×1296@25fps 1920×1080@25fps 1280×720@25fps
Second stream	1280×720@25fps 720×576@25fps 640×360@25fps 704×288@25fps 352×288@25fps
Third stream	720×576@25fps 640×360@25fps 704×288@25fps 352×288@25fps
Bitrate	128Kbps~16Mbps
Video compression	H.265 / H.265+ / H.264 / MJPEG
Day/night	ICR
Illuminator type	IR LED + WhiteLight
IR range	30m
WhiteLight range	30m
NightColor	Yes
Microphone	Yes
Loudspeaker	Yes
Audio compression	G.711A / G.711U

Storage	NAS(NFS)
Memory card slot	microSD 512GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IGMP, SMTP, IPv6, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTSP, DNS, DDNS, NTP, UPnP, HTTP, 802.1x, SNMP, QoS, SSL/TLS, SSH, IPv4, RTP, RTCP, RTMP, HTTPS
Network security	Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 9.6W
Housing color	White
IP class	IP67
Surge protection	4kV
Working environment	-30°C~+60°C max 95% RH
Dimensions	Ø111×98mm
Weight	0.47kg
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Recognition of people entering the area and crossing the line reduces false alarms.
Ai - People counting	People counting for intrusion and crossline, counting people in/out
Ai - SMD - Smart Motion Detection	Intelligent Ultra Motion Detection with human/vehicle recognition

BCS-P-EIP26FSR3L3-Ai2

Accessories

BCS-P-A173



BCS-P-U112(2)



BCS-P-U113




BCS-ADU-B



BCS-ADU125



BCS-ADU170



BCS-L-AD23

