

Specificații de preț (F4.2)

[Acest tabel va fi completat de către ofertant în coloanele 5,6,7,8, iar de către autoritatea contractantă – în coloanele 1,2,3,4,9]

Numărul licitației: <i>ocds-b3wdp1-MD-1573721835372</i>	Data: <i>14 noiembrie 2019</i>	Alternativa nr.: _____
Denumirea licitației: <i>Echipament informatic și accesorii de birou</i>	Lot: <i>2</i>	Pagina: __ din __

Lotul 2. Sistem interactiv LCD inteligent

Nr	Cod CPV	Denumirea bunurilor și/sau a serviciilor	Unit. de măs.	Cantitatea	Preț unitar fără TVA	Preț unitar cu TVA	Suma fără TVA	Suma cu TVA	Termenul de livrare/prestare	Clasificație bugetară (IBAN)
	1	2	3	4	5	6	7	8	9	
1	30000000-9	Cerințe minime: Dimension: 65” Resolution: Full-HD (1920 x 1080 pixel) Active Screen Area (WxH):1428.5x803.5 mm; Response Time: max. 6.5 ms (grey to grey); Backlight: LED, edge lit; Max. Brightness: 350 cd/m2; Max. Display colors: 16.77 million colours; Contrast Ratio: 5,000 :1; Viewing Angle (H/V): 178°/178° (CR ≥ 10); Touchscreen: Touch: Technology IR (infrared blocking detection method); Power Supply Supplied from main unit; Multi Touch:10 points; Wireless Communication platform: - 2.4 Ghz, IEEE802.11b/g/n; - 5 Ghz, IEEE802.11a/n; - LAN x 1 (10Base-T/100Base-TX) - USB x 1 (USB 2.0); - Wireless adapter x 1 (USB 2.0)	Buc.	2	55,590.00	66,708.00	111,180.00	133,416.00	30 de zile după înregistrarea contractului la organele de resort	

	- power supply of wireless board should be from the monitor; - Possibility to connect minimum of 25 mobile devices; Collaboration platform: - Allows up to 10 devices—including Mac® or Windows computers, smartphones and tablets simultaneously without any cable hassles. - Possibility of display of one whole image or four, splitted 2 x 2; Protection Glass: - Thickness: max. 4.1 mm; - Shock resistance: 130 cm; Computer Input: Video: Analogue RGB (0.7 Vp-p) [75 Ω], HDMI, DisplayPort; Synchronization: Horizontal/vertical separation (TTL: positive/negative); Plug & Play: VESA DDC2B; Power Management: VESA DPMS; Input Terminals: PC analogue: - Mini D-sub 15-pin x 1, - HDMI x 4 (HDCP and 1080p compatible, PC / AV signal compatible), - DisplayPort (HDCP compatible, PC signal compatible) x 1, - 3.5 mm-diameter mini stereo jack x 1, - RS-232C D-sub 9-pin x 1; Output Terminals: - 3.5 mm-diameter mini stereo jack x 1; - USB Hub Function: 2xUSB 2.0 (type A); - Expansion Slot: 12 V, 2.4 A (power supplied when expanding the functions with an optional part); - Speaker Output: 10 W + 10 W; - Mounting: VESA (4 points), 400 x 400 mm, M6 screw; Power Supply: 100 V – 240 V AC, 50/60 Hz; Power Consumption: Max. 205 W;								
--	---	--	--	--	--	--	--	--	--

		- Environmental Conditions:5°C to 35°C; - Operating Humidity:20% to 80% RH (no condensation); Dimensions: - Display only (W x D x H): max.1,521 x 99 x 952 mm; - Weight: max. 57.5 kg; Main Accessories: - AC power cord, - Remote control unit with battery (AAA) x 2, - Set-up manual, - Blank sticker, - Cable clamp x 3, - USB cable, - Pen tray, - Pen tray-mounting screw x 2, - Touch pen, - Camera mount, - Camera mount screw x 2, - Camera screw, - CD-ROM, - Display Connect license; Supplied hardware and software (Windows) - Windows 7/8/10. - Intel Core Duo 2.8 Ghz or higher; - Memory: 2Gb or more; - HDD: 200 Mb or more free space; Convenient Expandability: - MFP Connectivity; - Webcam mount; - Built-in speaker; - 16-hour Daily Operation; Viewable files: - Microsoft Office (Excel®, Word, PowerPoint), PDF, JPEG/PNG/BMP/TIFF; - WMV/AVI/MP4/FLV. OS requirements (as of March 2017): Host: - Windows 7, Windows 8.1, Windows 10; Client: Windows 7, Windows 8.1, Windows 10, D75Mac							
--	--	--	--	--	--	--	--	--	--

		OS X v10.7, v10.8, v10.9, v10.10, v10.11, macOS v10.12, Android 2.3–7.1, iOS 6–10. Software requirments: - Software must allow the manipulation of a variety of different files on the screen without actually opening the respective applications. The viewable files listed above, will be displayed onscreen as “sheets”, which can be stored in onscreen virtual “drawers”. This software brings convenience and originality to business meetings, in-store installations, and more. Garanție:36 luni; Alte cerințe: Perioada de suport local și menținere de la producător: 1.Producătorul trebuie să ofere suport 24/24, prin e-mail sau conectare de la distanță, inclusiv suport local in limba romana din partea partenerului. 2.Ofertantul va prezenta autorizarea de la producător pentru produsul livrat; 3. Ofertantul va prezenta certificatul de conformitate cu standardele si cerințele UE. 3.Se va oferi manual de instalare si administrare a produsului ofertat in limba engleza. Lucrările de instalare, configurare, punerea în funcțiune a soluției trebuie să fie executate de Ofertant, iar costul acestora trebuie să fie incluse în ofertă.									
		Total lotul 2						111,180.00	133,416.00		

Nume: **Alexei Leu**

În calitate de: **Director**

[funcția oficială a persoanei ce semnează formularul ofertei]

Ofertantul: **SRL PRIDE SYSTEM**

Adresa: mun. Chișinău, Durlești, str. Hîrtoape, 26/A, ap. 16

Data: “29” noembrie 2019