

Electrodes

Two-Stem Electrodes with Stabilizers, for Working Elements 27040DB/EB

For use with 24/26 Fr. resectoscope sheaths

The cutting loops are delivered with a wire diameter of 0.35 mm. Loops with 30 or 40 as the last digit of the order number indicate a wire diameter of 0.30 mm or 0.40 mm.



27040GP1

Cutting Loops

Distal Tip	24/26 Fr. color code: yellow	Instrument Description
	27040GP1	Cutting Loop , bipolar
	27040GP140	Cutting Loop , bipolar
	27040GD1	Cutting Loop , bipolar, small
	27040BL1	Cutting Loop , bipolar, pointed

Cutting Loops

Distal Tip	24/26 Fr. color code: yellow/orange	Instrument Description
	27040GP130	Cutting Loop , bipolar, diameter 0.30 mm
	27040JB1	Cutting Loop , bipolar, longitudinal
	27040JB130	Cutting Loop , bipolar, longitudinal, diameter 0.30 mm
	27040JBE130	Cutting Loop , bipolar, rectangular, longitudinal, diameter 0.30 mm

VapoEnucleation Electrode

Distal Tip	24/26 Fr. color code: yellow	Instrument Description
	27040VE	VapoEnucleation Electrode , bipolar, hemispherical

High Frequency Surgery Units



UH 400 **AUTOCON® III 400 High-End**, with KARL STORZ-SCB control NEO, power supply 220-240 VAC, 50/60 Hz, including mains cord

UH 400U **AUTOCON® III 400 High-End**, with KARL STORZ-SCB control NEO, power supply 100-127 VAC, 50/60 Hz, including mains cord



UH 801 **Bipolar High Frequency Cord**, length 400 cm, for KARL STORZ AUTOCON® III 400 SCB, for use with KARL STORZ bipolar resectoscopes



UF 902 **Two-Pedal Footswitch**, with button for switchover function, for use with HF generators