

**Specificații tehnice**

Numărul procedurii de achiziție ocds-b3wdp1-MD-1730805918325 din 13.11.2024
Obiectul achiziției: _ piese de schimb pentru PC _

Denumirea bunurilor	Denumirea modelului bunurilor	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
<b>Bunuri</b>						
<b>Lotul 1 Piese de schimb pentru calculatoare</b>						
Mainboard for S1200	BS H510MHP 2.0	Taiwan	Biostar	Mainboard for S1200, min. 2xDDR4, VGA,DVI,HDMI,PCI-Ex.16x1, PCIEx1x1,4xSATA 6GB/s6, 6xUSB 2.0,2+4xUSB 3.0, 1xGbit LAN, Audio on board	BIOSTAR H510MHP 2.0, Socket 1200, Intel® H510 (11/10th Gen CPU), Dual 2xDDR4-3200, CPU Intel graphics, VGA, HDMI, 1xPCIe X16 4.0, 4xSATA3, 1xM.2, 2xPCIe X1, ALC897 HDA, 1xGbE LAN, 4xUSB3.2, mATX	
CPU for S1200 (compatibil cu MB S1200 poz.1.1)	i5-11400	SUA	Intel	CPU for S1200 (compatibil cu MB poz.1), Min 6-cores Processor, min 12 threads, Frecventa de baza min.	Intel® Core™ i5-11400, S1200, 2.6-4.4GHz (6C/12T), 12MB Cache, No Integrated GPU, 14nm 65W	

				2,3 GHz, min 12MB cache, max.14 nm, max 65W, Integrated UHD Graphics)	
2.5" SSD SATA min. 240 Gb	VI550S3-256-49351	China	Verbatim	2.5" SSD SATA min. 240 Gb <b>(NO Refurbished)</b>	2.5" SSD 256GB Verbatim VI550 S3, SATAIII, Sequential Reads: 550 MB/s, Sequential Writes: 460 MB/s, Maximum Random 4k: Read: 65,000 IOPS / Write: 85,000 IOPS, Thickness-7mm, Controller Phison PS3111, 3D NAND TLC  <b>(NO Refurbished)</b>
2.5" SSD SATA min. 500 Gb	VI550S3-512-49352	China	Verbatim	2.5" SSD SATA min. 500 Gb <b>(NO Refurbished)</b>	2.5" SSD 512GB Verbatim VI550 S3, SATAIII, Sequential Reads: 520 MB/s, Sequential Writes: 500 MB/s, Maximum Random 4k: Read: 75,000 IOPS / Write: 86,000 IOPS, Thickness-7mm, Controller Phison PS3111, 3D NAND TLC  <b>(NO Refurbished)</b>
2.5" External HDD 2TB	SP020TBPHD66SS3B	Taiwan	Silicon Power	2.5" External HDD 2TB (USB3.0) Mobile", Anti-Shock case <b>(NO Refurbished)</b>	2.5" External HDD 2TB (USB3.0) Mobile", Anti-Shock case <b>(NO Refurbished)</b>
DIMM DDR 3, 1600 MHz, 8 Gb	PSD38G16002	Taiwan	Patriot	DIMM DDR 3, 1600 MHz, 8 Gb	8GB DDR3-1600 PATRIOT Signature Line, PC12800, CL11, 2Rank, Double-sided Module, 1.5V
DIMM DDR 4, 2400 MHz, 8 Gb	PSD48G266681	Taiwan	Patriot	DIMM DDR 4, 2400 MHz, 8 Gb	8GB DDR4-2666 PATRIOT Signature Line, PC21300, CL19, 1Rank, Single

					Sided Module, 1.2V	
DIMM DDR 4, 3200 MHz, 16 Gb	PSD416G32002	Taiwan	Patriot	DIMM DDR 4, 3200 MHz, 16 Gb	16GB DDR4-3200 PATRIOT Signature Line, PC25600, CL22, 2Rank, Double Sided Module, 1.2V	
64GB USB Flash Drive	DTKN/64GB	SUA	Kingston	64GB USB Flash Drive, Black/Silver, USB3.0, Metal	64GB USB3.2 Kingston DataTraveler Kyson Silver, Metal casing, Compact and lightweight (Read 200 MByte/s)	
32GB USB Flash Drive	DTKN/64GB	SUA	Kingston	32GB USB Flash Drive, Black/Silver, USB3.0, Metal	64GB USB3.2 Kingston DataTraveler Kyson Silver, Metal casing, Compact and lightweight (Read 200 MByte/s)	
Power Supply ATX 600W	ATX-750W	China	HPC	Power Supply ATX 600W, 1x20+4PIN, 1x4PIN, 3xSATA, 3xMolex, 220V, 1.2m power cord	PSU HPC ATX-750W, Active PFC, 12cm Black fan, Black flat output cables, 24 pin, 2x 8pin(4+4), 2x PCI-E 8pin(6+2), 6x SATA, 4x IDE, 1.2m EU-plug cable, Black	
Cooler Socket	XPCPU.M403 PRO	Taiwan	Xilence	Cooler Socket 775/1150/1151/1155/1156/FM1/FM2 / FM2+/AM2 / AM2+/AM3 / AM3+/AM4 up to min. 120W, 4-pin (max. 30db, 1600rpm, min. 38CFM)	XILENCE Cooler XC029 "M403PRO", Performance C Series, Intel Socket LGA1700/1200/1156/1155/1151/1150 & AMD AM5/AM4/AM3/FM2, up to 150W, 120ø120ø25mm Red Fan, Hydro-bearing fan, 500~1800rpm, 14.2~25.6dBA, 61.5CFM, 4pin, PWM, 3x Cooper heatpipes	
Battery 12V/7AH	GMB BAT-12V7AH	Olanda	Gembird	Battery 12V/7AH, 3-5 Years Life Time, Dimensions 150*100*65 mm	Nominal voltage: 12 V Dimensions: 151 x 65 x 93 mm Height (incl. terminal): 99 mm Terminal: F2 Weight:	

					2.06 kg	
Battery CR 2032 (BIOS MB)	GMB EG-BA-CR2032-01	Olanda	Gembird	Battery CR 2032 (BIOS MB), 3V, Lithium	Gembird Button cell CR2032, 2pcs, High performance and long lifetime	
Gigabit Ethernet Adapter USB 3.0	GMB NIC-U3-02	Olanda	Gembird	Gigabit Ethernet Adapter USB 3.0	Gembird NIC-U3-02, USB3.0 Gigabit LAN adapter, USB3.0 to RJ-45 LAN connector	
Gigabit Ethernet Adapter 3.1\3.0 Type-C	GMB A-CMU3-LAN-01	Olanda	Gembird	Gigabit Ethernet Adapter 3.1\3.0Type-C	Gembird A-CMU3-LAN-01, USB C-type Gigabit network adapter with 3-port USB 3.1 hub	
USB 2.0/ Wi-Fi Adapter	Archer T2U Plus	China	TP-link	USB 2.0/ Wi-Fi Adapter min. 150 Mbit/s	TP-LINK Archer T2U Plus AC600 Wireless Dual Band USB Adapter, 433Mbps on 5GHz + 150Mbps on 2.4GHz, 802.11a/b/g/n/ac, High Gain, 1 fixed Antenna	
Wireless Combo Tastieră + mouse set	SV KB-C3200W	Finlanda	Sven	Wireless Combo Tastieră + mouse set	SVEN KB-C3200W, Wireless, Multimedia Keyboard & Mouse, 2.4GHz, (115 keys, 11 Fn-keys) + Mouse (3 + 1 (scroll wheel), 800/1200/1600 dpi), Nano receiver, USB, Black, Rus/Ukr/Eng	
Adapter DP-VGA-A-ADPM-VGAF-01	GMB A-DPM-VGAF-01	Olanda	Gembird	Adapter DP-VGA-A-ADPM-VGAF-01, Display Port to VGA adapter, Converts digital DisplayPort input into VGA output (DB15 female)	Adapter DP-VGA - Gembird A-DPM-VGAF-01, DisplayPort to VGA adapter, Converts digital DisplayPort input into analog VGA output (DB15 female)	
Adapter HDMI-VGA-A-	GMB AB-HDMI-	Olanda	Gembird	Adapter HDMI-VGA-A-HDMI-	Adapter HDMI-VGA - Gembird AB-HDMI-VGA-001, HDMI to VGA	

HDMI-VGA-001	VGA-001			VGA-001, HDMI top VGA adapter, Converts digital HDMI input 19pin male, v 1.4) into analog VGA output (DB15 female)	adapter, Converts digital HDMI input (19 pin male, v.1.4) into analog VGA output (DB15 female), Blister
Adapter DP-HDMI	GMB AB-DPM-HDMIF-002	Olanda	Gembird	Adapter DP-HDMI, Display Port (male) to HDMI (female)	Adapter DP-HDMI - Gembird AB-DPM-HDMIF-002, DisplayPort male to HDMI femaile adapter cable, blister, Black
Splitter HDMI 3 ports – DSP-4PH4-02	GMB DSP-4PH4-02	Olanda	Gembird	Splitter HDMI 3 ports – DSP-4PH4-02, HDMI splitter, 4 ports, 1 input ports, 4 output HDMI receptacles, 19pin (A), HDMI+HDCP v1.4 (compatible with all HDMI versions)	Splitter HDMI 4 ports - Cablexpert - DSP-4PH4-02, HDMI splitter, 4 ports, 1 input, 4 output HDMI receptacles, 19 pin (A), HDMI + HDCP v.1.4 (compatible with all HDMI versions)
Cable HDMI - HDMI, 1.8 m, HDMI v.1.4	GMB CC-HDMIL-1.8M	Olanda	Gembird	Cable HDMI - HDMI, 1.8 m, HDMI v.1.4, male-male, Black cable with gold-plated connectors, Bulk packing (PC-Monitor)	Cable HDMI CC-HDMIL-1.8M, 1.8 m, High speed HDMI cable with Ethernet "Select Series", Supports 4K UHD resolutions at 60 Hz, 1.8 m
Cable HDMI -HDMI, 10 m, HDMI v.2.0	GMB CCBP-HDMI-AOC-10M-02	Olanda	Gembird	Cable HDMI -HDMI, 10 m, HDMI v.2.0, male-male, Black cable with gold-plated connectors, (PC-Monitor)	Cable HDMI CCBP-HDMI-AOC-10M-02, Active Optical (AOC) High speed HDMI cable with Ethernet "AOC Premium Series", Supports 4K UHD resolutions at 60Hz, male-male,10 m
Cable USB 2.0 – 3,0m	GMB CCF-USB2-AMBM-10	Olanda	Gembird	Cable USB2.0 – 3,0m - CCF-USB2-AMBM-6, Premium quality, A-plug B-plug (PC - Imprimanta)	Cable USB2.0 - 3m - Cablexpert CCF-USB2-AMBM-10, Premium quality, 3 m, USB 2.0 A-plug B-plug, with Ferrite core, Black

Cablu/mufă SATA Power	GMB CC-SATA-PSY	Olanda	Gembird	Cablu/mufă SATA Power CC-SATA-PSY, min. 15cm, 2 SATA Power	SATA Power Cable - 0.15m - Cablexpert CC-SATA-PSY, 150mm, 2 SATA Power	
Cablu/mufă SATA DATA	GMB CC-SATAM-DATA90	Olanda	Gembird	Cablu/mufă SATA DATA min 30 cm	SATA Data Cable - 0.5m - Cablexpert CC-SATAM-DATA90, Serial ATA III 50cm data cable with 90 degree bent connector, bulk packing, metal clips with 90 degree bent connector	
<b>TOTAL</b>						

Semnat: \_\_\_\_\_ Numele, Prenumele: Oleg Savcenco În calitate de: Director

Ofertantul: Accent Electronic SA Adresa: str. Bulgara 33/1