

PRODUCT DATASHEET

ECO CLASS AREA SPD 30 W 4000 K GR

ECO CLASS AREALIGHTING | LED outdoor luminaires



AREAS OF APPLICATION

- Road lighting
- Car parks

PRODUCT BENEFITS

- Energy savings thanks to high system efficacy: up to 120 lm/W
- Low maintenance and operation costs due to long lifetime of LED
- 5 years guarantee

PRODUCT FEATURES

- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Lifetime (L70/B50): up to 50,000 h
- Type of protection: IP66
- Impact resistance: IK08
- Operating temperature range at t_a : -35...50 °C
- Robust die-cast aluminum housing



TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W
Operating mode	Mains voltage
Nominal voltage	100...240 V
Mains frequency	50/60 Hz
Power factor λ	>0.90

Luminaire control gear data

Max. no. of lum. on circuit break. B16 A	16
Max. no. of lum. on circuit break. C10 A	15
Max. no. of lum. on circuit break. C16 A	24

Photometrical data

Color temperature	4000 K
Color rendering index Ra	>80
Luminous flux	3600 lm
Luminous efficacy	120 lm/W
Standard deviation of color matching	≤ 5 sdc _m

Light technical data

Beam angle	135 ° x 75 °
------------	--------------

Dimensions & weight

Length	325.0 mm
Width	121.0 mm
Height	64.0 mm
Product weight	855.00 g

Colors & materials

Housing color	Gray
Product color	Gray
Body material	Aluminum
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-30...50 °C
---------------------------	-------------

Lifespan

Lifespan L70 at 25 °C	
-----------------------	--



Additional product data

Mounting type	Suspended
Mounting location	Pole

Capabilities

Dimmable	No
Type of connection	Cable, 3-pole
LED module replaceable	Not replaceable

Certificates & standards

Type of protection	IP66
Protection class	I
Protection class IK (shock resistance)	IK08
Standards	CE/ROHS/REACH

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075269378	Folding carton box 1	366 mm x 94 mm x 168 mm	1058.00 g	5.78 dm ³
4058075269385	Shipping carton box 10	495 mm x 380 mm x 355 mm	11778.00 g	66.78 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



ECO CLASS
AREALIGHTING

GREY ALUMINUM
HOUSING*

 **LEDVANCE**

30 W / 3600 lm / 4000 K

120
lm/W

Ra
>80

IK
08

SPD
10 kV

V _{AC} · Hz	100-240 V · 50/60 Hz
W · lm	30 W LED · 3600 lm
	135° x 75°
t[h]	50.000 hrs@L70
 [°C]	-30° ...+50°
l x w x h	325 x 121 x 64 mm
	855 g
Model	ECO CLASS AREA SPD 840 30W 3600LM GR
	-


www.ledvance.com

For outdoor use
Made in China



G11073835

AC150420055



4 058075 269378

BLACK Orange Pantone 021C
score dimension 70 x 99 mm



100

95

75

25

5

0