

Declaration of Conformity (DoC)

We, **Shenzhen DOKE Electronic Co., Ltd**

801, Building 3, 7th Industrial Zone, Yulu Community, Yutang Road, Guangming District, Shenzhen, China.

Declare that the DoC issued under our sole responsibility and belongs to the following product(s):

Product Type: smartphone
Trademark: BLACKVIEW / OSCAL
Model Number(s): XPLORE 1, TANK 1

(Name of product, type or model, batch or serial number)

System components:

LDS Antenna 1: BT/Wi-Fi 2.4G: -1.2dBi; WiFi 5G: 1.2dBi; Antenna 2: Wi-Fi 2.4G: -0.6dBi; WiFi 5G: 1.24dBi;

GSM 900: -0.44 dBi / DCS 1800: 2.67dBi

WCDMA: Band I: 0.92dBi ; Band VIII: -0.44dBi;

LTE: Band 1: 0.92dBi; Band 3: 2.67dBi; Band 7: 1.91dBi;
Band 8: -0.44dBi; Band 20: -4.95dBi; Band 28: -4.07dBi;

NR: NR FDD n1: 0.8dBi, NR FDD n3: -1.0dBi, NR FDD n8: -2.6dBi, NR FDD n20: -3.4 dBi, NR FDD n28: -4.2 dBi,
NR TDD n40: -4.38dBi, NR TDD n77: -0.69dBi, NR TDD n78: -0.69dBi

Adapter 1:

Model: QZ-06502EC00

Input: 100-240V~50/60Hz 1.5A

Output USB-C: 5.0V $\overline{\text{---}}$ 3.0A OR 9.0V $\overline{\text{---}}$ 3.0A

OR 12.0V $\overline{\text{---}}$ 3.0A OR 15.0V $\overline{\text{---}}$ 3.0A

OR 20.0V $\overline{\text{---}}$ 3.25A

(PPS) 3.3V-21.0V $\overline{\text{---}}$ 3.15A 66.0W MAX

Manufacturer: Guangdong Quanzhi Technology Co., Ltd.

Adapter 2:

Model: HJ-PD55W-EU

Input: 100-240V~50/60Hz 1.5A

Output: 5.0V $\overline{\text{---}}$ 2.0A 10.0W

Output (PD): 5.0V $\overline{\text{---}}$ 3.0A 15.0W

9-20V $\overline{\text{---}}$ 3-2.75A 55.0W MAX

Manufacturer: Shenzhen Huajin Electronics Co., Ltd.



Rechargeable Li-ion Battery:

Model:Li536587HTT;Specification:DC 7.7V, 10000mAh, 77Wh;
Manufacturer:ShenzhenHuatiantongTechnologyCo.,Ltd.

The object of the declaration described above is in conformity with the essential requirements of the relevant Union harmonization legislation: Radio Equipment Directive RED(2014/53/EU).

The following harmonized standards and technical specifications have been applied:

HEALTH & SAFETY(Art. 3(1)(a)):

EN 50360:2017;
EN 50360:2017/A1:2023
EN 50566:2017;
EN 50566:2017/A1:2023
EN IEC/IEEE 62209-1528:2021
EN 62479:2010
EN IEC 62368-1:2020+A11:2020

EMC(Art. 3(1)(b)):

ETSI EN301489-1V2.2.3(2019-11)
ETSI EN301489-3V2.3.2(2023-01)
ETSI EN301489-17V3.2.4(2020-09)
ETSI EN301489-19V2.2.1(2022-09)
ETSI EN301489-52V1.2.1(2021-11)

EN 55032:2015+A1:2020

EN 55035:2017+A11:2020

EN IEC 61000-3-2:2019+A1:2021

EN 61000-3-3:2013+A2:2021

Radio Spectrum(Article 3.2):

EN 301511V12.5.1(2017-03);

EN 301908-1V15.2.1(2023-01)

EN 301908-2V13.1.1(2020-06)

EN 301908-13V13.2.1(2022-02);
EN 301 908-25 V15.1.1 (2024-10)

EN 300328V2.2.2(2019-07);

EN 301893V2.1.1(2017-05);

EN 300440V2.2.1(2018-07);

EN 303413V1.2.1(2021-04);

EN 303345-1V1.1.1(2019-06);

EN 303345-3V1.1.1(2021-06);

EN 300330 V2.1.1(2017-02)

NOTIFIED BODY:

Name:DERYCOM CERTIFICATION SERVICES, INC.

Address:1100 Falcon Avenue Glencoe, Mn 55336

Identification Number:3052

EU-type examination certificate number:JEC-20

RF Specification:

Function	Operation Frequency	Max RF output power:
BLE 1M	2402MHz~2480MHz	0.85 dBm
BLE 2M	2404MHz~2478MHz	0.92 dBm
BT(BR+EDR)	2402MHz~2480MHz	5.64 dBm
WiFi 802.11b/g/n/ax(HT20/40)	802.11b/g/n/ax(20MHz): 2412~2472MHz; 802.11n/ax(40MHz):2422~2462MHz	14.38dBm
Wi-Fi 5.2G(802.11a/n20/n40/ac20/ ac40/ac80/ax20/ax40/ax80)	802.11a/ n20/ac&ax 20:5180MHz~5240MHz 802.11 n40/ac&ax 40:5190MHz~5230MHz 802.11 ac&ax 80:5210MHz	13.18 dBm
Wi-Fi 5.8G(802.11a/n20/n40/ac20/ ac40/ac80/ax20/ax40/ax80)	802.11a/ n20/ac&ax 20:5745MHz~5825MHz 802.11 n40/ac&ax 40:5755MHz~5795MHz 802.11 ac&ax 80:57750MHz	13.63 dBm
GSM/GPRS/EGPRS 900	TX(Uplink):880M - 915MHZ; RX(Downlink):925M - 960MHZ	31.96 dBm
GSM/GPRS/EGPRS 1800	TX(Uplink):1710M - 1785MHZ; RX(Downlink):1805M - 1880MHZ	28.73 dBm
WCDMA B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	23.6 dBm
WCDMA B8	TX(Uplink): 880-915MHz; RX(Downlink):925-960MHz	22.74 dBm
LTE FDD B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	23.00dBm
LTE FDD B3	TX(Uplink) :1710-1785MHz; RX(Downlink):1805-1880MHz	23.28 dBm
LTE FDD B7	TX(Uplink) :2500-2570MHz; RX(Downlink):2620-2690MHz	22.6 dBm
LTE FDD B8	TX(Uplink): 880MHz to 915 MHz RX(Downlink): 925 MHz to 960 MHz	24.31 dBm
LTE FDD B20	TX(Uplink): 832MHz~862MHz; RX(Downlink):791MHz~821MHz	24.38 dBm
LTE FDD B28	TX(Uplink): 703 MHz to 736MHz RX(Downlink): 758 MHz to 791 MHz	24.16 dBm
NR FDD n1:	Uplink: 1920 MHz to 1980MHz Downlink: 2110 MHz to 2170 MHz	23.62 dBm
NR FDD n3:	Uplink: 1710 MHz to 1785 MHz Downlink: 1805 MHz to 1880 MHz	24.2 dBm
NR FDD n8:	Uplink: 880 MHz to 915 MHz Downlink: 925 MHz to 960 MHz	23.79 dBm
NR FDD n20:	Uplink: 832 MHz to 862 MHz Downlink: 791 MHz to 821 MHz	23.85 dBm
NR FDD n28:	Uplink: 703 MHz to 748 MHz Downlink: 758 MHz to 803 MHz	23.81 dBm
NR TDD n40:	Uplink & Downlink: 2300 MHz to 2400 MHz	24.05 dBm
NR TDD n77:	Uplink & Downlink: 3300 MHz to 4200 MHz	25.52 dBm
NR TDD n78	Uplink & Downlink: 3300 MHz to 3800 MHz	25.09 dBm
NFC	13.56MHz	-2.89dBuA/m@10m
FM	Rx(Downlink): 87.5MHz~108MHz	--
GPS	Rx(Downlink): 1.57542GHz&1.17645GHz	--

Tests for SAR are conducted using standard operating positions with the device transmitting at its highest certified power level in all tested frequency bands. The maximum SAR values tested on this device when used in its normal position at the ear and when used close to the body (at a minimum distance of 5mm/0mm) are:

Max SAR Value(W/kg)	10-gHead	0.353
Limitis 2.0(W/kg) for10-g	10-gBody	0.702
Limitis 4.0(W/kg) for10-g	10-gMemberDAS	2.318

Technical file held by: Shenzhen DOKE Electronic Co., Ltd
801, Building 3, 7th Industrial Zone, Yulu Community, Yutang Road, Guangming District, Shenzhen, China.

Signed for and on behalf of: Shenzhen DOKE Electronic Co., Ltd

Name and Title: zhang.liuwei/Manager

Address: 801, Building 3, 7th Industrial Zone, Yulu Community, Yutang Road, Guangming District, Shenzhen, China.

zhang.liuwei

SignatureofAuthorizedPerson

2025-07-29