

**213.3237****PLUG**

32A 3P+N+E 6h 346-415V 60Hz 50Hz  
Screw terminals



EN 60309-1 (1999)  
EN 60309-2 (1999)  
EN 60309-1/A1 (2007)  
EN 60309-1/A2 (2012)  
EN 60309-2/A1 (2007)  
EN 60309-2/A2 (2012)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA Series

Synthetical description

PLUG

Mounting version

PORTABLE

#### ■ TECHNICAL CHARACTERISTICS

|                   |                 |
|-------------------|-----------------|
| Rated current     | 32A             |
| Poles             | 3P+N+E          |
| Hour position     | 6h              |
| Rated voltage     | 346-415V        |
| Working frequency | 60Hz            |
|                   | 50Hz            |
| Terminals         | Screw terminals |

#### ■ PHYSICAL CHARACTERISTICS

|                            |               |
|----------------------------|---------------|
| Mounting version           | PORTABLE      |
| Colour                     | RED           |
| Material                   | THERMOPLASTIC |
| Protection degree          | Splash proof  |
| Protection degree IP       | IP44/IP54     |
| Protection degree IK       | IK08          |
| Types of available outlets | STRAIGHT      |
| Contact material           | CuZn (brass)  |
| Surface treatment contacts | Nickel-plated |
| Cable entry                | CABLE GLAND   |

#### ■ DOWNLOAD

Technical drawing [PDF]  
Technical drawing [DWG]  
Technical drawing [STP]

#### ■ OPTIONS & VARIOUS NOTES

Catalogue notes

Version also available in black; just add ".K" at the end of the catalogue number.