

# COMMUNICATION



**106R-000734**

issued by : Ministry of Transport  
L.Svobody 1222/12  
110 15 Praha 1  
Czech Republic

concerning: <sup>1/</sup>


~~APPROVAL GRANTED~~  
**APPROVAL EXTENDED**  
~~APPROVAL REFUSED~~  
~~APPROVAL WITHDRAWN~~  
~~PRODUCTION DEFINITELY DISCONTINUED~~

**of a type of pneumatic tyre for agricultural vehicles pursuant to Regulation No. 106**

Approval No.: **106R-000734**

Extension No. : **III.**

1. Manufacturer's name or trade mark (s) of the tyre: **PETLAS / STARMAXX / HARVESTER / MILESTONE**
2. Tyre type designation by the manufacturer: **IND25 / SM-125 / HR-15 / ML-15**
3. Manufacturer's name and address: **PETLAS TIRE INDUSTRY AND TRADE COMPANY  
Kindam Mah.  
Ankara-Kayseri Cad. No. 2/1  
Kirsehir  
TURKEY**
4. If applicable, name and address of manufacturer's representative: **N/A**
5. Summarized description:
  - 5.1. Size of tyre: **see tyre dimensions list**
  - 5.2. Category of use: **Construction applications (IND)**
  - 5.3. Structure: **diagonal (bias-ply)/bias-belted/radial <sup>1/</sup>**
  - 5.4. Speed category symbol: **see tyre dimensions list**
  - 5.5. Load-capacity index: **see tyre dimensions list**
    - 5.5.1. for traction (implement only):
    - 5.5.2. for trailer (implement only):



5.6. Whether the tyre is to be fitted with or without an inner tube ~~TUBE TYPE~~ / TUBELESS

5.7. The supplementary service description, if applicable: -

6. Technical Service and, where applicable,  
test laboratory approved for purposes  
of approval or of verification of conformity:

**IGTT a.s.**  
**Šternberská 446, Louky,**  
**763 02 ZLÍN**  
**CZECH REPUBLIC**

7. Date of report issued by that service: -


8. Number of report issued by that service: -

9. Reason(s) of extension (if applicable): **New size added**

10. Any remarks: -

11. Place: **Praha**

12. Date: **03. 10. 2018**



13. Signature: **Marek Brázdá**

14. Annexed to this communication is a list of documents in the approval file deposited at the Administrative Services having delivered the approval and which can be obtained upon request

List of attached documents

- Application for approval

---

<sup>1/</sup> Strike out what does not apply.



Annex No.1

Tyre dimensions list from the same range

12.5/80-18 12PR TL 142 A8 L2
12.5/80-18 14PR TL 146 A8 L2
340/80-18 12PR TL 142 A8 L2
16.0/70-20 14PR TL 154 A8
16.0/70-20 16PR TL 156 A8
16.0/70-24 14PR TL 152B
<b>405/70-20 14PR TL 154 A8</b>
405/70-24 14PR TL 152B
19.5 L-24 12PR TL 151 A8
440/80-24 12PR TL 149 A8 L2
16.9-24 12PR TL 149 A8 L2
16.9-24 14PR TL 152 A8 L2
16.5/85-24 12PR TL 149 A8
16.5/85-24 16PR TL 156 A8
16.9-28 12PR TL 152 A8 L2
16.9-28 12PR TL 152 A8 L2
16.9-28 14PR TL 156 A8 L2
440/80-28 12PR TL 152 A8 L2
480/80-26 14PR TL 158 A8 L2
18.4-26 12PR TL 156 A8 L2
18.4-26 14PR TL 158 A8 L2
18.4-26 16PR TL 160 A8 L2
14.5-20 14PR TL 143 D



APPLICATION FOR APPROVAL REGARDING ECE R106

1. Manufacturer's name or trade mark(s) on the tyre type : PETLAS/STARMAXX/HARVESTER/MILESTONE
2. Tread pattern designation by the manufacturer : IND-25 / SM-I25 / HR-15 / ML-15
3. Manufacturer's name and address : PETLAS TYRE INDUSTRY AND TRADE COMPANY.  
Kindam Mah.  
Ankara-Kayseri Cad. No.2/1  
Kirsehir TURKEY
4. Summarised description for worst case tyre
  - 4.1. Size : 14.5-20 (14.5/75-20) IND 14PR TL 143 D
  - 4.2. Category of use : Construction applications (IND)
  - 4.3. Structure : Diagonal (Bias-Ply)
  - 4.4. Speed Category symbol : D
  - 4.5. The load – capacity index : 143
  - 4.6. Tube or Tubeless type : TUBELESS
  - 4.7. Cold inflation pressure(psi) : 51
  - 4.8. Inflation Pressure(psi) : 51
  - 4.9. Water Burst Test Pressure (kpa) : 878
  - 4.10. Load/Speed Test Pressure(kpa) : 352



## APPLICATION FOR APPROVAL REGARDING ECE R106

5. WORST CASE REPRESENTATIVE TYRES:5.1. WATER BURST AND LOAD SPEED TEST:

<b>WATER BURST AND LOAD/SPEED TEST REPRESENTATIVE TYRE</b>		
<b>SIZE</b>	<b>LOAD / SPEED INDEX</b>	<b>REASON TO BE WORST CASE</b>
14.5-20 (14.5/75-20) 14PR TL	143 D	<b>SPEED CATEGORY</b>

6. LIST OF SIZES COVERED BY REPRESENTATIVE TYRES:

12.5/80-18 12PR TL 142 A8 L2
12.5/80-18 14PR TL 146 A8 L2
340/80-18 12PR TL 142 A8 L2
16.0/70-20 14PR TL 154 A8
16.0/70-20 16PR TL 156 A8
16.0/70-24 14PR TL 152B
<b>405/70-20 14PR TL 154 A8</b>
405/70-24 14PR TL 152B
19.5 L-24 12PR TL 151 A8
440/80-24 12PR TL 149 A8 L2
16.9-24 12PR TL 149 A8 L2
16.9-24 14PR TL 152 A8 L2
16.5/85-24 12PR TL 149 A8
16.5/85-24 16PR TL 156 A8
16.9-28 12PR 152 A8 L2
16.9-28 12PR TL 152 A8 L2
16.9-28 14PR TL 156 A8 L2
440/80-28 12PR TL 152 A8 L2
480/80-26 14PR TL 158 A8 L2
18.4-26 12PR TL 156 A8 L2
18.4-26 14PR TL 158 A8 L2
18.4-26 16PR TL 160 A8 L2
14.5-20 14PR TL 143 D

*lsh*