

## Technical Data Sheet

[www.soletex.com](http://www.soletex.com)

<b>Article- No</b>	KW 064 - FAVORITE	
<b>Application</b>	Flag / Beach Flag	
<b>Printable Ink</b>	Treatment applied for Sub Paper , Direct Sub.	
<b>Material</b>	100% Polyester (Recycled version is available on demand)	 *Optional
<b>Standart Sizes</b>	270 cm, 320 cm (106",126") x 100mt. (109 yrd.)	
<b>Weight</b>	110 ( g/m2 )+- 5(gr) (3,8 oz)	
<b>Tensile Strength</b>	27/95 warp/weft (daN)	DIN EN ISO 13934-1
<b>Tear Resistance</b>	8/13 warp/weft (N)	DIN EN ISO 13937-1
<b>Finishing</b>	Digital Coating	

**Packaging** 3" paper core, wrapped with stretch film + put in a cardboard box or tubes

Our product enables to have vivid colors and good printing quality with SUBLIMATION inks.  
(Test printing is suggested before the printing job.)

								
Ink Type	Sub Direct and Paper Transfer	Fire Retardant	Cutting	Cold Cut				

All above released specifications and informations are for guidance purposes only. Our policy of continuous improvement may result in changes , we therefore reserve the right to alter the specifications and the informations at anytime without notice.