

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/201



Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Compressive strength	R3	System 2+	EN 1504-3:2005
Chloride ion content 1)	≤ 0,05 %	System 2+	
Adhesive bond	≥ 1,5 MPa	System 2+	
Restrained shrinkage/expansion 2)	≥ 1,5 MPa	System 2+	
Carbonation resistance 1)3)	NPD	System 2+	
Elastic modulus	≥ 20 GPa	System 2+	
Thermal compatibility	NPD	System 2+	
Skid Resistance	NPD	System 2+	
Coefficient of thermal expansion 4)	NPD	System 2+	
Capillary absorption	NPD	System 2+	
Reaction to fire 5)	Е	System 3	
Dangerous substances	NPD	System 2+	

- 1) Only relevant for repair of reinforced concrete.
- 2) Not required if thermal cycling is undertaken.
- 3) Not required if the repair product includes a surface protection system with proven protection against carbonation (EN 1504-2) or is a PC mortar.
- 4) Relevant to PC only.
- 5) Also possible A1, A2, B, C and D, whereby the last four classes in Germany for the time being need an approval from DIBt. The possible class F is not admitted in Germany. This class means in Germany "readily flammable". In other European MS this class means "no performance determined" (NPD)" and is admitted with consideration of the valid regulation in the respective MS.

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Daniel Schempershofe, head of quality control and product development

D. Schempershafe

Essen, 01.07.2013