



## LK-F43L Woodpecker UDS-N3 LED Ultrasonic Scaler

- Product Item: LK-F43L
- Category : Ultrasonic Scaler
- Woodpecker Brand
- UDS-N3 LED
- Scaling, Perio, Endo Function
- Golden Tips
- Product description : LK-F43L

Woodpecker UDS-N3 LED Ultrasonic Scaler, built in for dental chair

## LK-F43L Woodpecker UDS-N3 LED Ultrasonic Scaler

### Specification:

Detachable handpiece with light, autoclavable.  
Automatic frequency tracking.

Scaling, endo, function

Accurate feedback control and constant power output, ensure a more comfortable feeling to patients

Detachable handpiece: HW-3L

Main unit input	24V~ 50Hz/60Hz 1.3A
Output power	3W ~ 20W
Frequency	28kHz $\pm$ 3kHz
Water pressure	0.1bar ~ 5bar(0.01MPa ~ 0.5MPa)
Main unit weight	0.2kg
Dimensions	74mm×56mm×38mm

Golden Tips: E1T G1T\*2, G2T, G4T, P1T

宁波蓝野医疗器械有限公司  
NINGBO RUNYES MEDICAL INSTRUMENT CO., LTD.

徐步光

## J111 Stool

### Standard Features:

- Stool: Double Lever Adjustment
- Back: Oval Back
- Seat: Contoured
- Cylinder: Short Base: Beige Powder Coated Metal
- Casters: Beige Carpet
- Cushioning: Standard Foam
- Upholstery: Standard Vinyl

### Benefits:

- Full tilt adjustment allows user to sit comfortably while working.
- Oval Backrest allows better torso maneuverability.
- Contoured, deep seat is perfect for medium to tall users.
- Superior cushioning creates unparalleled comfort.
- Carpet or hard floor casters glide easily in any environment.
- Five-leg powder coated aluminum base provides improved stability.
- Choice of different height lift mechanisms provides a wide range of adjustment.

### Specifications:

- Max load: 150kg
- Stool Base Diameter: 23"
- Floor - Seat Height: 17.5" - 22.5"
- Back: Width 15" x Height 12"
- Seat Measurements: Width 18.5" x Depth 16.5"



宁波蓝野医疗器械有限公司  
NINGBO RUNYES MEDICAL INSTRUMENT CO., LTD.

徐步光



## Description

### 3-Ways Syringe with Two Autoclavable Tips

Waldent 3-way syringe has 2 nozzles in a box controlled by 2 buttons. The left button controls the water flow volume, and the right button controls the airflow volume. Pushing both buttons at the same time generates a mist.

Waldent 3-Ways syringe features an O-ring groove that secures the tip-lock for patient safety and eliminates leakage.

The angle in the tip provides an ideal placement of the tip anywhere in a patient's mouth and is strong enough

to allow for retraction.

### Waldent 3-Way Syringe Is Made Of:

- The box and housing are made of premium Quality Stainless Steel
- The handle is made of High-Quality aluminum with smooth styling that fits comfortably in your hand
- The package includes 2 Autoclavable tips
- Tips are constructed of solid alloy

### INDICATION:

- Waldent 3-way syringe supplies a focused stream of compressed air, water, or a combination of both
- Frequently used to clean a tooth or surface during dental treatment

### Key Specifications:-

- 6-Holes in the tip head for wider coverage
- Tip Size & Weight:  $\varnothing 4 \times 85\text{mm}$ , 6g
- Syringe Size & Weight:  $31 \times 118 \times 20\text{mm}$ , 123g
- Autoclavable Tip (within  $135^{\circ}\text{C}$ )
- 3 Way Syringe - With Two Autoclavable Tips

### TECHNICAL SPECIFICATION

宁波蓝野医疗器械有限公司  
NINGBO RUNYES MEDICAL INSTRUMENT CO., LTD.

徐步光

Rusting Prevention	Passivated
Ultrasonic cleaned	Yes
Usage	Right & Left hand
Test Performed	Boil Test, Performance Test, Shape Test
Packing	Pouches
Manufacturer	CE & ISO Certified
Tip	Detachable

**Features:-**

**1) ERGONOMIC DESIGN**

Well-balanced.

Smooth, comfortable style.

**2) MATERIAL**

Highly Harm-free Aircraft-Grade Aluminum

**3) OPERATION**

- Valve Core style button operation
- Left Button Controls the Water Flow Volume
- Right Button Controls the Air Flow Volume
- Pushing Both Buttons at the Same Time Generates Mist

**4) NOZZLES**

- Tips are constructed of solid alloy
- Precise control of air, water and spray

**5) RUST FREE**

Corrosion Resistant - Passivated

**6) DISINFECTION**

Nozzles is full autoclavable up to 134 °C / 273 °C

**Packaging:-**

宁波蓝野医疗器械有限公司  
NINGBO RUNYES MEDICAL INSTRUMENT CO.,LTD.

徐步光