



Labromed Laborator SRL <labromed.laborator@gmail.com>

Re: Re: TSWB- New product 400Kwh BESS

1 письмо

Jean @TSWB <winston777@thundersky-winston.com>
Кому: "Alexandr @MD-LL" <labromed.laborator@gmail.com>
Копия: comdept <comdept@thundersky-winston.com>

14 декабря 2024 г. в 02:40

Dear Alexandr,

I will make a project authorization to you later.
But pls note that the quality certificate shall be ready only when cargo ready, and operator's manual shall be down load on our website:
<https://en.winston-battery.com/static/upload/file/20210914/1631631798186525.pdf>
You may down load our company brochure at: <https://en.winston-battery.com/static/upload/file/20210520/1621489289205326.pdf>
Here is the data sheet of 100ah and 160ah cell in attachment.
Regards the voltage, the operation voltage for our cell is 2.7V-4.0V, for better use our cell, we make 2.8V-3.8V in data sheet.
You may find it in Operator's manual page 23.

One more thing, since it's shipment busy time, the sea freight will be high this month, and it shall down a bit in Jan.
Could you pls confirm how many pcs in series/paralleled? (last year, it's 160 pcs in series for 100ah, how about this year, and how about 160ah?) So that we can make the estimate packing list. I will ask forwarder to quote December price for you information later.

標準充放電
Standard Charge and Discharge

首次充放電 Charge/discharge setup for the first use.
新出廠的電池處於半荷電狀態，切勿直接使用！首次使用時必須將每個單體電池依照各類電池的特性設定充電極限。對電池充電，必須選擇匹配的專用充電器進行充電。
The new battery is in half electric charge condition, which can not be used directly! Before using the new battery for each new battery must charge according to each kind of battery's charge standard that is set by their characteristics. The battery must use the matched battery charger to charge.

	LVP 膠電池 LVP battery	LP 膠電池 LP battery
■ 充電最高電壓 The highest charge voltage	4.00V	18V
■ 充電最佳電流 The best charge current:	0.5CA	0.5CA
■ 放電最低電壓 The lowest discharge voltage	2.70V	11.0V
■ 放電最佳電流 The best discharge current:	0.5CA	0.5CA

當電池經過首次充放電後，可依照各類單體電池特性設定充放電電壓。
After initial charge and discharge, the user could set up the charge and discharge voltage according to each kind of battery's characteristics.

23

Thanks.

Best regards,

Jean Zheng
Ms. 郑锦

Commercial attache of Int'l Commerce Department
国际商务部专员

Thunder Sky Winston Battery Inc. Co., Ltd.

Mob: 86-15759101097; Tel: +86-596-8316202

E-mail: winston777@thundersky-winston.com

Website: <https://thundersky-winston.com> ; <https://en.winston-battery.com>