

D-Mic 40 SL

Directional Microphone, 40 cm



Description

The removable gooseneck microphone is equipped with a screw lock connector for easy connection to the different delegate and interpreter units.

Its unidirectional response results in optimal performance even in environments with a lot of ambient noise.

The gooseneck design also allows for a large freedom of movement. Another important advantage is the very low susceptibility to interference from mobile phones.

Finally, the D-MIC SL microphones deliver a rich, natural sound. It enables longer and more comfortable meetings where participants experience less strain produced by traditional artificial and mechanical microphone sounds. The light ring is dark (opaque) when the microphone is switched off, it lights up red when active, and green when in request.



To prevent any damage during transportation and storage, the microphones should always be handled in a horizontal position in their packaging.

Certification

Region	Certification
Europe	CE

Specifications

Mechanical	
Material	Brass
Color	Matt black, RAL 9011
Size (mm)	405 (w) × 25 (h) × 25 (d)
Size packed (mm)	480 (w) × 50 (h) × 50 (d)
Weight	100 g
Weight packed	175 g
Diameter of the stem	Flexible part: 8 mm Rigid part: 6.3 mm
Electrical	
Transducer principle	Back electret (condenser)
Operating principle	Pressure gradient
Polar pattern	Unidirectional, cardioid
Nominal conditions	Bias resistor = 1k2 Vdd = 3.3 V DC 1 Pa = 94 dB SPL
Max SPL @ 1 kHz	110 dB SPL (1% THD+N)
Signal to noise ratio	> 67 dB(A)
Free field sensitivity	(-40.5±2) dBV @ 1Pa, 1KHz
Power supply	3.3 V DC, 0.5 mA
Consumption	0.5 mA (without LED ring) Max 25 mA (with LED ring)
Connection	Screw lock
Environmental	
Operating temperature	5 to 45°C Humidity
Humidity	< 95%, >5%

